User Guide





HP OfficeJet 7110



HP Officejet 7110 Wide Format ePrinter

User Guide

Copyright information

© Copyright 2016 HP Development Company, I.P.

Edition 3, 8/2016

Hewlett-Packard Company notices

The information contained in this document is subject to change without notice.

All rights reserved. Reproduction, adaptation, or translation of this material is prohibited without prior written permission of Hewlett-Packard, except as allowed under copyright laws.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Acknowledgements

Microsoft, Windows, Windows XP, Windows Vista, Windows 7, and Windows 8 are U.S. registered trademarks of Microsoft Corporation.

ENERGY STAR and the ENERGY STAR mark are registered U.S. marks.

Safety information



Always follow basic safety precautions when using this product to reduce risk of injury from fire or electric shock.

- 1. Read and understand all instructions in the documentation that comes with the printer.
- 2. Observe all warnings and instructions marked on the product.
- 3. Unplug this product from wall outlets before cleaning.
- 4. Do not install or use this product near water, or when you are wet.
- 5. Install the product securely on a stable surface.
- 6. Install the product in a protected location where no one can step on or trip over the line cord, and the line cord cannot be damaged.
- 7. If the product does not operate normally, see <u>Maintain the printer on page 18</u>.
- 8. There are no user-serviceable parts inside. Refer servicing to qualified service personnel.

Table of contents

1 Ge	t started	
	Accessibility	2
	HP EcoSolutions (HP and the Environment)	3
	Manage Power	3
	Optimize Printing Supplies	3
	Understand the printer parts	5
	Front view	5
	Printing supplies area	5
	Control panel	6
	Back view	6
	Select print paper	8
	Recommended papers for printing	8
	Recommended papers for photo printing	9
	Tips for selecting and using paper	10
	Load paper	11
	Load standard-size paper	11
	Load envelopes	12
	Load cards and photo paper	12
	Load custom-size paper	13
	Turn the printer off	14
	Update the printer	15
	Install the accessories	16
	Install the automatic two-sided printing accessory (duplexer)	16
	Turn on accessories in the printer driver	16
	To turn on accessories (Windows)	16
	To turn on accessories on (Mac OS X)	16
	Maintain the printer	18
	Clean the exterior	18
	Restore factory defaults	18
	Open the HP printer software (Windows)	19

2 Pri	int	
	Print documents	20
	Print documents (Windows)	20
	Print documents (Mac OS X)	20
	Print brochures	21
	Print brochures (Windows)	21
	Print brochures (Mac OS X)	21
	Print on envelopes	23
	Print on envelopes (Windows)	23
	Print on envelopes (Mac OS X)	23
	Print photos	25
	Print photos on photo paper (Windows)	25
	Print photos on photo paper (Mac OS X)	25
	Print on special and custom-sized paper	27
	Print on special or custom-sized paper (Mac OS X)	27
	Set up custom sizes (Mac OS X)	27
	Print borderless documents or photos	29
	Print borderless documents or photos (Windows)	29
	Print borderless documents or photos (Mac OS X)	29
	Print on both sides (duplexing)	31
	Perform two-sided printing (Windows)	31
	Perform two-sided printing (Mac OS X)	31
	Tips for print success	32
3 HP	PePrint	34
	Set up HP ePrint	36
	Set up HP ePrint using the embedded web server	36
	Set up HP ePrint using the HP printer software	36
	Use HP ePrint	38
	Print using HP ePrint	38
	Find the printer's email address	38
	Turn off HP ePrint	38
	Remove Web Services	39
4 Wo	ork with ink cartridges	39
	Information on ink cartridges and the printhead	40
	Check the estimated ink levels	41
	Printing with black or color ink only	42
	Replace the ink cartridges	43
	Store printing supplies	45

roblem		•••••
HP support		
Ot	otain electronic support	
HF	support by phone	
	Before you call	
	Phone support period	
	Telephone support numbers	
	After the phone support period	
General troub	leshooting tips and resources	
Solve printer	problems	
Th	ne printer shuts down unexpectedly	
Al	ignment fails	
Th	ne printer is not responding (nothing prints)	
Th	ne printer prints slowly	
	Solution 1: Use a lower print quality setting	
	Solution 2: Check the ink levels	
	Solution 3: Contact HP support	
Th	ne printer is making some unexpected noises	
Bl	ank or partial page printed	
Sc	mething on the page is missing or incorrect	
Pl	acement of the text or graphics is wrong	
Print quality t	roubleshooting	
Sc	olution 1: Make sure you are using original HP ink cartridges	
Sc	olution 2: Check the ink levels	
Sc	olution 3: Check the paper loaded in the input tray	
Sc	olution 4: Check the paper type	
Sc	olution 5: Check the print settings	
Sc	olution 6: Print and evaluate a print quality report	
Sc	olution 7: Contact HP support	
Solve paper-f	eed problems	
Solve problen	ns using HP ePrint and HP websites	
Sc	olve problems using HP ePrint	
Sc	olve problems using HP websites	
Configure you	ır firewall software to work with the printer	
Solve printer	management problems	
Er	nbedded web server cannot be opened	
Solve networ	k problems	
Sc	olve Ethernet network problems	
Sc	olve wireless problems	

Basic wireless troubleshooting	70
Advanced wireless troubleshooting	71
Step 1: Make sure your computer is connected to your network	71
Step 2: Make sure that the printer is connected to your network	72
Step 3: Make sure your computer is not connected over a Virtual Private Network (VPN)	74
Step 4: Make sure the printer is online and ready	74
Step 5: Make sure the HP printer labeled (Network) is set as the default printer driver (Windows only)	75
Step 6: Check to see if the firewall software is blocking communicati	
After resolving the problems	
Reset the Printer Network Settings	76
Troubleshoot installation issues	77
Hardware installation suggestions	77
HP software installation suggestions	77
Understand the Printer Status Report	
Understand the network configuration page	81
Printhead maintenance	84
Clean the printhead	84
Align the printhead	85
Uninstall and reinstall the HP software	86
Clear jams	88
Clear paper jams	88
Avoid paper jams	89
Control panel lights reference	91
Appendix A Technical information	97
Warranty information	98
Hewlett-Packard limited warranty statement	
Ink cartridge warranty information	
Printer specifications	
Physical specifications	
Product features and capacities	
Processor and memory specifications	
System requirements	
Network protocol specifications	102
Embedded web server specifications	
Paper specifications	
Understand specifications for supported paper	
Understand supported sizes	103
Understand supported paper types and weights	

viii ENWW

	Set minimum margins	106
	Guidelines for printing on both sides of a page	107
	Print resolution	107
	HP ePrint and HP website specifications	108
	HP ePrint specifications	108
	HP website specifications	108
	Environmental specifications	109
	Electrical specifications	109
	Acoustic emission specifications	109
Regulato	ry information	110
	Regulatory model number	110
	FCC statement	111
	Notice to users in Korea	111
	VCCI (Class B) compliance statement for users in Japan	111
	Notice to users in Japan about the power cord	112
	Noise emission statement for Germany	112
	GS Declaration (Germany)	112
	European Union Regulatory Notice	112
	Regulatory information for wireless products	113
	Exposure to radio frequency radiation	113
	Notice to users in Brazil	114
	Notice to users in Canada	114
	Notice to users in Taiwan	115
	Notice to users in Mexico	115
	Notice to users in Japan	115
Environm	nental product stewardship program	116
	European Union Commission Regulation 1275/2008	116
	Paper use	116
	Plastics	116
	Material safety data sheets	117
	Recycling program	117
	HP inkjet supplies recycling program	117
	Disposal of waste equipment by users in private households in the European Union	118
	Power consumption	119
	Chemical Substances	119
	Battery information	119
	Battery disposal in Taiwan	119
	Attention California users	119
	Battery disposal in the Netherlands	
	RoHS notices (China only)	
	RoHS notices (Ukraine only)	120

	Third-party licenses	121
Append	lix B HP supplies and accessories	131
	Order printing supplies online	132
	Supplies	133
	Ink cartridges	133
	HP paper	133
Append	lix C Network setup	133
	Change basic network settings	135
	View and print network settings	135
	Turn the wireless radio on and off	135
	Change advanced network settings	136
	Set link speed	136
	View IP settings	136
	Change IP settings	136
	Reset network settings	137
	Set up the printer for wireless communication	138
	Before you begin	138
	Set up the printer on your wireless network	138
	Set up the printer using the HP printer software	139
	Set up the printer using WiFi Protected Setup (WPS)	139
	Set up the printer using the embedded web server (EWS)	140
	Change the connection type	140
	To change from an Ethernet connection to a wireless connection	
	To change from a USB connection to a wireless connection	141
	To change from a wireless connection to a USB or Ethernet connection	141
	Test the wireless connection	142
	Guidelines for ensuring wireless network security	142
	Overview of security settings	
	Add hardware addresses to a wireless router (MAC filtering)	
	To add hard addresses to a wireless router or wireless access point	
	Other wireless security guidelines	
	Guidelines for reducing interference on a wireless network	143
	HP wireless direct printing	144
	Turn on HP wireless direct printing	
	Print from a wireless-capable mobile device	145
	Print from a wireless-capable computer	
	Print from a wireless-capable computer (Windows)	
	Print from a wireless-capable computer (Mac OS X)	146

x ENWW

Appendix D Printer management tools	146
Toolbox (Windows)	147
Open the Toolbox	147
HP Utility (Mac OS X)	148
To open HP Utility	148
Embedded web server	149
About cookies	149
To open the embedded web server	149
Appendix E How do I?	150
Appendix F Errors (Windows)	150
Low on ink	
Cartridge Problem	153
Replace the ink cartridge	
Paper Mismatch	
The cartridge cradle cannot move	156
Paper Jam	
The printer is out of paper	158
Printer Offline	159
Printer Paused	160
Document failed to print	
Printer failure	
Door or cover open	
Previously used ink cartridge installed	
Ink cartridges depleted	165
Ink cartridge failure	166
Printer supply upgrade	167
Printer supply upgrade successful	168
Printer supply upgrade problem	169
Non-HP ink cartridges installed	170
Using Original HP Cartridges has its Rewards	171
Counterfeit Cartridge Advisory	172
Used, Refilled or Counterfeit Cartridge Detected	173
Use SETUP cartridges	174
Do not use SETUP cartridges	175
Not enough ink at startup	176
Use black ink only?	177
Use color ink only?	178
Incompatible ink cartridges	179

	Unable to Communicate with Printer	180
	Ink sensor failure	181
	Ink sensor warning	182
	Problem with printer preparation	183
	Color cartridge out of ink	. 184
	Black cartridge out of ink	185
	Problem with ink system	186
ndex		187

Get started

This guide provides details about how to use the printer and how to resolve problems.

- Accessibility
- **HP EcoSolutions (HP and the Environment)**
- **Understand the printer parts**
- Select print paper
- Load paper
- Turn the printer off
- Update the printer
- **Install the accessories**
- Maintain the printer
- Open the HP printer software (Windows)



NOTE: If you are using the printer with a computer running Windows XP Starter Edition, Windows Vista Starter Edition, Windows 7 Starter Edition, or Windows 8 Starter Edition, some features might not be available. For more information, see System requirements on page 102.

ENWW 1

Accessibility

The printer provides a number of features that make it accessible for people with disabilities.

Visual

The HP software provided with the printer is accessible for users with visual impairments or low vision by using your operating system's accessibility options and features. The software also supports most assistive technology such as screen readers, Braille readers, and voice-to-text applications. For users who are color blind, colored buttons and tabs used in the HP software have simple text or icon labels that convey the appropriate action.

Mobility

For users with mobility impairments, the HP software functions can be executed through keyboard commands. The HP software also supports Windows accessibility options such as StickyKeys, ToggleKeys, FilterKeys, and MouseKeys. The printer doors, buttons, paper trays, and paper guides can be operated by users with limited strength and reach.

Support

2

For more details about the accessibility of this printer and HP's commitment to product accessibility, visit HP's website at www.hp.com/accessibility.

For accessibility information for Mac OS X, visit the Apple website at www.apple.com/accessibility.

HP EcoSolutions (HP and the Environment)

Hewlett-Packard is committed to helping you optimize your environmental footprint and empowering you to print responsibly—at home or in the office.

For more detailed information about environmental guidelines HP follows during the manufacturing process, see Environmental product stewardship program on page 116. For more information about HP's environmental initiatives, visit www.hp.com/ecosolutions.

This section contains the following topics:

- Manage Power
- Optimize Printing Supplies

Manage Power

To conserve electricity, the printer comes with the following features:

Sleep mode

Power usage is reduced while in Sleep mode. After initial setup of printer, the printer will enter Sleep mode after 5 minutes of inactivity.

To change the setting, complete the following steps:

- 1. Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the **Settings** tab.
- 3. In the Power Management section, click Energy Save Mode and select the desired option.
- 4. Click Apply.

Auto- off

This feature turns the printer off after 2 hours of inactivity to help reduce energy use. Auto-Off turns the printer off completely, so you must use the Power button to turn the printer back on. If your printer supports this energy saving feature, Auto-Off is automatically enabled or disabled depending on printer capabilities and connection options. Even when Auto-Off is disabled, the printer enters Sleep mode after 5 minutes of inactivity to help reduce energy use.

- Auto-Off is enabled when the printer is turned on, if the printer does not have network, fax or Wi-Fi
 Direct capability, or is not using these capabilities.
- Auto-Off is disabled when a printer's wireless or Wi-Fi Direct capability is turned on or when a printer with fax, USB, or Ethernet network capability establishes a fax, USB, or Ethernet network connection.

Optimize Printing Supplies

To optimize printing supplies such as ink and paper, try the following:

- Recycle used original HP ink cartridges through HP Planet Partners. For more information, visit www.hp.com/recycle.
- Optimize paper usage by printing on both sides of the paper. If the printer has an HP automatic two-sided printing accessory (duplexer), see Print on both sides (duplexing) on page 31. Otherwise, you can first print just the odd pages, flip the pages over, and then print just the even pages.

- Save ink and paper when printing web content with HP Smart Print. For more information, visit www.hp.com/go/smartprint.
- Change the print mode to a draft setting. The draft setting uses less ink.
- Do not clean the printhead unnecessarily. Doing so wastes ink and shortens the life of the cartridges.

Understand the printer parts

This section contains the following topics:


- Front view
- Printing supplies area
- Control panel
- Back view

Front view



1 Ink cartridge access door
2 Input tray
3 Paper guides
4 Tray extender
5 Output tray
6 Power button (1) and light

Printing supplies area



1 Ink cartridge access door


- 2 Ink cartridges
- 3 Printhead assembly



NOTE: Printing supplies should be kept in the printer to prevent possible print quality issues or printhead damage. Avoid removing supplies for extended periods of time. Do not turn off the printer when a cartridge is missing.


Control panel

For more information, see Control panel lights reference on page 91.



- ePrint button 耐 and light
- 2 Ethernet light 🚣
- 3 Wireless button 🙌 and light
- 4 Network Information button 🌇
- 5 Cancel button X
- 6 Resume button 🚺 and light
- Alert light
- 8 Ink cartridge lights
- Power button (1) and light

Back view



1	USB port
2	Ethernet network port
3	Power input
4	Rear access panel

Select print paper

The printer is designed to work well with most types of office paper. It is best to test a variety of print paper types before buying large quantities. Use HP paper for optimum print quality. Visit the HP website at www.hp.com for more information about HP paper.



HP recommends plain papers with the ColorLok logo for printing everyday documents. All papers with the ColorLok logo are independently tested to meet high standards of reliability and print quality, and produce documents with crisp, vivid color, bolder blacks, and that dry faster than ordinary plain papers. Look for papers with the ColorLok logo in a variety of weights and sizes from major paper manufacturers.

This section contains the following topics:

- Recommended papers for printing
- Recommended papers for photo printing
- <u>Tips for selecting and using paper</u>

Recommended papers for printing

8

If you want the best print quality, HP recommends using HP papers that are specifically designed for the type of project you are printing.

Depending on your country/region, some of these papers might not be available.

HP Brochure Paper	These papers are glossy-coated or matte-coated on both sides for two-sided use. They are the perfect choice for producing professional quality marketing materials such as brochures and
HP Professional Paper	mailers, as well as business graphics for report covers and calendars.
HP Brochure and Flyer Paper	
HP Tri-fold Brochure Paper	
HP Premium Presentation Paper	These papers are heavy two-sided matte papers perfect for presentations, proposals, reports, and newsletters. They are heavyweight for an impressive look and feel.
HP Professional Paper	newstetters. They are neavyweight for all impressive took and reet.
HP Bright White Inkjet Paper	HP Bright White Inkjet Paper delivers high-contrast colors and sharp text. It is opaque enough for two-sided color usage with no showthrough, which makes it ideal for newsletters, reports, and flyers. It features ColorLok Technology for less smearing, bolder blacks, and vivid colors.
HP Printing Paper	HP Printing Paper is a high-quality multifunction paper. It produces documents that look and feel more substantial than documents printed on standard multipurpose or copy paper. It features ColorLok Technology for less smearing, bolder blacks, and vivid colors.
HP Office Paper	HP Office Paper is a high-quality multifunction paper. It is suitable for copies, drafts, memos and other everyday documents. It features ColorLok Technology for less smearing, bolder blacks, and vivid colors.
HP Office Recycled Paper	HP Office Recycled Paper is a high-quality multifunction paper made with 30% recycled fiber. It features ColorLok Technology for less smearing, bolder blacks, and vivid colors.

HP Premium Plus Photo Paper	HP's best photo paper is heavyweight for producing professional quality photos. Features an instant-dry finish for easy handling without smudging. It resists water, smears, fingerprints, and humidity. It is available in several sizes, including A4, 8.5 x 11 inch, 10 x 15 cm (4 x 6 inch), 13 x 18 cm (5 x 7 inch), and two finishes – glossy or soft-gloss (satin matte). It is acid-free for longer lasting documents.
HP Advanced Photo Paper	This thick photo paper features an instant-dry finish for easy handling without smudging. It resists water, smears, fingerprints, and humidity. Your prints have a look and feel comparable to a store processed photo. It is available in several sizes, including A4, 8.5 x 11 inch, 10 x 15 cm (4 x 6 inch), 13x18 cm (5 x7 inch), A3, and two finishes – glossy or soft-gloss (satin matte). It is acid-free for longer lasting documents.
HP Everyday Photo Paper	Print colorful, everyday snapshots at a low cost, using paper designed for casual photo printing. This affordable photo paper dries quickly for easy handling. Get sharp, crisp images when you use this paper with any inkjet printer. Available in semi-gloss finish in 8.5 \times 11 inch, A4, 4 \times 6 inch, and 10 \times 15 cm. It is acid-free for longer lasting documents.

To order HP papers and other supplies, go to www.hp.com . Go to Shop for Products & Services, and select Ink & Toner .



NOTE: At this time, some portions of the HP website are available in English only.

Recommended papers for photo printing

For the best print quality, HP recommends using HP papers that are specifically designed for the type of project you are printing.

Depending on your country/region, some of these papers might not be available.

HP Premium Plus Photo Paper	HP's best photo paper is heavyweight for producing professional quality photos. Features an instant-dry finish for easy handling without smudging. It resists water, smears, fingerprints, and humidity. It is available in several sizes, including A4, 8.5×11 inch, 10×15 cm (4×6 inch), 13×18 cm (5×7 inch), and two finishes – glossy or soft-gloss (satin matte). It is acid-free for longer lasting documents.
HP Advanced Photo Paper	This thick photo paper features an instant-dry finish for easy handling without smudging. It resists water, smears, fingerprints, and humidity. Your prints have a look and feel comparable to a store processed photo. It is available in several sizes, including A4, 8.5 x 11 inch, $10 \times 15 \text{ cm}$ (4 x 6 inch), $13 \times 18 \text{ cm}$ (5 x7 inch), A3, and two finishes – glossy or soft-gloss (satin matte). It is acid-free for longer lasting documents.
HP Everyday Photo Paper	Print colorful, everyday snapshots at a low cost, using paper designed for casual photo printing. This affordable, photo paper dries quickly for easy handling. Get sharp, crisp images when you use this paper with any inkjet printer. Available in semi-gloss finish in 8.5 x 11 inch, A4, 4 x 6 inch, and 10 x 15 cm. It is acid-free for longer lasting documents.
HP Photo Value Packs	HP Photo Value Packs conveniently package original HP ink cartridges and HP Advanced Photo Paper to save you time and take the guesswork out of printing affordable, lab-quality photos with your HP printer. Original HP inks and HP Advanced Photo Paper have been designed to work together so your photos are long lasting and vivid, print after print. Great for printing out an entire vacation's worth of photos or multiple prints to share.

To order HP papers and other supplies, go to www.hp.com. Go to Shop for Products & Services and select Ink & Toner .



NOTE: At this time, some portions of the HP website are available in English only.

ENWW Select print paper

9

Tips for selecting and using paper

For the best results, observe the following guidelines.

- Always use paper that conforms to the printer specifications. For more information, see <u>Paper specifications on page 102</u>.
- Load only one type of paper at a time into a tray.
- When loading the trays, make sure the paper is loaded correctly. For more information, see <u>Load paper</u> on page 11.
- Do not overload the tray. For more information, see <u>Load paper on page 11</u>.
- To prevent jams, poor print quality, and other printing problems, avoid loading the following paper in the trays:
 - Multipart forms
 - Media that is damaged, curled, or wrinkled
 - Media with cutouts or perforations
 - Media that is heavily textured, embossed, or does not accept ink well
 - Media that is too lightweight or stretches easily
 - Media that contains staples or clips

Load paper

This section provides instructions for loading paper into the printer.


- Load standard-size paper
- Load envelopes
- Load cards and photo paper
- Load custom-size paper

Load standard-size paper


Use these instructions to load standard—size paper.

- **1.** Lift the output tray.
- **2.** Slide the paper guides out as far as possible.
 - **NOTE:** If the paper is too long, pull the input tray to extend it.
- 3. Load the paper in portrait orientation and with the side to be printed facing down.

Make sure the stack of paper aligns with the right and back edges of the tray and does not exceed the line marking in the tray.



- **NOTE:** Do not load paper while the printer is printing.
- 4. Slide the paper guides in the tray to adjust them for the paper size that you have loaded.
- **5.** Lower the output tray.
- **6.** Pull out the output tray extension.




ENWW Load paper 11

Load envelopes


Use these instructions to load envelopes.

- 1. Lift the output tray.
- **2.** Slide the paper guides out as far as possible.
- 3. Insert the envelopes print-side down and load according to the graphic.

Make sure the stack of envelopes does not exceed the line marking in the tray.



- **NOTE:** Do not load paper envelopes while the printer is printing.
- **4.** Slide the paper guides in the tray to adjust them for the envelope size that you have loaded.
- **5.** Lower the output tray.
- **6.** Pull out the output tray extension.



Load cards and photo paper


Use these instructions to load cards and photo paper.

- **1.** Lift the output tray.
- **2.** Slide the paper guides out as far as possible.
- 3. Insert the paper print-side down along the right edge of the main tray.

Make sure the stack of paper aligns with the right and back edges of the tray and does not exceed the line marking in the tray. If the photo paper has a tab along one edge, make sure the tab is pointing towards the front of the printer.

- **NOTE:** Do not load cards or photo paper while the printer is printing.
- 4. Slide the paper guides in the tray to adjust them for the paper size that you have loaded.

- **5.** Lower the output tray.
- **6.** Pull out the output tray extension.



Load custom-size paper


Use these instructions to load custom-size paper.

CAUTION: Use only custom-size paper that is supported by the printer. For more information, see <u>Paper specifications on page 102</u>.

- 1. Lift the output tray.
- **2.** Slide the paper guides out as far as possible.
- **3.** Insert the paper print-side down along the right of the main tray.

Make sure the stack of paper aligns with the right and back edges of the tray, and does not exceed the line marking in the tray.

- **NOTE:** Do not load paper while the printer is printing.
- **4.** Slide the paper guides in the tray to adjust them for the paper size that you have loaded.
- **5.** Lower the output tray.
- **6.** Pull out the output tray extension.



ENWW Load paper 13

Turn the printer off

Always turn off the printer by pressing the () (Power) button located on the printer. Wait until the power light turns off before unplugging the power cord or turning off a power strip.

CAUTION: If you incorrectly turn the printer off, the print carriage might not return to the correct position, causing printhead problems and print quality issues.

CAUTION: HP recommends that you replace any missing cartridges as soon as possible to avoid print quality issues, possible extra ink usage, or damage to the ink system. Never turn off the printer when ink cartridges are missing.

Update the printer

HP is always working to improve the performance of its printers and bring you the latest features. If the printer is connected to a network and Web Services has been enabled, you can check for and install printer updates.

To update the printer, complete the following steps:

- 1. Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the Web Services tab.
- In the Web Services Settings section, click Product Update, click Check Now, and follow the on-screen instructions.
- **4.** If the printer update option is not available, follow these instructions:
 - In the Web Services Settings section, click Setup, click Continue, and follow the on-screen instructions.
 - **b.** If prompted, choose to allow the printer to check for and install printer updates.
- **NOTE:** If a printer update is available, the printer downloads and installs the update, and then restarts.
- **NOTE:** If prompted for proxy settings and if your network uses proxy settings, follow the on-screen instructions to set up a proxy server. If you do not have the details, contact your network administrator or the person who set up the network.

ENWW Update the printer 1

Install the accessories

This section contains the following topics:


- Install the automatic two-sided printing accessory (duplexer)
- Turn on accessories in the printer driver

Install the automatic two-sided printing accessory (duplexer)

You can print on both sides of a sheet of paper automatically. For information on using the duplexer, see <u>Print</u> on both sides (duplexing) on page 31.

To install the duplexer:

Slide the duplexer into the back of the printer until the unit locks into place. Do not press the buttons on either side of the duplexer when installing the unit; use them only for removing the unit from the printer.



Turn on accessories in the printer driver

- <u>To turn on accessories (Windows)</u>
- To turn on accessories on (Mac OS X)

To turn on accessories (Windows)

- 1. Click Start, and then click Printers, Printers and Faxes, or Devices and Printers.
 - Or -

Click Start, click Control Panel, and then double-click Printers.

- Or -

On the Start screen, click Control Panel, and then click View devices and printers.

- **2.** Right-click the printer icon, and then click **Properties**.
- **3.** Select the **Device Settings** tab. Click the accessory that you want to turn on, click **Installed** from the drop-down menu, and then click **OK**.

To turn on accessories on (Mac OS X)

Mac OS X automatically turns on all accessories in the printer driver when you install the printer software. If you add a new accessory later, follow these steps:

- 1. Open the **System Preferences** and then select **Print & Fax** or **Print & Scan**.
- **2.** Select the printer from list of printers, and then click **Options & Supplies**.
- 3. Click the **Driver** tab.
- **4.** Select the options you want to install, and then click **OK**.

ENWW Install the accessories 17

Maintain the printer

This section provides instructions for keeping the printer in top working condition. Perform these maintenance procedures as necessary.

- <u>Clean the exterior</u>
- Restore factory defaults

Clean the exterior

WARNING! Before cleaning the printer, turn off the power and unplug the power cord from the electrical socket.

Use a soft, damp, lint-free cloth to wipe dust, smudges, and stains off of the case. Keep fluids away from the interior of the printer, as well as from the printer control panel.

Restore factory defaults

This section provides instructions about how to restore your printer back to the factory defaults.

▲ On the printer control panel, press and hold the (Resume) button and the (1) (Wireless) button, approximately five seconds, and then release the buttons.

Open the HP printer software (Windows)

Open the HP printer software by doing one of the following:

- From the computer desktop, click Start, select Programs or All Programs, click HP, click the folder for the printer, and then select the icon with the printer's name.
- On the Start screen, right-click an empty area on the screen, click All Apps on the app bar, and then click the icon with the printer's name.

Print

Most print settings are automatically handled by the software application. Change the settings manually only when you want to change print quality, print on specific types of paper, or use special features. For more information, see Select print paper on page 8.

Choose a print job to continue:

P	Print documents on page 20
	Print brochures on page 21
\bowtie	Print on envelopes on page 23
	Print photos on page 25
	Print on special and custom-sized paper on page 27
	Print borderless documents or photos on page 29

Print documents

Follow the instructions for your operating system.

- Print documents (Windows)
- Print documents (Mac OS X)
- **TIP:** This printer includes HP ePrint, a free service from HP that allows you to print documents on your HP ePrint-enabled printer anytime, from any location, without any additional software or printer drivers. For more information, see Use HP ePrint on page 38.

Print documents (Windows)

- **1.** Load paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. On the **File** menu in your software application, click **Print**.
- **3.** Make sure the printer you want to use is selected.
- **4.** To change settings, click the button that opens the **Properties** dialog box.

Depending on your software application, this button might be called **Properties**, **Options**, **Printer Setup**, **Printer**, or **Preferences**.

5. Change the paper orientation on the **Layout** tab, and paper source, media type, paper size, and quality settings on the **Paper/Quality** tab.

To print in black and white, click the **Advanced** button, and then select **Black Ink Only** from the **Print in Grayscale** drop-down list under **Printer Features**.

- 6. Click OK.
- 7. Click **Print** or **OK** to begin printing.

Print documents (Mac OS X)

- 1. Load paper in the tray. For more information, see Load paper on page 11.
- 2. From the File menu in your software application, click Print.
- **3.** Make sure the printer you want to use is selected in the **Format For** pop-up menu.

If you do not see print options in the **Print** dialog, do the following:

- **Mac OS X v10.6**: Click the blue disclosure triangle next to the printer selection.
- OS X Lion: Click Show Details.
- **4.** Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

5. Click Print.


20 Chapter 2 Print ENWW

Print brochures

Follow the instructions for your operating system.

- Print brochures (Windows)
- Print brochures (Mac OS X)
- TIP: This printer includes HP ePrint, a free service from HP that allows you to print documents on your HP ePrint-enabled printer anytime, from any location, without any additional software or printer drivers. For more information, see <u>Use HP ePrint on page 38</u>.

Print brochures (Windows)



- **1.** Load paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. On the File menu in your software application, click Print.
- **3.** Make sure the printer you want to use is selected.
- **4.** To change settings, click the button that opens the **Properties** dialog box.

Depending on your software application, this button might be called **Properties**, **Options**, **Printer Setup**, **Printer**, or **Preferences**.

5. Change the paper orientation on the **Layout** tab, and paper source, media type, paper size, and quality settings on the **Paper/Quality** tab.

To print in black and white, click the **Advanced** button, and then select **Black Ink Only** from the **Print in Gravscale** drop-down list under **Printer Features**.

- 6. Click OK.
- 7. Click **Print** or **OK** to begin printing.

Print brochures (Mac OS X)

- 1. Load paper in the tray. For more information, see Load paper on page 11.
- 2. From the File menu in your software application, click Print.
- **3.** Make sure the printer you want to use is selected in the **Format For** pop-up menu.

If you do not see print options in the **Print** dialog, do the following:

- Mac OS X v10.6: Click the blue disclosure triangle next to the printer selection.
- OS X Lion: Click Show Details .
- **4.** Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

5. Click **Paper Type/Quality** from the pop-up menu, and then select the following settings:

ENWW Print brochures 21

- **Paper Type:** The appropriate brochure paper type
- Quality: Normal or Best
- **6.** Select any other print settings that you want, and then click **Print** to begin printing.

22 Chapter 2 Print ENWW

Print on envelopes

Avoid envelopes with the following characteristics:

- Very slick finish
- Self-stick adhesives, clasps, or windows
- Thick, irregular, or curled edges
- Areas that are wrinkled, torn, or otherwise damaged

Make sure the folds of envelopes you load in the printer are sharply creased.

NOTE: For more information about printing on envelopes, see the documentation available with the software program you are using.

Follow the instructions for your operating system.

- Print on envelopes (Windows)
- Print on envelopes (Mac OS X)

Print on envelopes (Windows)

- Load envelopes print-side down in the tray. For more information, see Load paper on page 11. 1.
- 2. On the File menu in your software application, click Print.
- Make sure the printer you want to use is selected. 3.
- To change settings, click the button that opens the **Properties** dialog box.

Depending on your software application, this button might be called **Properties**, **Options**, **Printer Setup**, **Printer**, or **Preferences**.

- On the **Layout** tab, change the orientation to **Landscape**.
- Click Paper/Quality, and then select the appropriate envelope type from the Paper Size drop-down list.
 - **TIP:** You can change more options for the print job by using the features available on the other tabs in the dialog box.
- Click **OK**, and then click **Print** or **OK** to begin printing.

Print on envelopes (Mac OS X)

- Load envelopes print-side down in the tray. For more information, see Load paper on page 11.
- From the File menu in your software application, click Print. 2.
- Make sure the printer you want to use is selected in the **Format For** pop-up menu.

If you do not see print options in the **Print** dialog, do the following:

- **Mac OS X v10.6**: Click the blue disclosure triangle next to the printer selection.
- **OS X Lion**: Click **Show Details**.

ENWW Print on envelopes 23 **4.** Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

- **5.** Select the **Orientation** option.
- **6.** Select any other print settings that you want, and then click **Print** to begin printing.

24 Chapter 2 Print ENWW

Print photos

Do not leave unused photo paper in the input tray. The paper might start to curl, which could impair the quality of your printout. Photo paper should be flat before printing.

Follow the instructions for your operating system.

- Print photos on photo paper (Windows)
- Print photos on photo paper (Mac OS X)
- **TIP:** This printer includes HP ePrint, a free service from HP that allows you to print documents on your HP ePrint-enabled printer anytime, from any location, and without any additional software or printer drivers. For more information, see Use HP ePrint on page 38.

Print photos on photo paper (Windows)

- **1.** Load paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. On the **File** menu in your software application, click **Print**.
- **3.** Make sure the printer you want to use is selected.
- **4.** To change settings, click the option that opens the printer **Properties** dialog box.

Depending on your software application, this option might be called **Properties**, **Options**, **Printer Setup**, **Printer**, or **Preferences**.

- 5. On the **Paper/Quality** tab, select the appropriate photo paper type from the **Media** drop-down menu.
 - NOTE: Maximum DPI is only supported for color printing on HP Premium Plus Photo Papers and HP Advanced Photo Papers.
- Click Advanced, and then select Best or Maximum DPI from the Output Quality drop-down menu.
- 7. To print the photo in black and white, click the **Print in Grayscale** drop-down menu, and then select one of the following options:
 - High-Quality Grayscale: uses all the available colors to print your photo in grayscale. This creates smooth and natural shades of gray.
- 8. Click **OK**, and then click **Print** or **OK** to begin printing.

Print photos on photo paper (Mac OS X)

- 1. Load photo paper print-side down in the tray. For more information, see Load paper on page 11.
- **2.** From the **File** menu in your software application, click **Print**.
- **3.** Make sure the printer you want to use is selected.

If you do not see print options in the **Print** dialog, do the following.

- Mac OS X v10.6: Click the blue disclosure triangle next to the printer selection.
- OS X Lion: Click Show Details.

ENWW Print photos 25

4. Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

- **5.** Click **Paper Type/Quality** from the pop-up menu, and then select the following settings:
 - **Paper Type:** The appropriate photo paper type
 - Quality: Best or Maximum dpi
- **6.** If necessary, change the photo and color options:
 - a. Click the disclosure triangle beside Color Options and select the appropriate Photo Fix options:
 - Off: Applies no automatic adjustments to the image.
 - **Basic:** Automatically focuses the image; moderately adjusts image sharpness.
 - **b.** To print the photo in black and white, click **Grayscale** from the **Color** pop-up menu, and then select one of the following options:
 - **High Quality:** Uses all the available colors to print your photo in grayscale. This creates smooth and natural shades of gray.
- 7. Select any other print settings that you want, and then click **Print** to begin printing.

26 Chapter 2 Print ENWW

Print on special and custom-sized paper

If your application supports custom-sized paper, set the size in the application before printing the document. If not, set the size in the printer driver. You might need to reformat existing documents to print them correctly on custom-sized paper.

Use only custom-sized paper that is supported by the printer. For more information, see <u>Paper specifications</u> on page 102.

NOTE: Defining custom-sized paper sizes is only available in the HP printing software in Mac OS X.

- Print on special or custom-sized paper (Mac OS X)
- Set up custom sizes (Mac OS X)

Print on special or custom-sized paper (Mac OS X)

NOTE: Before you can print on custom-sized paper, you must set up the custom sizes in the HP software provided with the printer. For instructions, see <u>Set up custom sizes</u> (Mac OS X) on page <u>27</u>.

- 1. Load the appropriate paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. From the File menu in your software application, click Print.
- 3. Make sure the printer you want to use is selected in the Format For pop-up menu.

If you do not see print options in the **Print** dialog, do the following:

- **Mac OS X v10.6**: Click the blue disclosure triangle next to the printer selection.
- OS X Lion: Click Show Details.
- **4.** Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

- 5. Click **Paper Handling** from the pop-up menu.
- **6.** Under **Destination Paper Size**, click **Scale to fit paper size**, and then select the custom size.
- **7.** Select any other print settings that you want, and then click **Print** to begin printing.

Set up custom sizes (Mac OS X)

- **1.** Load paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. From the **File** menu in your software application, click **Page Setup**, and then make sure the printer you want to use is selected in the **Format For** pop-up menu.
 - OR -

From the **File** menu in your software application, click **Print**, and then make sure the printer you want to use is selected.

3. Select Manage Custom Sizes in the Paper Size pop-up menu.

- NOTE: If you do not see these options in the **Print** dialog, click the disclosure triangle next to the Printer pop-up menu or click Show Details.
- Click the + on the left side of the screen, double-click **Untitled**, and type a name for the new custom size.
- In the **Width** and **Height** boxes, type the dimensions, and then set the margins, if you want to customize
- 6. Click OK.

ENWW 28 Chapter 2 Print

Print borderless documents or photos

Borderless printing lets you print to the edges of certain photo media types and a range of standard media sizes.

Before printing, open the file and make sure the size of the document or image matches the size of the media loaded in the printer.

NOTE: Borderless printing is only available in some applications.

Follow the instructions for your operating system.

- Print borderless documents or photos (Windows)
- Print borderless documents or photos (Mac OS X)

Print borderless documents or photos (Windows)

- Load paper in the tray. For more information, see <u>Load paper on page 11</u>.
- 2. On the File menu in your software application, click Print.
- 3. Make sure the printer you want to use is selected.
- To change settings, click the button that opens the **Properties** dialog box.

Depending on your software application, this button might be called **Properties**, **Options**, **Printer Setup**, **Printer**, or **Preferences**.

- 5. Click the **Paper/Quality** tab, and then click the **Advanced** button.
- 6. In the **Borderless Printing** option, click **Print Borderless**, and then click the **OK** button.
- 7. In the **Media** drop-down list, select the appropriate paper type.
- Click **OK**, and then click **Print** or **OK** to begin printing.

Print borderless documents or photos (Mac OS X)

- Load paper in the tray. For more information, see Load paper on page 11.
- 2. From the **File** menu in your software application, click **Print**.
- Make sure the printer you want to use is selected. 3.

If you do not see print options in the **Print** dialog, do the following.

- **Mac OS X v10.6**: Click the blue disclosure triangle next to the printer selection.
- **OS X Lion**: Click **Show Details**.
- Select a paper size from the pop-up menu.

If the Paper Size pop-up menu is not in the Print dialog, click the Page Setup button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

Click **Paper Type/Quality** from the pop-up menu, and then select the following settings:

- Paper Type: The appropriate paper type
- Quality: Best or Maximum dpi
- NOTE: If you do not see these options, click the disclosure triangle next to the **Printer** pop-up menu or click **Show Details**.
- **6.** Make sure the **Print Borderless** check box is selected.
- **7.** If necessary, click the disclosure triangle beside **Color Options** and select the appropriate **Photo Fix** options:
 - **Off:** Applies no automatic adjustments to the image.
 - Basic: Automatically focuses the image; moderately adjusts image sharpness.
- **8.** Select any other print settings that you want, and then click **Print** to begin printing.

30 Chapter 2 Print ENWW

Print on both sides (duplexing)

You can print on both sides of a sheet of media automatically by using the automatic two-sided printing accessory (duplexer).

- **NOTE:** Two-sided printing requires an automatic two-sided printing accessory (duplexer) to be installed on the printer.
- **NOTE:** You can perform manual duplexing by first printing only the odd pages, flipping the pages over, and then printing only the even pages.
- **TIP:** If the top and bottom margins in your document are smaller than 16 mm (0.63 inches), the document might not print out correct.
 - Perform two-sided printing (Windows)
 - Perform two-sided printing (Mac OS X)

Perform two-sided printing (Windows)

- 1. Load the appropriate media. For more information, see Load paper on page 11.
- **2.** Make sure the duplexer is installed correctly. For more information, see <u>Install the automatic two-sided</u> printing accessory (duplexer) on page 16.
- 3. With a document open, click **Print** on the **File** menu, and then under the **Print on Both Sides** options on the **Layout** tab, select either **Flip on Long Edge** or **Flip on Short Edge**.
- 4. Change any other settings, and then click **OK** .
- **5.** Print your document.

Perform two-sided printing (Mac OS X)

- 1. Load the appropriate media. For more information, see Load paper on page 11.
- **2.** Make sure the duplexer is installed correctly. For more information, see <u>Install the automatic two-sided</u> printing accessory (duplexer) on page 16.
- 3. From the **File** menu in your software application, click **Print**.
- **4.** Make sure the printer you want to use is selected in the **Format For** pop-up menu.

If you do not see print options in the **Print** dialog, do the following:

- **Mac OS X v10.6**: Click the blue disclosure triangle next to the printer selection.
- OS X Lion: Click Show Details .
- **5.** Select a paper size from the pop-up menu.

If the **Paper Size** pop-up menu is not in the **Print** dialog, click the **Page Setup** button. When you are done selecting the paper size, click **OK** to close **Page Setup** and return to the **Print** dialog.

- **6.** Click the **Layout** pop-up menu, and then select the appropriate binding options for the document from the **Two-Sided** pop-up menu.
- Select any other print settings that you want, and then click Print to begin printing.

Tips for print success

For good printing experience, HP ink cartridges should be correctly installed, have sufficient ink, and working properly; and paper should be properly loaded with correct print settings.

Ink tips

- If the print quality is not acceptable, see <u>Print quality troubleshooting on page 57</u> for more information.
- Use original HP ink cartridges.
- Install both the black and color cartridges correctly.
 - For more information, see Replace the ink cartridges on page 43.
- Check the estimated ink levels in the cartridges to make sure there is sufficient ink.
 - For more information, see Check the estimated ink levels on page 41.
- Always turn off the printer with (1) (the Power button) to allow the printer to protect the nozzles.

Paper loading tips

For more information, also see Load paper on page 11.

- Load a stack of paper (not just one page). All the paper in the stack should be of the same size and type to avoid a paper jam.
- Load paper with the print-side down in the main tray.
- Ensure that paper loaded in the input tray lays flat and the edges are not bent or torn.
- Adjust the paper-width guides in the input tray to fit snugly against all paper. Make sure the guides do not bend the paper in the tray.

Printer settings tips (Windows)

 To change default print settings, click Set Preferences under Print, Scan & Fax in the HP printer software.

For more information to open the printer software, see <u>Open the HP printer software (Windows)</u> <u>on page 19</u>.

- To select the number of pages to print per sheet, on the **Layout** tab of the printer driver, select the appropriate option from the **Pages per Sheet** drop-down list.
- If you want to change the page orientation, set it in your application interface.
- To view more printing settings, on the **Layout** or **Paper/Quality** tab of the printer driver, click the **Advanced** button to open the **Advanced Options** dialog box.

32 Chapter 2 Print ENWW

- Print in Grayscale: Allows you to print a black and white document using the black ink only. Select
 Black ink Only, and then click the OK button.
- Pages per Sheet Layout: Helps you specify the order of the pages if you print document in more than two pages per sheet.
- NOTE: The preview on the Layout tab cannot reflect what you select from the Pages per Sheet Layout drop-down list.
- Borderless Printing: Select this feature to print photos without border. Not all paper types support
 this feature. You will see an alert icon beside the option if the selected paper type in the Media
 drop-down list does not support it.
- Preserve Layout: This feature only works with the duplex printing. If the image is larger than the
 printable area, select this feature to scale the page content to be within the smaller margins so
 that extra pages are not created.
- HP Real Life Technologies: This feature smooths and sharpens images and graphics for improved print quality.
- Booklet: Allows you to print multiple-page document as a booklet. It places two pages on each side
 of a sheet that can then be folded into a booklet in half size of the paper. Select a binding method
 from the drop-down list, and then click **OK**.
 - Booklet-LeftBinding: The binding side after folded into a booklet appears at the left side.
 Select the option if your reading habit is from left to right.
 - Booklet-RightBinding: The binding side after folded into a booklet appears at the right side.
 Select the option if your reading habit is from right to left.
 - NOTE: The preview on the **Layout** tab cannot reflect what you select from the **Booklet** dropdown list.
- Page Borders: Allows you to add the borders to the pages if you print the document with two or more pages per sheet.
- **NOTE:** The preview on the **Layout** tab cannot reflect what you select from the **Page Borders** drop-down list.
- You can use printing shortcut to save setting time. A printing shortcut stores the setting values that are
 appropriate for a particular kind of job, so that you can set all the options with a single click. To use it, go
 to the **Printing Shortcut** tab, select one printing shortcut, and then click **OK**.

To add a new printing shortcut, after making settings on the **Layout** or **Paper/Quality** tab, click the **Printing Shortcut** tab, click **Save As** and enter a name, and then click **OK**.

To delete a printing shortcut, select it, and then click **Delete**.

NOTE: You cannot delete the default printing shortcuts.


ENWW Tips for print success 33

Printer settings tips (OS X)

- On the Print dialog, use the Paper Size pop-up menu to select the size of paper loaded in the printer.
- On the Print dialog, choose the **Paper Type/Quality** pop-up menu and select the appropriate paper type and quality.
- To print a black and white document using only black ink, choose the Paper Type/Quality from the popup menu and choose Grayscale from the Color pop-up menu.

Notes

• Original HP ink cartridges are designed and tested with HP printers and papers to help you easily produce great results, time after time.



If you believe you purchased original HP ink cartridges, go to:

www.hp.com/go/anticounterfeit

- Ink level warnings and indicators provide estimates for planning purposes only.
- **NOTE:** When you receive a low-ink warning message, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace the cartridges until print quality becomes unacceptable.
- Software settings selected in the print driver only apply to printing, they do not apply to copying or scanning.
- You can print your document on both sides of the paper.

3 HP ePrint

HP ePrint is a free service from HP that allows you to print to your HP ePrint-enabled printer anywhere you can send an email. Just send your documents and photos to the email address assigned to your printer when you enable Web Services. No additional drivers or software are needed.

Once you have signed up for an account on ePrintCenter (www.eprintcenter.com), you can sign in to view your HP ePrint job status, manage your HP ePrint printer queue, control who can use your printer's HP ePrint email address to print, and get help for HP ePrint.

NOTE: To use HP ePrint, the printer must be connected to an active network providing Internet access. You cannot use these web features if the printer is connected using a USB cable.

This section contains the following topics:

34 Chapter 3 HP ePrint ENWW

- Set up HP ePrint
- <u>Use HP ePrint</u>
- Remove Web Services

ENWW 35

Set up HP ePrint

To set up HP ePrint, use one of the following methods:

NOTE: Before you set up HP ePrint, make sure your printer is connected using either an Ethernet or wireless connection.

- Set up HP ePrint using the embedded web server
- Set up HP ePrint using the HP printer software

Set up HP ePrint using the embedded web server

You can use the printer embedded web server (EWS) to set up and manage HP ePrint.

To set up HP ePrint, complete the following steps:

- 1. Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the Web Services tab.
- **3.** In the **Web Services Settings** section, click **Setup**, click **Continue**, and follow the on-screen instructions to accept the terms of use.
- **4.** If prompted, choose to allow the printer to check for and install printer updates.
 - **NOTE:** If a printer update is available, the printer downloads and installs the update, and then restarts. Repeat the instructions from step 1 to set up HP ePrint.
 - **NOTE:** If prompted for proxy settings and if your network uses proxy settings, follow the on-screen instructions to set up a proxy server. If you do not have the proxy details, contact your network administrator or the person who set up the network.
- **5.** When the printer is connected to the server, the printer prints an information page. Follow the instructions on the information page to finish the setup.

Set up HP ePrint using the HP printer software

If you do not set up HP ePrint when you installed the HP software on your computer, you can still use the software to set up HP ePrint.

To set up HP ePrint, complete the following steps for your operating system:

Windows

- **1.** Open the HP printer software. For more information, see <u>Open the HP printer software (Windows)</u> on page 19.
- 2. In the window that appears, select **Print, Scan & Fax**, and then select **ePrint Setup** under **Print**. The printer's embedded web server opens.
- 3. Click the Web Services tab.
- **4.** In the **Web Services Settings** section, click **Setup**, click **Continue**, and follow the on-screen instructions to accept the terms of use.
- 5. If prompted, choose to allow the printer to check for and install printer updates.

36 Chapter 3 HP ePrint ENWW

- **NOTE:** If a printer update is available, the printer will download and install the update, and then restart. You will have to repeat the instructions from step 1 to set up HP ePrint.
- **NOTE:** If prompted for proxy settings and if your network uses proxy settings, follow the on-screen instructions to set up a proxy server. If you do not have the proxy details, contact your network administrator or the person who set up the network.
- **6.** When the printer is connected to the server, the printer prints an information page. Follow the instructions on the information page to finish the setup.

Mac OS X

To set up and manage Web Services in Mac OS X, you can use the printer's embedded web server (EWS). For more information, see <u>Set up HP ePrint using the embedded web server on page 36</u>.

ENWW Set up HP ePrint 37

Use HP ePrint

To use HP ePrint, make sure to have the following:

- An Internet- and email-capable computer or mobile device
- An HP ePrint-capable printer on which Web Services has been enabled
- **TIP:** For more information about managing and configuring HP ePrint settings and to learn about the latest features, visit ePrintCenter (<u>www.eprintcenter.com</u>).
 - Print using HP ePrint
 - Find the printer's email address
 - Turn off HP ePrint

Print using HP ePrint

To print documents using HP ePrint, complete the following steps:

- **1.** On your computer or mobile device, open your email application.
 - **NOTE:** For information about using the email application on your computer or mobile device, see the documentation provided with the application.
- **2.** Create a new email message, and then attach the file that you want to print. For a list of files that can be printed using HP ePrint, as well as guidelines to follow when using HP ePrint, see <u>Set up HP ePrint using</u> the embedded web server on page 36.
- **3.** Enter the printer's email address in the "To" line of the email message, and then select the option to send the email message.
 - NOTE: The HP ePrint server does not accept email print jobs if there are multiple email addresses included in the "To" or "Cc" fields. Only enter the email address of your HP printer in the "To" field. Do not enter any additional email addresses in the other fields.

Find the printer's email address

NOTE: Make sure you have created an ePrint account.

To sign up for an account on ePrintCenter, visit ePrintCenter at www.eprintcenter.com.

To obtain the printer's email address, press the nt (HP ePrint) button on the printer control panel.

The printer prints an information page that contains the printer email address.

Turn off HP ePrint

- 1. Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the **Web Services** tab, and then click **ePrint** in the **Web Services Settings** section.
- 3. Click Turn Off ePrint.
- NOTE: To remove all Web Services, see Remove Web Services on page 39.

38 Chapter 3 HP ePrint ENWW

Remove Web Services

To remove Web Services, complete the following steps:

- 1. Open the EWS. For more information, see <u>Embedded web server on page 149</u>.
- 2. Click the Web Services tab, and then click Remove Web Services in the Web Services Settings section.
- 3. Click Remove Web Services.
- 4. Click Yes to remove Web Services from your printer.

4 Work with ink cartridges

To ensure the best print quality from the printer, you need to perform some simple maintenance procedures.

TIP: If you have problems printing documents, see Print quality troubleshooting on page 57.

This section contains the following topics:

- Information on ink cartridges and the printhead
- Check the estimated ink levels
- Printing with black or color ink only
- Replace the ink cartridges
- Store printing supplies
- Anonymous usage information storage

ENWW Remove Web Services 39

Information on ink cartridges and the printhead

The following tips help maintain HP ink cartridges and ensure consistent print quality.

 The instructions in this user guide are for replacing ink cartridges, and are not intended for first time installation.

CAUTION: While ink cartridges are not damaged when left outside of the printer, the printhead does need to have all cartridges installed at all times after the printer is set up and in use. Leaving one or more cartridge slots empty for an extended period may lead to print quality problems and possibly damage the printhead. If you have recently left a cartridge out of the printer for an extended period, or if you have had a recent paper jam, and have noticed poor print quality, clean the printhead. For more information, see Clean the printhead on page 84.

- Keep all ink cartridges in the original sealed packages until they are needed.
- Be sure to turn off the printer properly. For more information, see Turn the printer off on page 14.
- Store ink cartridges at room temperature (15-35° C or 59-95° F).
- Always turn off the printer by pressing the () (Power) button. Wait until the Power light turns off before unplugging the power cord or turning off a power strip. If you improperly turn off the printer, the print carriage might not return to the correct position, and that can cause problems with the printhead and print quality issues.
- Do not clean the printhead unnecessarily. This wastes ink and shortens the life of the cartridges.
- Handle ink cartridges carefully. Dropping, jarring, or rough handling during installation can cause temporary printing problems.
- If you are transporting the printer, do the following to prevent ink leaking from the printer or other damage from occurring to the printer:
 - Make sure you turn off the printer by pressing the () (Power) button. Wait until all sounds of internal motion stop before unplugging the printer. For more information, see <u>Turn the printer off</u> on page 14.
 - Make sure you leave the ink cartridges installed.
 - Place the printer sitting flat in the box during packing. During transportation, the printer should be stored in the same position (sitting flat) and should not be placed on its side, back, front, or inverted.

Related topics

- Check the estimated ink levels on page 41
- <u>Clean the printhead on page 84</u>

Check the estimated ink levels

You can check the estimated ink levels from the printer software. For information about using these tools, see <u>Printer management tools on page 146</u>. You can also print the Printer Status page to view this information (see Understand the Printer Status Report on page 79).

- **NOTE:** Ink level alerts and indicators provide estimates for planning purposes only. When you receive a low-ink alert, consider having a replacement cartridge available to avoid possible printing delays. You do not have to replace the cartridges until you are prompted.
- **NOTE:** If you have installed a refilled or remanufactured cartridge, or a cartridge that has been used in another printer, the ink level indicator might be inaccurate or unavailable.
- **NOTE:** Ink from the cartridges is used in the printing process in a number of different ways, including in the initialization process, which prepares the printer and cartridges for printing, and in printhead servicing, which keeps print nozzles clear and ink flowing smoothly. In addition, some residual ink is left in the cartridge after it is used. For more information, see www.hp.com/go/inkusage.

Printing with black or color ink only

For regular usage, this product is not designed to print using only the black cartridge when the color cartridges are out of ink.

However, your printer is designed to let you print as long as possible when your cartridges start to run out of ink

When there is sufficient ink in the printhead, the printer will offer you the use of black ink only when one or more of the color cartridges are out of ink, and the use of color ink only when the black cartridge is out of ink.

- The amount that you can print using black or color ink only is limited, so have replacement ink cartridges available when you are printing with black or color ink only.
- When there is no longer sufficient ink to print you will get a message that one or more cartridges are depleted, and you will need to replace the depleted cartridges before you resume printing.

CAUTION: While ink cartridges are not damaged when left outside of the printer, the printhead does need to have all cartridges installed at all times after the printer is set up and in use. Leaving one or more cartridge slots empty for an extended period may lead to print quality problems and possibly damage the printhead. If you have recently left a cartridge out of the printer for an extended period, or if you have had a recent paper jam, and have noticed poor print quality, clean the printhead. For more information, see Clean the printhead on page 84.

Replace the ink cartridges

NOTE: For information on recycling used ink supplies, see <u>HP inkjet supplies recycling program on page 117</u>.

If you do not already have replacement ink cartridges for the printer, see <u>Order printing supplies online</u> on page 132.

NOTE: At this time, some portions of the HP website are available in English only.

NOTE: Not all cartridges are available in all countries/regions.

CAUTION: While ink cartridges are not damaged when left outside of the printer, the printhead does need to have all cartridges installed at all times after the printer is set up and in use. Leaving one or more cartridge slots empty for an extended period may lead to print quality problems and possibly damage the printhead. If you have recently left a cartridge out of the printer for an extended period, or if you have had a recent paper jam, and have noticed poor print quality, clean the printhead. For more information, see Clean the printhead on page 84.

To replace the ink cartridges

Use these steps to replace the ink cartridges.

- **1.** Make sure the printer is turned on.
- **2.** Open the ink cartridge access door.

 \triangle **WARNING!** Wait until the print carriage stops moving before proceeding.

3. Press the front of the ink cartridge to release it, and then remove it from the slot.






4. Remove the new ink cartridge from its packaging.

5. Using the color-coded letters for help, slide the ink cartridge into the empty slot until it is securely installed in the slot.





Make sure that you insert the ink cartridge into the slot that has the same colored letter as the color you are installing.



- **6.** Repeat steps 3 through 5 for each ink cartridge you are replacing.
- 7. Close the ink cartridge access door.

Related topics

• Order printing supplies online on page 132

Store printing supplies

Ink cartridges can be left in the printer for extended periods of time. However, to assure optimal ink cartridge health, be sure to turn off the printer properly. For more information, <u>Turn the printer off on page 14</u>.

ENWW Store printing supplies 45

Anonymous usage information storage

The HP cartridges used with this printer contain a memory chip that assists in the operation of the printer. In addition, this memory chip stores a limited set of anonymous information about the usage of the printer, which might include the following: the date when the cartridge was first installed, the date when the cartridge was last used, the number of pages printed using the cartridge, the page coverage, frequency of printing, the printing modes used, any printing errors that might have occurred, and the printer model.

This information helps HP design future printers to meet our customers' printing needs. The data collected from the cartridge memory chip does not contain information that can be used to identify a customer or user of the cartridge or their printer.


HP collects a sampling of the memory chips from cartridges returned to HP's free return and recycling program (HP Planet Partners: www.hp.com/hpinfo/globalcitizenship/environment/recycle/). The memory chips from this sampling are read and studied in order to improve future HP printers. HP partners who assist in recycling this cartridge might have access to this data, as well.

Any third party possessing the cartridge might have access to the anonymous information on the memory chip. If you prefer to not allow access to this information, you can render the chip inoperable. However, after you render the memory chip inoperable, the cartridge cannot be used in an HP printer.

If you are concerned about providing this anonymous information, you can make this information inaccessible by turning off the memory chip's ability to collect the printer's usage information.

To disable the usage information function

▲ On the printer control panel, press and hold the ⚠ (Resume) button and the ♠ (Network Information) button until the ink cartridge lights blink, approximately five seconds, and then release the buttons.



For more information about how to open the EWS, see Embedded web server on page 149.

NOTE: You can continue to use the cartridge in the HP printer if you turn off the memory chip's ability to collect the printer's usage information.

5 Solve a problem

The information in <u>General troubleshooting tips and resources on page 51</u> suggests solutions to common problems. If your printer is not operating correctly and those suggestions did not solve your problem, try using the HP support services to obtain assistance.

This section contains the following topics:

- HP support
- General troubleshooting tips and resources
- Solve printer problems
- Print quality troubleshooting
- Solve paper-feed problems
- Solve problems using HP ePrint and HP websites
- Configure your firewall software to work with the printer
- Solve printer management problems
- Solve network problems
- <u>Troubleshoot installation issues</u>
- Understand the Printer Status Report
- Understand the network configuration page
- Printhead maintenance
- Uninstall and reinstall the HP software
- <u>Clear jams</u>
- Control panel lights reference

ENWW 47

HP support

If you have a problem, follow these steps

- 1. Check the documentation that came with the printer.
- 2. Visit the HP online support website at www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems. HP online support is available to all HP customers. It is the fastest source for up-to-date printer information and expert assistance and includes the following features:
 - Fast access to qualified online support specialists
 - HP software and driver updates for the HP printer
 - Valuable troubleshooting information for common problems
 - Proactive printer updates, support alerts, and HP news grams that are available when you register the printer

For more information, see Obtain electronic support on page 48.

- 3. Call HP support. Support options and availability vary by printer, country/region, and language. For more information, see HP support by phone on page 48.
- Obtain electronic support
- HP support by phone

Obtain electronic support

To find support and warranty information, go to the HP website at www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems. If prompted, select your country/region, and then click **Contact HP** for information about calling for technical support.

This website also offers technical support, drivers, supplies, ordering information and other options such as:

- Access online support pages.
- Send HP an email message for answers to your guestions.
- Connect with an HP technician by using online chat.
- Check for HP software updates.

You can also obtain support from the HP software for Windows or Mac OS X, which provide easy, step-by-step solutions to common printing problems. For more information, see <u>Printer management tools on page 146</u>.

Support options and availability vary by printer, country/region, and language.

HP support by phone

The phone support numbers and associated costs listed here are those in effect at time of publication and are applicable only for calls made on a land line. Different rates may apply for mobile phones.

For the most current HP list of telephone support numbers and call costs information, see www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems.

During the warranty period, you may obtain assistance from the HP Customer Care Center.



NOTE: HP does not provide telephone support for Linux printing. All support is provided online at the following website: https://launchpad.net/hplip. Click the Ask a question button to begin the support process.

The HPLIP website does not provide support for Windows or Mac OS X. If you are using these operating systems, see www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems.

This section contains the following topics:

- Before you call
- Phone support period
- Telephone support numbers
- After the phone support period

Before you call

Call HP support while you are in front of the computer and the printer. Be prepared to provide the following information:

- Model number
- Serial number (located on the back or bottom of the printer)
- Messages that appear when the situation occurs
- Answers to these questions:
 - Has this situation happened before?
 - Can you re-create it?
 - Did you add any new hardware or software to your computer at about the time that this situation began?
 - Did anything else occur prior to this situation (such as a thunderstorm or moving the printer)?

Phone support period

One year of phone support is available in North America, Asia Pacific, and Latin America (including Mexico). To determine the duration of phone support in Europe, the Middle East, and Africa, go to www.hp.com/support. Standard phone company charges apply.

Telephone support numbers

In many locations, HP provides toll free telephone support during the warranty period. However, some of the support numbers might not be toll free.

For the most current list of telephone support numbers, see www.hp.com/support . This website provides information and utilities that can help you correct many common printer problems.

ENWW HP support 49

www.hp.com/support

		.com/soppori	
Africa (English speaking)	(0027)112345872	Lietuva	+370 5 210 3333
Afrique (francophone)	0033 1 4993 9230	Jamaica	1-800-711-2884
021 672 280	الجزائر 021 67 22 80	日本	0120-96-1665
Algérie Argentina (Buenos Aires)	54-11-4708-1600	0800 222 47	الأردن
Argentina	0-800-555-5000	한국	الران 1588-3003
Australia	1300 721 147	Luxembourg (Français)	900 40 006
Australia (out-of-warranty)	1902 910 910		0.15 €/min
Österreich	0820 874 417	Luxemburg (Deutsch)	900 40 007 0.15 €Min
Белоруссия	doppelter Ortstarif (375) 17 328 4640	Madagascar	262 262 51 21 21
172 12 049	(375) 17 320 4040 البحرين	Magyarország	06 40 200 629
België (Nederlands)	078 600 019	Magyarorozag	7,2 HUF/perc vezetékes telefonra
Doigle (Houseland)	0.0546 euro/min piekuren	Malaysia	1800 88 8588
Belgique (Français)	0.0273 euro/min daluren 078 600 020	Maurice	262 262 210 404
beigique (Français)	0,0546 euro/min heures de pointe	México (Ciudad de México) México	55-5258-9922 01-800-472-68368
България	0,0273 euro/min heures creuses	Maroc	0801 005 010
	0 700 1 0404 0800 223213	Nederland	+31 0900 2020 165
Hrvatska			0.10 €/Min
Brasil (Sao Paulo) Brasil	55-11-4004-7751 0-800-709-7751	New Zealand	0800 441 147
Canada	1-(800)-474-6836 (1-800 hp	Nigeria	(01) 271 2320
Odridda	invent)	Norge	815 62 070
Central America & The	www.hp.com/la/soporte		starter på 0,59 Kr per min., deretter 0,39 Kr per min.
Caribbean			Fra mobiltelefon gjelder mobiltelefontakster.
Chile	800-360-999	24791773	غمان
中国	800-820-6616 400-885-6616	Panamá	1-800-711-2884
中国 Colombia (Bogotá)	571-606-9191	Paraguay	009 800 54 1 0006
Colombia	01-8000-51-4746-8368	Perú	0-800-10111
Costa Rica	0-800-011-1046	Philippines Polska	2 867 3551 (22) 583 43 73
Česká republika	420 810 222 222	Poiska	Koszt nolaczenia: z tel
Danmark	1.53 CZN/min 70 20 28 45		stacjonarnego jak za 1 impuls wg taryfy operatora,- z tel. komorkowego wg taryfy operatora.
Danmark	70 20 28 45 Opkald: 0,145 (kr. pr. min.)		
	Opkald: 0,145 (kr. pr. min.) Pr. min. man-lør 08.00-19.30: 0,25 Pr. min. øvrige tidspunkter: 0,125	Portugal	808 201 492 Custo: 8 cêntimos no primeiro
Festi			minuto e 3 cêntimos restantes minutos
Ecuador (Andinatel)	372 6813 823 1-999-119 🕾	Puerto Rico	1-877-232-0589
Ecuador (Andinatei)	800-711-2884	00974 - 44761936	ždc.
Ecuador (Pacifitel)	1-800-225-528 🕾	República Dominicana	1-800-711-2884
	800-711-2884	La Réunion	0820 890 323
02 691 0602	مصر	România	0801 033 390
El Salvador	800-6160		(021 204 7090) 0,029 pe minut
España	902 010 059 Coste horario normal	Россия	800 500 9268
	(de 8:00 a 20:00)	800 897 1415	السعوبية
	6.73 cts/min Coste horario reducido	Singapore	+65 6272 5300
	4.03 cts/min	Srbija	0700 301 301 0850 111 256
	Coste de establecimiento de llamada 8.33 cts	Slovenská republika	miestna tarifa
France	0969 320 435	Slovenija	01 432 2001
	Tarif local	South Africa (RSA)	0860 104 771
Deutschland	069 29 993 434	Count mice (10. y	Calls at Local Rate
	0,14 €/Min aus dem deutschen Festnetz - bei Anrufen aus	Suomi	0203 667 67
	Mobilfunknetzen können andere	Currier	0.0147€/min 0771-20 47 65
Ελλάδα	Preise gelten	Sverige	0,23 kr/min
Lividod	801-11-75400 0,30 Ευρώ/λεπτό	Schweiz (Deutsch)	0848 672 672
	0,30 Ευρώ/λεπτό	, ,	8Rp./Min
Κύπρος Guatemala		Schweiz (Deutsch) Suisse (Français)	
Κύπρος	0,30 Ευρώ/λεπτό 800 9 2654	, ,	8Rp./Min 0848 672 672 0,08CHF/min 0848 672 672
Κύπρος Guatemala	0,30 Ευρώ/λεπτό 800 9 2654 1-800-711-2884	Suisse (Français) Svizzera	8Rp./Min 0848 672 672 0,08CHF/min 0848 672 672 0,08CHF/min
Kύπρος Guatemala 香港特別行政區	0,30 Ευρώ/λεπτό 800 9 2654 1-800-711-2884 (852) 2802 4098	Suisse (Français) Svizzera 臺灣	8Rp./Min 0848 672 672 0.06CHF/min 0848 672 672 0.06CHF/min 0800-010055 (免費)
Ки́троς Guatemala 香港特別行政區 India Indonesia	0,30 Eupid/Aemró 800 9 2654 1-800-711-2884 (862) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408	Suisse (Français) Svizzera	8RQ.Min 0848 672 672 0,08CHF/min 0848 672 672 085 672
Kúrrpoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189	0,30 Eupiü/kemö 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408	Suisse (Français) Svizzera 臺灣 Twu 071 891 391 Trinidad & Tobago	8Rp.Min 0848 672 672 0,08CHF/min 0848 672 672 0,08CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884
Kúmpoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 +971 4 224 9189	0,30 Eupüi/kirmö 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408	Suisse (Français) Svizzera 臺灣 Tinu 071 891 391 Trinidad & Tobago Tunisie	8Rp.Min 0848 672 672 9,080:HF/min 0848 672 672 9,080:HF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 23 927 000
Kúrrpoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189	0,30 Ευριώ/λεπτό 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 الرساق العراق 1890 923 902 Calls cost Cost 5.1 cent peak /	Suisse (Français) Svizzera 臺灣 Twu 071 891 391 Trinidad & Tobago	88p_Min 0848 672 672 0,86CHF/min 0848 672 672 0,86CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 23 927 000 0(212) 444 0307
Kύπρος Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 Ireland	0,30 Eupki/Amm6 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 البراق 1890 923 902 Calls cost Cost 51 cent peak / 1.3 cent off-peak per minute	Suisse (Français) Svizzera 臺灣 Tinu 071 891 391 Trinidad & Tobago Tunisie	88p.Min 0848 672 672 0.86CHF/min 0848 672 672 0.96CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 23 927 000 0(212) 444 0307 Yerel numara: 444 0307 Oos Tufk, yeer numara (stanbul
Kύπρος Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland	0,30 Ευριώ/λεπτό 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 الرساق العراق 1890 923 902 Calls cost Cost 5.1 cent peak /	Suisse (Français) Svizzera 臺灣 Tinu 071 891 391 Trinidad & Tobago Tunisie	8FQ.Min 00448 672 672 0,080:HFmin 0800-010055 (免費) +66 (2) 353 9000 1.800-711-2884 23 927 000 0(212) 444 0307 Yerel numara: 444 0307 0,08 Tulk, yerel numara (stanbul, Bursa, Ankara ve Izmj) ve
Kúripoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland	0,30 Eupki/Amm6 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 البراق 1890 923 902 Calls cost Cost 51 cent peak / 1.3 cent off-peak per minute	Suisse (Français) Svizzera 臺灣 Nui 071 891 391 Trinidad & Tobago Tunisie Türkiye	8R9_Min 00446 872 672 0.08CHF/min 0846 872 672 0.08CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 23 927 000 0(212) 444 0307 Yerel numara: 444 0307 Ool Tulkus leviel numara (stanbul, Bursa, Arkara ve Izmir) vo 101 Tulkusal lotet
Kúmpoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland	0,30 Eupki/Amm6 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 البراق 1890 923 902 Calls cost Cost 51 cent peak / 1.3 cent off-peak per minute	Suisse (Français) Svizzera 臺灣 Tinu 071 891 391 Trinidad & Tobago Tunisie	889_Min 0848 672 672 0,080:HF/min 0848 672 672 0,080:HF/min 0800-010055 (免費) +66 (2) 353 9000 1,800-711-2884 23 927 000 0(212) 444 0307 Yerel numara: 444 0307 Oo8 Tutki yerel numara (Istanbul, Bursa, Ankara ve Izmir) ve 0,10 Tu Luksal 600 10 Tu Luksal 613 10 Tu Luksal 613 11 Tu Luksal 613 11 Tu Luksal 613 12 Tu Luksal 613 13 Tu Luksal 613 13 Tu Luksal 613 14 Tu Luksal 613 16 Tu Luksal 613 16 Tu Luksal 613 17 Tu Luksal 613 18 Tu Luk
Kúmpoç Guatemala 香港特別行政區 India India Indonesia +971.4.224.9189 +971.4.224.9189 Ireland 1-700-503-048 กลาก เกต เกต เกต เกต เกต เกต เกต เกต เกต เก	0,30 Eupki/Amm6 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 البراق 1890 923 902 Calls cost Cost 51 cent peak / 1.3 cent off-peak per minute	Suisse (Français) Svizzera 臺灣 Iwu 071 891 391 Trinidad & Tobago Tunisie Türkiye	88p.Min 0848 672 672 0.88CHF/min 0848 672 672 0.88CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 29 927 000 0(212) 444 0307 Yerel numara: 444 0307 O80 T-Lidix, yerel numara (Blanbul, Bursa, Arkara ve Izmir) ve 0,10 T. Luksai (0,10 T. Luksai (1,10 T. Luksai (1,1
Kύmpoç Guatemala 香港特別行政區 India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland Ireland 1-700-503-048 มหา เพลาะ เพลา	0,30 Eupki/kmro 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408	Suisse (Français) Svizzera 臺灣 Timu 071 891 391 Trinidad & Tobago Tunisie Türkiye Україна 600 54 47 47 United Kingdom	8FQ.Min (1904年 1972) 1904年 1972 (1904年 1972) 1904年 19
Kúmpoç Guatemala 香港特別行政區 India India Indonesia +971.4.224.9189 +971.4.224.9189 Ireland 1-700-503-048 กลาก เกต เกต เกต เกต เกต เกต เกต เกต เกต เก	0,30 Eupki/kmro 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-2852900 +62 (21) 350 3408 البراق 1890 923 902 Calls cost Cost 5.1 cont peak / 1.3 cont off-peak per minuto "שראל 848 800 871	Suisse (Français) Svizzera 臺灣 Timi 071 891 391 Trinidad & Tobago Tunisie Türkiye Україна 600 54 47 47 United Kingdom United States	8Rp_Min (1944 672 672 1944 672 1944 672 1945 672 1945 672 1945 674 675 675 675 675 675 675 675 675 675 675
Kύmpoç Guatemala 香港特別行政區 India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland Ireland 1-700-503-048 มหา เพลาะ เพลา	0,30 Eupli/Ammö 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 الرياق 1890 923 902 Calls cost Cost 5 t cent peak / 1.3 cent off-peak per minute אישראל 1.3 cent off-peak per minute 1.3 cent off-pea	Suisse (Français) Svizzera 臺灣 โพย 071 891 391 Trinidad & Tobago Tunisie Türkiye Україна 600 54 47 47 United Kingdom United States Uruguay	88p.Min 0848 672 672 0.08CHF/min 0848 672 672 0.08CHF/min 0800-010055 (免費) +66 (2) 353 9000 1-800-711-2884 23 927 000 0(212) 444 0307 Yerel numara: 444 0307 Oon Tutkus lorder 10 1T Lubasi Orarioret 38 (044) 230-51-06 10 15 15 15 15 15 15 15 15 15 15 15 15 15
Kúmpoç Guatemala 香港特別行政區 India India India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland 1-700-503-048 กฐาว กับการ เกตร์ เกตร	1,30 Eupüi/Airmö 1,00 1,00 Eupüi/Airmö 1,00 1,00 1,00 1,00 1,00 1,00 1,00 1,00	Suisse (Français) Svizzera 臺灣 Timi 071 891 391 Trinidad & Tobago Tunisie Türkiye Україна 600 54 47 47 United Kingdom United States	8Rp_Min (1944 672 672 1944 672 1944 672 1945 672 1945 672 1945 674 675 675 675 675 675 675 675 675 675 675
Kúmpoç Guatemala 香港特別行政區 India India Indonesia +971 4 224 9189 +971 4 224 9189 Ireland 1-700-503-048 กรา การบลุกท่าย (การบลุกท่าย เกรา การบลุกท่าย (การบลุกท่าย เกรา การบลุกท่าย (การบลุกท่าย เกรา การบลุกท่าย (การบลุกท่าย กรา การบลุกท่าย (การบลุกท่าย เกรา การบลุกท่าย เกรา (การบลุกท่าย เกรา (การบลุกท่าย ท่าย (การบลุกท่าย เกรา (การบลุกท่าย (การบลุกท	0,30 Eupli/Ammö 800 9 2654 1-800-711-2884 (852) 2802 4098 1-800-425-7737 91-80-28526900 +62 (21) 350 3408 الرياق 1890 923 902 Calls cost Cost 5 t cent peak / 1.3 cent off-peak per minute אישראל 1.3 cent off-peak per minute 1.3 cent off-pea	Suisse (Français) Svizzera 臺灣 Timu 071 891 391 Trinidad & Tobago Tunisie Türkiye Україна 600 54 47 47 United States Uruguay Venezuela (Caracas)	8Rp_Min (1948) (1948) (1948) (1944) (1948) (1944)

After the phone support period

After the phone support period, help is available from HP at an additional cost. Help may also be available at the HP online support Web site: www.hp.com/support. Contact your HP dealer or call the support phone number for your country/region to learn more about support options.

General troubleshooting tips and resources

NOTE: Many of the following steps require HP software. If you did not install the HP software, you can install it using the HP software CD included with the printer, or download the HP software from the HP support website, www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems.

Check or do the following before you begin troubleshooting:

- Try turning the printer off and then on again.
- For a paper jam, see Clear jams on page 88.
- For paper-feed problems, such as the paper skew and paper pick, see Solve paper-feed problems on page 62.
- Power light is on and not blinking. When the printer is turned on for the first time, it takes approximately 9 minutes to initialize it after the ink cartridges are installed.
- Power cord and other cables are working, and are firmly connected to the printer. Make sure the printer is connected firmly to a functioning alternating current (AC) power outlet, and is turned on. For voltage requirements, see Electrical specifications on page 109.
- Media is loaded correctly in the input tray and is not jammed in the printer.
- All packing tapes and materials are removed.
- The printer is set as the current or default printer. For Windows, set it as the default in the Printers folder. For Mac OS X, set it as the default in the Print & Fax or Print & Scan section of the System **Preferences**. See your computer's documentation for more information.
- **Pause Printing** is not selected if you are using a computer running Windows.
- You are not running too many programs when you are performing a task. Close programs that you are not using or restart the computer before attempting the task again.

Solve printer problems

TIP: You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

This section contains the following topics:

- The printer shuts down unexpectedly
- Alignment fails
- The printer is not responding (nothing prints)
- The printer prints slowly
- The printer is making some unexpected noises
- Blank or partial page printed
- Something on the page is missing or incorrect
- Placement of the text or graphics is wrong

The printer shuts down unexpectedly

Check the power and power connections

 Make sure the printer is connected firmly to a functioning alternating current (AC) power outlet. For voltage requirements, see Electrical specifications on page 109.

Alignment fails

If the alignment process fails, make sure you have loaded unused, plain white paper into the input tray. The alignment fails when you have colored paper loaded in the input tray.

If the alignment process fails repeatedly, you may need to clean the printhead, or you might have a defective sensor. To clean the printhead, see Clean the printhead on page 84.

If cleaning the printhead does not solve the problem, contact HP support. Go to www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems. If prompted, select your country/region, and then click **Contact HP** for information on calling for technical support.

The printer is not responding (nothing prints)

There are print jobs stuck in the print queue

• Open the print queue, cancel all documents, and then reboot the computer. Try to print after the computer reboots. Refer to the Help system for the operating system for more information.

Check the printer setup

52

• For more information, see <u>General troubleshooting tips and resources on page 51</u>.

Chapter 5 Solve a problem ENWW

Check the HP software installation

 If the printer is turned off when printing, an alert message should appear on your computer screen; otherwise, the HP software provided with the printer might not be installed correctly. To resolve this, uninstall the HP software completely, and then reinstall the HP software. For more information, see Uninstall and reinstall the HP software on page 86.

Check the cable connections

- Make sure both ends of the USB cable or Ethernet cable are secure.
- If the printer is connected to a network, check the following:
 - Check the Link light on the back of the printer.
 - Make sure you are not using a phone cord to connect the printer.

Check any personal firewall software installed on the computer

 The personal software firewall is a security program that protects a computer from intrusion. However, the firewall might block communication between the computer and the printer. If there is a problem communicating with the printer, try temporarily disabling the firewall. If the problem persists, the firewall is not the source of the communication problem. Re-enable the firewall.

The printer prints slowly

Try the following solutions if the printer is printing very slowly.

- Solution 1: Use a lower print quality setting
- Solution 2: Check the ink levels
- Solution 3: Contact HP support

Solution 1: Use a lower print quality setting

The print quality was set to a higher setting.

Check the print quality setting. **Best** and **Maximum dpi** provide the best quality but are slower than **Normal** or **Draft**. **Draft** provides the fastest print speed.

If this did not solve the issue, try the next solution.

Solution 2: Check the ink levels

The ink cartridges might have insufficient ink. Insufficient ink may cause the printhead to overheat. When the printhead overheats, the printer slows down to allow it to cool.

Check the estimated ink levels in the ink cartridges.

NOTE: Ink level alerts and indicators provide estimates for planning purposes only. When you receive a lowink alert, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace the ink cartridges until prompted to do so.

ENWW Solve printer problems 53

↑ CAUTION: While ink cartridges are not damaged when left outside of the printer, the printhead does need to have all cartridges installed at all times after the printer is set up and in use. Leaving one or more cartridge slots empty for an extended period may lead to print quality problems and possibly damage the printhead. If you have recently left a cartridge out of the printer for an extended period, or if you have had a recent paper jam, and have noticed poor print quality, clean the printhead. For more information, see Clean the printhead on page 84.

For more information, see:

Check the estimated ink levels on page 41

If this did not solve the issue, try the next solution.

Solution 3: Contact HP support

There was a problem with the printer.

Contact HP support for service.

Go to: www.hp.com/support. This website provides information and utilities that can help you correct many common printer problems.

If prompted, choose your country/region, and then click Contact HP for information on calling for technical support.

The printer is making some unexpected noises

You might hear some unexpected noises made by the printer. These are the servicing sounds when the printer performs automatic servicing functions to maintain the health of the printheads.



NOTE: To prevent any potential damage to your printer:

Do not turn off the printer while the printer is performing any servicing. If you are turning off the printer, wait for the printer to come to a complete stop before turning it off using the (1) (Power) button. For more information, see Turn the printer off on page 14.

Make sure all ink cartridges are installed. If any of the ink cartridges are missing, the printer will perform extra servicing to protect the printheads.

Blank or partial page printed

Clean the printhead

Complete the printhead cleaning procedure. For more information, see Clean the printhead on page 84. The printhead may need to be cleaned if the printer was turned off incorrectly.



NOTE: Incorrectly turning off the printer can cause print quality problems like blank or partial pages. Printhead cleaning can solve these problems, but turning off the printer correctly can prevent them in the first place. Always turn the printer off by pressing the 🔱 (Power) button on the printer. Wait until the power light goes out before unplugging the power cord or turning off a power strip.

Check the paper settings

- Make sure you select the correct print quality settings in the printer driver for the paper loaded in the trays.
- Make sure the page settings in the printer driver match the page size of paper loaded in the tray.

More than one page is being picked

• For more information, see Solve paper-feed problems on page 62.

There is a blank page in the file

Check the file to make sure there is no blank page.

Something on the page is missing or incorrect

Check the Print Quality Diagnostic page

 Print a Print Quality Diagnostic page to help you decide whether to run any maintenance tools to improve the print quality of your printouts. For more information, see <u>Print quality troubleshooting</u> on page 57.

Check the margin settings

- Make sure the margin settings for the document do not exceed the printable area of the printer. For more information, see <u>Set minimum margins on page 106</u>.
- TIP: If the top and bottom margins in your document are smaller than 16 mm (0.63 inches), the document might not print out correct.

Check the color print settings

• Make sure **Print in Grayscale** is not selected in the printer driver.

Check the printer location and length of USB cable

High electromagnetic fields (such as those generated by USB cables) can sometimes cause slight
distortions to printouts. Move the printer away from the source of the electromagnetic fields. Also, it is
recommended that you use a USB cable that is less than 3 meters (9.8 feet) long to minimize the effects
of these electromagnetic fields.

Check the paper size

• Make sure the selected paper size matches the actual loaded paper size.

Placement of the text or graphics is wrong

Check how the paper is loaded

 Make sure the paper guides fit snugly against the edges of the stack of paper, and make sure the tray is not overloaded. For more information, see <u>Load paper on page 11</u>.

Check the paper size

- Content on a page might be cut off if the document size is larger than the paper that you are using.
- Make sure the paper size selected in the printer driver matches the size of paper loaded in the tray.

Check the margin settings

• If the text or graphics are cut off at the edges of the page, make sure the margin settings for the document do not exceed the printable area of your printer. For more information, see <u>Set minimum</u> margins on page 106.

ENWW Solve printer problems 55

Check the page-orientation setting

• Make sure the paper size and page orientation selected in the application match the settings in the printer driver. For more information, see Change basic network settings on page 135.

Check the printer location and length of USB cable

High electromagnetic fields (such as those generated by USB cables) can sometimes cause slight
distortions to printouts. Move the printer away from the source of the electromagnetic fields. Also, it is
recommended that you use a USB cable that is less than 3 meters (9.8 feet) long to minimize the effects
of these electromagnetic fields.

If the above solutions do not work, the problem may be caused by the inability of the application to interpret print settings correctly. See the release notes for known software conflicts, refer to the application's documentation, or contact the software manufacturer for specific help.

TIP: You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

Print quality troubleshooting

Try the solutions in this section to resolve print quality problems in your printout.

- Solution 1: Make sure you are using original HP ink cartridges
- Solution 2: Check the ink levels
- Solution 3: Check the paper loaded in the input trav
- Solution 4: Check the paper type
- Solution 5: Check the print settings
- Solution 6: Print and evaluate a print quality report
- Solution 7: Contact HP support

Solution 1: Make sure you are using original HP ink cartridges

Non-HP ink cartridges were being used.

Check to see if your ink cartridges are original HP ink cartridges.

HP recommends that you use original HP ink cartridges. Original HP ink cartridges are designed and tested with HP printers to help you easily produce great results, time after time.



NOTE: HP cannot quarantee the quality or reliability of non-HP supplies. Printer service or repairs required as a result of using a non-HP supply are not covered under warranty.

If you believe you purchased original HP ink cartridges, go to:

www.hp.com/go/anticounterfeit


If this did not solve the issue, try the next solution.

Solution 2: Check the ink levels

The ink cartridges might have insufficient ink.



NOTE: Ink level alerts and indicators provide estimates for planning purposes only. When you receive a lowink alert, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace the ink cartridges until print quality becomes unacceptable.



Check the estimated ink levels in the ink cartridges. For more information, see Check the estimated ink levels on page 41.

If this did not solve the issue, try the next solution.

Solution 3: Check the paper loaded in the input tray

The paper was loaded incorrectly, or it was wrinkled or too thick.

Make sure the paper is loaded correctly and that it is not wrinkled or too thick.

- Load paper with the print side facing down. For example, if you are loading glossy photo paper, load the paper with the glossy side down.
- Make sure the paper lays flat in the input tray and is not wrinkled. If the paper is too close to the printhead during printing, the ink might be smeared. This can happen if the paper is raised, wrinkled, or very thick, such as a mailing envelope.

For more information, see:

Load paper on page 11

If this did not solve the issue, try the next solution.

Solution 4: Check the paper type

The wrong kind of paper was loaded in the input tray.

HP recommends that you use HP papers or any other paper type with ColorLok technology that is appropriate for the printer. All papers with the ColorLok logo are independently tested to meet high standards of reliability and print quality, and produce documents with crisp, vivid color, bolder blacks and dry faster than ordinary plain papers.

Always make sure the paper you are printing on is flat. For best results when printing images, use HP Advanced Photo Paper.

Store specialty paper in its original packaging inside a resealable plastic bag on a flat surface in a cool, dry place. When you are ready to print, remove only the paper you plan to use immediately. When you have finished printing, return any unused photo paper to the plastic bag. This prevents the photo paper from curling.



NOTE: For this issue, there is not a problem with your ink supplies. Therefore, replacing the ink cartridges is not necessary.

For more information, see:

Select print paper on page 8

If this did not solve the issue, try the next solution.

Solution 5: Check the print settings

The print settings were set incorrectly.

Check the print settings.

Check the print settings to see if the color settings are incorrect.

For example, check to see if the document is set to print in grayscale. Or, check to see if advanced color settings such as saturation, brightness, or color tone, are set to modify the appearance of colors.

Check the print quality setting and make sure it matches the type of paper loaded in the printer.

You might need to choose a lower print quality setting if colors are running into each other. Or, choose a higher setting if you are printing a high-quality photo, and then make sure photo paper such as HP Advanced Photo Paper is loaded in the input trav.

NOTE: On some computer screens, colors might appear differently than they do when printed on paper. In this case, there is nothing wrong with the printer, print settings, or ink cartridges. No further troubleshooting is required.

For more information, see:

Select print paper on page 8


If this did not solve the issue, try the next solution.

Solution 6: Print and evaluate a print quality report

Print quality problems can have many causes: software settings, a poor image file, or the printing system itself. If you are unhappy with the quality of your prints, a Print Quality Diagnostic page can help you determine if the printing system is working correctly.

To print a print quality report

- **Control panel:** Press and hold the (1) (Power) button, press the X (Cancel) button seven times, press the (Resume) button two times, and then release the (1) (Power) button.
- Embedded web server: Click the Tools tab, click Print Quality Toolbox under Utilities, and then click the **Print Quality Report** button.
- HP Utility (Mac OS X): In the Information And Support section, click Print Quality Diagnostics, and then click **Print**.



If defects are seen on the page, follow the steps below:

- 1. If the lines in Test Pattern 1 are not straight and connected, align the printer. For more information, see Align the printhead on page 85.
- 2. If you see white lines in any of the color blocks in Test Pattern 2, clean the printhead. For more information, see Clean the printhead on page 84.
- **3.** If you see white or dark lines where the arrows are pointing in Test Pattern 3, align the printer. For more information, see <u>Align the printhead on page 85</u>.

If there are no defects, then the printer and ink system are working properly. If you still see print quality problems in your output, double-check your software settings and paper as described in the previous solutions.

Solution 7: Contact HP support

There was a problem with the printer.

Contact HP support for service.

Go to: www.hp.com/support . This website provides information and utilities that can help you correct many common printer problems.

If prompted, choose your country/region, and then click **Contact HP** for information on calling for technical support.

Solve paper-feed problems

TIP: You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

Paper is not supported for the printer or tray


• Use only paper that is supported for the printer and the tray being used. For more information, see Paper specifications on page 102.

Paper is not picked up from a tray

- Make sure paper is loaded in the tray. For more information, see <u>Load paper on page 11</u>. Fan the paper before loading.
- Make sure the paper guides are set to the correct markings in the tray for the paper size you are loading. Also make sure the paper guides are snug, but not tight, against the stack.
- Make sure paper in the tray is not curled. Uncurl paper by bending it in the opposite direction of the curl.

Media is not coming out correctly

 Make sure the output output tray extension is fully extended; otherwise, printed pages may fall off the printer.




Remove excess paper from the output tray. There is a limit to the number of sheets the tray can hold.

Pages are skewing

62

- Make sure the paper loaded in the trays is aligned to the paper guides. If needed, pull out the trays from the printer and reload the paper correctly, making sure that the paper guides are aligned correctly.
- Load paper into the printer only when it is not printing.
- Remove and replace the automatic two-sided printing accessory (duplexer).
 - Push the button on either side of the duplexer, and then remove the unit.

Chapter 5 Solve a problem ENWW



Reinsert the duplexer into the printer.

Multiple pages are being picked up

- Fan the paper before loading.
- Make sure the paper guides are set to the correct markings in the tray for the paper size you are loading.
 Also make sure the paper guides are snug, but not tight, against the stack.
- Make sure the tray is not overloaded with paper.
- Use HP paper for optimum performance and efficiency.

Solve problems using HP ePrint and HP websites

This section provides solutions to common problems using HP ePrint and HP websites.

- Solve problems using HP ePrint
- Solve problems using HP websites

Solve problems using HP ePrint

64

If you are having problems using HP ePrint, check the following:

- Make sure the printer is connected to the Internet using an Ethernet or wireless connection.
- **NOTE:** You cannot use these web features if the printer is connected using a USB cable.
- Make sure the latest printer updates have been installed on the printer. For more information, see
 Update the printer on page 15.
- Make sure HP ePrint is enabled on the embedded web server (EWS). For more information, see <u>Set up HP</u> ePrint using the embedded web server on page 36.
- Make sure the network hub, switch, or router is turned on and working correctly.
- If you are connecting the printer using an Ethernet cable, make sure you are not connecting the printer
 using a phone cord or a crossover cable to connect the printer to the network and that the Ethernet
 cable is securely connected to the printer. For more information, see <u>Solve Ethernet network problems</u>
 on page 69.
- If you are connecting the printer using a wireless connection, make sure the wireless network is functioning properly. For more information, see <u>Solve wireless problems on page 69</u>.
- If you are using HP ePrint, check the following:
 - Make sure the printer's email address is correct.
 - Make sure that the printer's email address is the only address listed in the "To" line of the email message. If other email addresses are listed in the "To" line, the attachments you are sending might not print.
 - Make sure you are sending documents that meet the HP ePrint requirements. For more information, see <u>HP ePrint specifications on page 108</u>.
- If your network uses proxy settings when connecting to the Internet, make sure the proxy settings you
 are entering are valid:
 - Check the settings being used by the Web browser you are using (such as Internet Explorer, Firefox, or Safari).
 - Check with the IT administrator or person who set up your firewall.
 - If the proxy settings used by your firewall have changed, you must update these settings in either the printer control panel. If these settings are not updated, you will not be able to use HP ePrint.
 - For more information, see Set up HP ePrint using the embedded web server on page 36.
- 🏋 TIP: For additional help on setting up and using HP ePrint, visit ePrintCenter (www.eprintcenter.com).

Solve problems using HP websites

If you are having problems using HP websites from your computer, check the following:

- Make sure the computer that you are using is connected to the Internet.
- Make sure the web browser meets the minimum system requirements. For more information, see HP website specifications on page 108.
- If your web browser uses any proxy settings to connect to the Internet, try turning off these settings. For more information, see the documentation provided with your web browser.

Configure your firewall software to work with the printer

A personal firewall, which is security software running on your computer, can block network communication between your printer and your computer.

If you are having problems such as:

- Printer not found when installing HP software
- Unable to print, print job stuck in queue or printer goes offline
- Unable to see printer status on your computer

The firewall might be preventing your printer from notifying computers on your network where it can be found.

If you are using the HP software on a computer running Windows and cannot find the printer during installation (and you know the printer is on the network)—or if you have already successfully installed HP software and experience problems—check the following:

- If you have just installed the HP software, try turning off your computer and the printer, and then turning them both on again.
- Keep your security software up to date. Many security software vendors provide updates that correct known issues and provide the latest defenses against new security threats.
- If your firewall has "High," "Medium," or "Low" security settings, use the "Medium" setting when your computer is connected to your network.
- If you have changed any firewall settings from default, try going back to the default setting.
- If your firewall has a setting called "trusted zone," use this setting when your computer is connected to vour network.
- If your firewall has a setting to "not show alert messages," you should disable this. When installing the HP software and using the HP printer you may see alert messages from your firewall software that provide options to "allow," "permit" or "unblock." You should allow any HP software that causes an alert. Also, if the alert has a "remember this action" or "create a rule for this" selection, select it. This is how the firewall learns what can be trusted on your network.
- Do not have more than one firewall enabled at the same time on your computer. An example would be having both the Windows firewall provided by the operating system and a third party firewall enabled at the same time. Having more than one firewall enabled at the same time will not make you computer any safer and may cause problems.

For more information about using your printer with personal firewall software, visit www.hp.com/go/ wirelessprinting, and then click **Firewall Help** in the **Wireless Network Help** section.



NOTE: At this time, some portions of this site are not available in all languages.

Solve printer management problems

This section provides solutions to common problems that involve managing the printer. This section contains the following topic:

Embedded web server cannot be opened



NOTE: To use the embedded EWS, the printer must be connected to a network using either an Ethernet or a wireless connection. You cannot use the embedded web server if the printer is connected to a computer with a USB cable.

Embedded web server cannot be opened

Check your network setup

- Make sure you are not using a phone cord or a crossover cable to connect the printer to the network.
- Make sure the network cable is securely connected to the printer.
- Make sure the network hub, switch, or router is turned on and working correctly.

Check the computer

Make sure the computer that you are using is connected to the network.



NOTE: To use the EWS, the printer must be connected to a network using either an Ethernet or a wireless connection. You cannot use the embedded web server if the printer is connected to a computer with a USB cable.

Check your web browser

- Make sure the web browser meets the minimum system requirements. For more information, see Embedded web server specifications on page 102.
- If your web browser uses any proxy settings to connect to the Internet, try turning off these settings. For more information, see the documentation available with your web browser.
- Make sure JavaScript and cookies are enabled in your web browser. For more information, see the documentation available with your web browser.

Check the printer IP address

- To check the IP address of the printer, obtain the IP address by printing a network configuration page. Press the \P (Network Information) button to print the network configuration page.
- Ping the printer using the IP address from the command prompt (Windows) or from Network Utility (Mac OS X). (Network Utility is located in the **Utilities** folder in the **Applications** folder at the top level of the hard disk.)

For example, if the IP address is 123.123.123.123, type the following at the command prompt (Windows):

```
C:\Ping 123.123.123.123
```

Ô٢

In Network Utility (Mac OS X), click the **Ping** tab, type the 123.123.123.123 in the box, and then click **Ping**.

If a reply appears, the IP address is correct. If a time-out response appears, the IP address is incorrect.

TIP: You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

Chapter 5 Solve a problem

Solve network problems

This section provides solutions to common problems when you are unable to connect or use the printer over your network.

This section contains the following topics:

- Solve Ethernet network problems
- Solve wireless problems
- Reset the Printer Network Settings

Solve Ethernet network problems

If you are unable to connect the printer to your Ethernet network, verify that:

- Make sure the Wireless light on the printer does not turn on.
- All cable connections to the computer and the printer are secure.
- The network is operational and the network hub, switch, or router is turned on.
- For computers running Windows, all applications, including virus protection programs, spyware protection programs, and firewalls, are closed or disabled.
- The printer is installed on the same subnet as the computers that use the printer.
- If the installation program cannot discover the printer, print the network configuration page, and enter the IP address manually in the installation program. For more information, see <u>Understand the network</u> <u>configuration page on page 81</u>.
- Reinstall the HP software. For more information, see <u>Uninstall and reinstall the HP software</u> on page 86.

Assigning the printer with a static IP address might resolve some installation problems, such as a conflict with a personal firewall. (Not recommended)

TIP: You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

Solve wireless problems

This section provides information about solving problems you might encounter when connecting the printer to your wireless network.

Follow these suggestions in order, starting with those listed in the "Basic wireless troubleshooting" section. If you still encounter problems, follow the suggestions provided in the "Advanced wireless troubleshooting" section.

- Basic wireless troubleshooting
- Advanced wireless troubleshooting
- After resolving the problems
- **TIP:** For more information about troubleshooting wireless problems, visit www.hp.com/go/wirelessprinting.

ENWW Solve network problems 69

Basic wireless troubleshooting

NOTE: If you have already configured the printer for wireless connection but the wireless light is still blinking, restart components of the wireless network.

To restart the components, turn off the router and the printer, and then turn them back on in this order: router first and then the printer. If you still are unable to connect, turn off the router, printer, and your computer. Sometimes, turning off the power and then turning it back on recovers from a network communication issue.

NOTE: If you have not configured the printer for wireless connection, use the HP software to complete the setup. For more information, see Set up the printer using the embedded web server (EWS) on page 140.

Perform the following steps in the order presented.

TIP: If you are using a computer running Windows, use the HP Print and Scan Doctor to help diagnose and get assistance in installing and using HP printers on home network. To use this tool, visit the HP Wireless Printing Center www.hp.com/go/wirelessprinting, and then click **Print and Scan Doctor** in the **Quick Links** section.

Step 1 - Make sure the wireless (802.11) light is turned on

The Wireless light in the printer control panel indicates the status of the wireless capabilities.

To turn on the printer wireless capabilities

Press the \P (Wireless) button to turn on the printer wireless capabilities.



70

NOTE: If your printer supports Ethernet networking, make sure that an Ethernet cable has not been connected to the printer. Connecting an Ethernet cable turns off the printer wireless capabilities.

Light description/Light pattern	Explanation
The Power light is on but the Wireless light is off.	The wireless capabilities are turned off.
(
The Power light is on and the Wireless light is on but blinking.	The wireless capabilities are turned on but the printer is not connected to a network.
The Power light is on and the Wireless light is on and solid.	The wireless capabilities are turned on but the printer is connected to a network.
₩ % 6 6	

Chapter 5 Solve a problem **ENWW**

Step 2 - Move the printer closer to the wireless router

• If you have configured the printer for wireless connection and the wireless light is solid, but the printer still has trouble staying connected, or you have print or scan communication issues, try moving the printer closer to the wireless router.

Step 3 - Run the Wireless Network Test

• For wireless networking issues, run the Wireless Network Test. If a problem is detected, the printed test report includes recommendations that might help solve the problem. For more information about how to print the wireless test page, see Test the wireless connection on page 142.

Advanced wireless troubleshooting

If you have tried the suggestions provided in <u>Basic wireless troubleshooting on page 70</u> and are still unable to use the printer over the network with a computer or mobile devices for print, try the following steps in the order presented:

- Step 1: Make sure your computer is connected to your network
- Step 2: Make sure that the printer is connected to your network
- Step 3: Make sure your computer is not connected over a Virtual Private Network (VPN)
- Step 4: Make sure the printer is online and ready
- Step 5: Make sure the HP printer labeled (Network) is set as the default printer driver (Windows only)
- Step 6: Check to see if the firewall software is blocking communication
- **TIP:** If you are using a computer running Windows, use the HP Print and Scan Doctor to help diagnose and get assistance in installing and using HP printers on home network. To use this tool, visit the HP Wireless Printing Center www.hp.com/go/wirelessprinting, and then click **Print and Scan Doctor** in the **Quick Links** section.

Step 1: Make sure your computer is connected to your network

Make sure your computer is connected to your network—either the Ethernet network or the wireless network. If the computer is not connected to the network, you cannot use the printer over the network.

To check an Ethernet connection

- Many computers have indicator lights beside the port where the Ethernet cable from the router connects to your computer. Usually there are two indicator lights, one that is on and another that blinks. If your computer has indicator lights, check to see if the indicator lights are on. If the lights are not on, try reconnecting the Ethernet cable to the computer and the router. If you still do not see lights, there might be a problem with the router, the Ethernet cable, or your computer.
 - NOTE: Mac computers do not have indicator lights. To check the Ethernet connection on a Macintosh computer, click System Preferences in the Dock, and then click Network. If the Ethernet connection is working correctly, Built-in Ethernet appears in the list of connections, along with the IP address and other status information. If Built-in Ethernet does not appear in the list, there might be a problem with the router, the Ethernet cable, or your computer. For more information, click the Help button in the window.

ENWW Solve network problems 71

To check a wireless connection

- **1.** Make sure that your computer's wireless has been turned on. (For more information, see the documentation that came with your computer.)
- **2.** If you are not using a unique network name (SSID), then it is possible that your wireless computer could be connected to a nearby network that is not yours.

The following steps can help you determine if your computer is connected to your network.

Windows

 From the computer desktop, click Start, click Control Panel, point to Network and Internet, and then click View network status and tasks.

- Or -

From the computer desktop, click **Start**, select **Settings**, click **Control Panel**, double-click **Network Connections**.

- Or -


Right-click an empty area on the **Start** screen, click **All Apps** on the app bar, click **Control Panel**, click **Network and Sharing Center**, and then click **View network status and tasks**.

Leave the network dialog box open while you continue to the next step.

- **b.** Disconnect the power cord from the wireless router. The connection status of your computer should change to **Not Connected**.
- Reconnect the power cord to the wireless router. The connection status should change to
 Connected.

Mac OS X

▲ Click the **AirPort** icon in the menu bar at the top of the screen. From the menu that appears, you can determine if the AirPort is turned on and which wireless network your computer is connected to.



If you are unable to get your computer connected to your network, contact the person who set up your network or the router manufacturer as there might be a hardware issue with either your router or computer.

TIP: If you are using a computer running Windows, use the HP Print and Scan Doctor to help diagnose and get assistance in installing and using HP printers on home network. To use this tool, visit the HP Wireless Printing Center www.hp.com/go/wirelessprinting, and then click Print and Scan Doctor in the Quick Links section.

Step 2: Make sure that the printer is connected to your network

If your printer is not connected to the same network as your computer, you cannot use the printer over the network. Follow the steps described in this section to find out if your printer is actively connected to the correct network.



NOTE: If your wireless router or Apple AirPort Base Station is using a hidden SSID, your printer cannot automatically detect the network.

A: Make sure the printer is on the network

- If the printer supports Ethernet networking and is connected to an Ethernet network, make sure an Ethernet cable is not plugged into the back of the printer. If an Ethernet cable is plugged into the back, then wireless connectivity is disabled.
- If the printer is connected to a wireless network, run the Wireless Network Test. For more information about how to print the wireless test page, see Test the wireless connection on page 142.
- After the page has been printed, check the wireless connection status, the Network Name (SSID), and the IP address:

Connected	The Connected is listed in the Connectivity area, the Diagnostics Results section, which indicates if the printer is connected to your network — either your Ethernet network or your wireless network.	
	 If the Connected is Ready, the printer is actively connected to a network. 	
	• If the Connected is Offline, the printer is not connected to a network.	
Network Name (SSID)	The Network Name (SSID) is listed in the Current Configuration setction, which shows the network name what your printer choose for connecting the wireless network.	
IP Address	The IP Address is listed in the Current Configuration section, which indicates your printer has the valid IP address.	
	The IP address is the one used to open your printer's embedded web server (EWS).	

For information about connecting the printer to a wireless network, see Set up the printer using the embedded web server (EWS) on page 140.

B: Check to see if you can access the EWS

After you establish that the computer and the printer both have active connections to a network, you can verify if they are on the same network by accessing the printer's EWS. For more information, see Embedded web server on page 149.

To access the EWS

- On your computer, open the EWS. For more information, see Embedded web server on page 149.
 - **NOTE:** If you are using a proxy server in your browser, you might need to disable it to access the EWS.
- If you can open the EWS, try using the printer over the network (such as to print) to see if your network setup was successful.

If you cannot open the EWS or are still having problems using the printer over the network, continue to the next section regarding firewalls.

ENWW Solve network problems 73

C: Reconfigure wireless settings to make sure the connection is established

- ▲ If the printer is still not connected to your network, you need to reconfigure wireless settings in HP printer software on the computer. For more information about the configuration, see <u>Basic wireless</u> troubleshooting on page 70.
- **NOTE:** Make sure an Ethernet cable is not plugged into the back of the printer. If it is plugged into the back, then wireless connectivity is disabled.

Step 3: Make sure your computer is not connected over a Virtual Private Network (VPN)

A Virtual Private Network (VPN) is a computer network that uses the Internet to provide a remote, secure connection to an organization's network. However, most VPN services do not allow you to access local devices (like your printer) on your local network while your computer is connected to the VPN.

To connect to the printer, disconnect from the VPN.

TIP: To use the printer while connected to the VPN, you can connect the printer to your computer with a USB cable. The printer uses its USB and network connections at the same time.

For more information, contact your network administrator or the person who set up the wireless network.

Step 4: Make sure the printer is online and ready

If you have the HP software installed, you can check the printer's status from your computer to see if the printer is paused or offline, preventing you from using it.

To check the printer's status, complete the following steps:

Windows

- 1. Click Start , and then click Printers, Printers and Faxes , or Devices and Printers .
 - Or -

Click Start, click Control Panel, and then double-click Printers.

- Or -

On the Start screen, click Control Panel, and then click View devices and printers.

- **2.** If the printers on your computer are not being displayed in Details view, click the **View** menu, and then click **Details**.
- **3.** Do one of the following, depending on the printer status:
 - a. If the printer is **Offline**, right-click the printer, and click **Use Printer Online**.
 - **b.** If the printer is **Paused**, right-click the printer, and click **Resume Printing**.
- **4.** Try using the printer over the network.

Mac OS X

- Click System Preferences in the Dock, and then click Print & Fax or Print & Scan.
- **2.** Select the printer, and then click **Open Print Queue**.

- **3.** If the print job is on hold, click **Resume**.
- **4.** If the printer is paused, click **Resume Printer**.

If you can use the printer after performing the steps above but find that the symptoms persist as you continue to use the printer, your firewall might be interfering.

If you still cannot use the printer over the network, continue to the next section for additional troubleshooting help.

Step 5: Make sure the HP printer labeled (Network) is set as the default printer driver (Windows only)

If you install the HP software again, the installer might create a second version of the printer driver in your **Printers, Print & Fax**, **Devices and Printers, View devices and printers** folder. If you have difficulties printing or connecting to the printer, make sure the correct version of the printer driver is set as the default.

- 1. Click Start, and then click Printers, Printers and Faxes, or Devices and Printers.
 - Or -

Click **Start**, click **Control Panel**, and then double-click **Printers**.

- Or -

On the **Start** screen, click **Control Panel**, and then click **View devices and printers**.

- 2. Right-click the printer icon for the version of the printer driver that is connected wirelessly, and select **Set as Default Printer**.
- **NOTE:** If there is more than one icon in the folder for the printer, right-click the printer icon for the version of the printer driver that is connected wirelessly, and select **Set as Default Printer**.

Step 6: Check to see if the firewall software is blocking communication

Temporarily turn off the firewall security software running on your computer, and then try to print, scan, or fax to see if the communication is established.

TIP: If you are using a computer running Windows, use the HP Print and Scan Doctor to help diagnose and get assistance in installing and using HP printers on home network. To use this tool, visit the HP Wireless Printing Center www.hp.com/go/wirelessprinting, and then click Print and Scan Doctor in the Quick Links section.

Alternatively, the Firewall Help also provides the detailed information about firewall troubleshooting. For more information, visit the HP Wireless Printing Center www.hp.com/go/wirelessprinting, and then click Firewall Help in the Wireless Network Help section.

After resolving the problems

After you resolve any problems and have successfully connected the printer to your wireless network, complete the following steps for your operating system:

Windows

1. On the computer desktop, click **Start**, select **Programs** or **All Programs**, click **HP**, select your printer name, and then click **Printer Setup & Software**.

- Or -

ENWW Solve network problems 75

On the Start screen, click Printer Setup & Software.

2. Click Connect a new printer, and then select the type of connection you want to use.

Mac OS X

76

- 1. Open HP Utility. For more information, see HP Utility (Mac OS X) on page 148.
- 2. Click the **Applications** icon on the HP Utility toolbar, double-click **HP Setup Assistant**, and then follow the on-screen instructions.

Reset the Printer Network Settings

To reset the printer network settings, complete the following steps:

- 1. Press and hold the (1) (Wireless) button and the × (Cancel) button for three seconds.
- 2. Press the (Network Information) button to print the network configuration page and verify that the network settings have been reset. By default, the network name (SSID) is "HP-Print-**-Officejet 7110", where "** is a random number generated by the printer, and the communication mode is "infrastructure."
- **NOTE:** Previously configured wireless settings are removed after you reset the printer network settings. You have to reconnect the printer to the wireless network using the Wireless Setup Wizard. For more information, see <u>Set up the printer using the embedded web server (EWS) on page 140</u>.
- **TIP:** You can visit the HP online support website at www.hp.com/support for information and utilities that can help you correct many common printer problems.

Chapter 5 Solve a problem ENWW

Troubleshoot installation issues

If the following topics do not help, see HP support on page 48 for information about HP support.

- Hardware installation suggestions
- HP software installation suggestions

Hardware installation suggestions

Check the printer

- Make sure that all packing tape and material have been removed from outside and inside the printer.
- Make sure that the printer is loaded with paper.
- Make sure that no lights are on or blinking except the Power light, which should be on.

Check the hardware connections

- Make sure that any cords and cables that you are using are in good working order.
- Make sure that the power cord is connected securely to both the printer and to a working power outlet.

Check the ink cartridges

Make sure that all of the ink cartridges are firmly installed and aligned in their correct, color-coded slot. A correctly installed ink cartridge should not move when pulled slightly. The printer cannot work if all the ink cartridges are not installed.

HP software installation suggestions

Check the computer system

- Make sure that your computer is running one of the supported operating systems.
- Make sure that the computer meets at least the minimum system requirements.
- In Windows Device Manager, make sure that the USB drivers have not been disabled.
- If you are using a computer running Windows, and the computer cannot detect the printer, run the uninstallation utility (util\ccc\uninstall.bat on the installation CD) to perform a complete uninstallation of the printer driver. Restart your computer, and reinstall the printer driver.

Verify installation preliminaries

- Make sure to use the installation CD that contains the correct HP software for your operating system.
- Before installing HP software, make sure that all other programs are closed.
- If the computer does not recognize the path to the CD-ROM drive that you type, make sure that you are specifying the correct drive letter.
- If the computer cannot recognize the installation CD in the CD-ROM drive, inspect the installation CD for damage. You can download the printer driver from the HP website www.hp.com/support . This website provides information and utilities that can help you correct many common printer problems.



NOTE: After correcting any problems, run the installation program again.

Understand the Printer Status Report


Use the printer status report to view current printer information and ink cartridge status. Also use the printer status report to help you troubleshoot problems with the printer.

The printer status report also contains a log of recent events.

If you need to call HP, print the printer status report before calling.

To print the Printer Status Report

Press and hold the X (Cancel) button for three seconds.



- 1. **Product Information:** Shows printer information (such as the printer name, model number, serial number, and firmware version number), the accessories that are installed (such as the duplexer), and the number of pages printed from the trays and accessories.
- 2. **Print Usage Information:** Shows summary information about pages printed from the printer.


- **3. Ink Delivery System Information:** Shows the estimated ink levels (represented in graphical form as gauges) and the part numbers and Warranty expiration dates of the ink cartridges.
- **NOTE:** Ink level warnings and indicators provide estimates for planning purposes only. When you receive a low-ink warning message, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace cartridges until prompted to do so.
- **4. Additional Assistance:** Shows where to find more help for using your printer.

Understand the network configuration page

If the printer is connected to a network, you can print a network configuration page to view the network settings for the printer and a list of networks detected by your printer. You can use the network configuration page to help troubleshoot network connectivity problems. If you need to call HP, it is often useful to print this page before calling.

To print the network configuration page from the printer control panel

• Press the \P (Network Information) button to print the network configuration page.



- **1. WPS PIN:** Shows the WPS PIN for you to set up the printer on your wireless network using the PIN Method.
- **2. General Information:** Shows information about the current status and active connection type of the network and other information, such as the URL of the embedded web server.
- **802.3 Wired:** Shows information about the active Ethernet network connection, such as the IP address, subnet mask, default gateway, as well as the hardware address of the printer.

82

- **4. 802.11 Wireless:** Shows information about your wireless network connection, such as the host name, IP address, subnet mask, default gateway, and server. It also indicates the network name (SSID), the relative signal strengths and the channels being used. You can check the network list to view if your own network signal strength is good and change the wireless communication setup using embedded web server (EWS). For more information, see <u>Set up the printer using the embedded web server (EWS) on page 140</u>.
- **5. Wireless Direct:** Shows information about your Wireless Direct Printing connection, such as the network name (SSID), IP address, subnet mask, default gateway, and server.
- Miscellaneous: Shows information about more advanced network settings.
 - Port 9100: The printer supports raw IP printing through TCP Port 9100. This HP-proprietary TCP/IP
 port on the printer is the default port for printing. It is accessed by HP software (for example, the
 HP Standard Port).
 - Bonjour: Bonjour services (which use mDNS, or Multicast Domain Name System) are typically used on small networks for IP address and name resolution (through UDP port 5353), where a conventional DNS server is not used.
 - SLP: Service Location Protocol (SLP) is an Internet standard network protocol that provides
 a framework to allow networking applications to discover the existence, location, and
 configuration of networked services in enterprise networks. This protocol simplifies discovery and
 use of network resources such as printers, web servers, fax machines, video cameras, files
 systems, backup devices (tape drives), databases, directories, mail servers, calendars.
 - Microsoft Web Services: Enable or disable the Microsoft Web Services Dynamic Discovery (WS
 Discovery) protocols or Microsoft Web Services for Devices (WSD) Print services supported on the
 printer. Disable unused print services to prevent access through those services.
 - NOTE: For more information about WS Discovery and WSD Print, visit www.microsoft.com.
 - IPP: Internet Printing Protocol (IPP) is a standard network protocol for remote printing. Unlike other remote IP-based protocols, IPP supports access control, authentication, and encryption, allowing for more secure printing.

Printhead maintenance

If you are experiencing problems with printing, you might have a problem with the printhead. You should perform the procedures in the following sections only when directed to do so for resolving print quality issues.

Performing the aligning and cleaning procedures unnecessarily can waste ink and shorten the life of the cartridges.

This section contains the following topics:

- Clean the printhead
- Align the printhead

Clean the printhead

If your printed output is streaked or has any incorrect or missing colors, the printhead might need to be cleaned.

There are two stages of cleaning. Each stage lasts about two minutes, uses one sheet of paper, and uses an increasing amount of ink. After each stage, review the quality of the printed page. You should only initiate the next phase of cleaning if the print quality is poor.

If print quality still seems poor after you complete both stages of cleaning, try aligning the printer. If print quality problems persist after cleaning and aligning, contact HP support. For more information, see HP support on page 48.



84

NOTE: Cleaning uses ink, so clean the printheads only when necessary. The cleaning process takes a few minutes. Some noise might be generated in the process. Before cleaning the printheads, make sure you load paper. For more information, see Load paper on page 11.

Not turning the printer off correctly can cause print quality problems. For more information, see Turn the printer off on page 14.

To clean the printhead from the embedded web server (EWS)

- Open the EWS. For more information, see Embedded web server on page 149.
- Click the **Tools** tab, and then click **Print Quality Toolbox** in the **Utilities** section.
- 3. Click **Clean Printhead** and follow the on-screen instructions.

To clean the printhead from Toolbox (Windows)

- Load Letter, A4, or Legal unused plain white paper into the main input tray. For more information, see Load standard-size paper on page 11.
- 2. Open Toolbox. For more information, see Open the Toolbox on page 147.
- 3. From the **Device Services** tab, click the icon to the left of **Clean Printheads**.
- Follow the on-screen instructions.

To clean the printhead from HP Utility (Mac OS X)

- 1. Open HP Utility. For more information, see HP Utility (Mac OS X) on page 148.
- 2. In the Information And Support section, click Clean Printheads.
- 3. Click **Clean**, and then follow the on-screen instructions.

Align the printhead

The printer automatically aligns the printhead during the initial setup.

You might want to use this feature when the printer status page shows streaking or white lines through any of the blocks of color or if you are having print quality issues with your printouts.

To align the printhead from the printer control panel

- **1.** Load letter, A4, or legal unused plain white paper into the main input tray.
- 2. On the printer control panel, press and hold the () (Power) button.
- **3.** Press the (Resume) button three times.

To align the printhead from the embedded web server (EWS)

- 1. Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the **Tools** tab, and then click **Print Quality Toolbox** in the **Utilities** section.
- 3. Click **Align Printer** and follow the on-screen instructions.

To align the printhead from Toolbox (Windows)

- 1. Load Letter, A4, or Legal unused plain white paper into the main input tray. For more information, see Load standard-size paper on page 11.
- 2. Open Toolbox. For more information, see Open the Toolbox on page 147.
- 3. From the **Device Services** tab, click the icon to the left of **Align Printheads**.
- 4. Follow the on-screen instructions.

To align the printhead from HP Utility (Mac OS X)

- 1. Open HP Utility. For more information, see HP Utility (Mac OS X) on page 148.
- 2. In the **Information And Support** section, click **Align**.
- **3.** Click **Align**, and then follow the on-screen instructions.

ENWW Printhead maintenance

85

Uninstall and reinstall the HP software

If your installation is incomplete, or if you connected the USB cable to the computer before prompted by the HP software installation screen, you might need to uninstall and then reinstall the HP software that came with the printer. Do not simply delete the printer application files from your computer. Make sure to remove them correctly using the uninstall utility provided when you installed the HP software.

To uninstall from a Windows computer, method 1

- Disconnect the printer from your computer. Do not connect it to your computer until after you have reinstalled the HP software.
- 2. On the computer desktop, click **Start**, select **Programs** or **All Programs**, click **HP**, click the printer name, and then click **Uninstall**.
- 3. Follow the on-screen instructions.
- **4.** If you are asked whether you would like to remove shared files, click **No**.

Other programs that use these files might not work correctly if the files are deleted.

- **5.** Restart your computer.
- **6.** To reinstall the HP software, insert the HP software CD into your computer's CD drive, and follow the onscreen instructions.
- **7.** Connect the printer when the HP software prompts you to connect it to the computer.
- 8. Press the (1) (Power) button to turn the printer on.

After connecting and turning on the printer, you might have to wait several minutes for all of the Plug and Play events to complete.

9. Follow the on-screen instructions.

To uninstall from a Windows computer, method 2

- **NOTE:** Use this method if **Uninstall** is not available in the Windows Start menu.
 - On the computer desktop, click Start, select Settings, click Control Panel, and then click Add/Remove Programs.
 - Or -

Click **Start**, click **Control Panel**, and then click **Uninstall a Program** or double-click **Programs and Features**.

- Or -

On the Start screen, click Control Panel, and then click Uninstall a program.

- 2. Select the HP printer software, and then click **Uninstall**.
 - Follow the on-screen instructions.
- **3.** Disconnect the printer from your computer.
- **4.** Restart your computer.

- NOTE: It is important that you disconnect the printer before restarting your computer. Do not connect the printer to your computer until after you have reinstalled the HP software.
- Insert the HP software CD into your computer's CD drive and then start the Setup program.
- Follow the on-screen instructions.

To uninstall from a Mac computer

- Double-click the HP Uninstaller icon (located in the Hewlett-Packard folder in the Applications folder at the top level of the hard disk), and then click **Continue**.
- When prompted, type the correct administrator's name and password, and then click **OK**. 2.
- 3. Follow the on-screen instructions.
- When the **HP Uninstaller** finishes, restart your computer.

Clear jams

Occasionally, paper becomes jammed during a job.

This section contains the following topics:

- Clear paper jams
- Avoid paper jams

Clear paper jams


CAUTION: To prevent possible damage to the printhead, clear paper jams as soon as possible.

TIP: If you notice poor print quality, clean the printhead. For more information, see <u>Clean the printhead</u> on page 84.

To clear a jam

Use these steps to clear a paper jam.

- 1. Remove all papers from the output tray.
- **2.** Push the handle on either side of the rear access panel (or duplexer,) and then pull the panel (or duplexer) towards you.




CAUTION: Trying to clear a paper jam from the front of the printer can damage the print mechanism. Always access and clear paper jams through the rear access panel.

- **3.** Gently pull the paper out of the rollers.
 - CAUTION: If the paper tears when you are removing it from the rollers, check the rollers and wheels for torn pieces of paper that might be remaining inside the printer. If you do not remove all the pieces of paper from the printer, more paper jams are likely to occur.
- **4.** Replace the rear access panel (or the duplexer). Gently push the door (or the duplexer) forward until it snaps into place.
- Check the front of the printer.
 - **a.** Open the ink cartridge access door.

b. If there is paper remaining inside the printer, ensure the carriage has moved to the right of the printer, free any paper scraps or wrinkled paper, and pull the paper towards you through the top of the printer.



c. Move the carriage to the left, locate any jammed paper inside the printer on the right side of the carriage, free any paper scraps or wrinkled paper, and pull the paper towards you through the top of the printer.



- **WARNING!** Do not reach into the printer when it is on and the carriage is stuck. When you open the ink cartridge access door, the carriage should return to its position on the right side of the printer. If it does not move to the right, turn off the printer before you remove any jam.
- **6.** After clearing the jam, close all covers, turn on the printer (if you turned it off) and resend the print job.

Avoid paper jams

To help avoid paper jams, follow these guidelines.

- Remove printed papers from the output tray frequently.
- Make sure that you are printing with paper that is not wrinkled, folded, or damaged.


ENWW Clear jams 89

- Prevent curled or wrinkled paper by storing all unused paper flat in a resealable bag.
- Do not use paper that is too thick or too thin for the printer.
- Ensure that paper loaded in the input tray lays flat and the edges are not bent or torn.
- Make sure that the tray is loaded correctly and is not too full. For more information, see <u>Load paper</u> on page 11.
- Do not combine different paper types and paper sizes in the input tray; the entire stack of paper in the input tray must be the same size and type.
- Adjust the paper guides in the input tray to fit snugly against all paper. Make sure the paper guides does not bend the paper in the input tray.
- Do not force paper too far forward in the input tray.
- If you are printing on both sides of a page, do not print highly saturated images on light weight paper.
- Use paper types that are recommended for the printer. For more information, see <u>Paper specifications</u> on page 102.
- Make sure that the printer is clean.

Control panel lights reference

The control panel lights indicate the status and are useful for diagnosing printing problems. This section contains information about the lights, what they indicate, and what action to take if necessary.

For more information, visit the HP website <u>www.hp.com/support</u> for the latest troubleshooting information, printer fixes, and updates. This website provides information and utilities that can help you correct many common printer problems.



ePrint button 📸 and light 1 2 Ethernet light 👫 3 Wireless button 🙌 and light 4 Network Information button 🐏 5 Cancel button X Resume button and light 6 7 Alert light Ink cartridge lights 8 9 Power button (1) and light

Interpreting control panel lights

Light description/Light pattern	Explanation and recommended action
All lights are off.	The printer is off.
	 Connect the power cable.
	• Press the (1) (Power) button.
The Power light is on.	The printer is ready.
	• No action is required.

The Power light blinks.



The Power light is on, and the Alert light and the Resume light blink.



The Power light is on and the Alert light blinks.



Explanation and recommended action

The printer is turning on or off, or is processing a print job.

No action is required.

The printer is pausing for the ink to dry.

Wait for the ink to dry.

Print paper is jammed in the printer.

Remove all paper from the output tray.
 Locate and clear the jam. For more information, see <u>Clear jams on page 88</u>.

The paper width setting does not match the paper loaded.

 Change the paper setting in the print driver to match the paper loaded. For more information, see <u>Print on special</u> and custom-sized paper on page 27

The printer is out of paper.

 Load paper and press the (Resume) button.

The printer carriage has stalled.


- Open the top cover and remove any obstructions (such as jammed paper).
- Press the (Resume) button to continue printing.
- If the error persists, turn the printer off, and then on again.

A front cover, cleanout, duplexer, or jam door is not closed completely.

 Make sure all covers are completely closed.

Chapter 5 Solve a problem

The Power light is on, the Alert light blinks, and the ink cartridge lights blink one after the other, from left to right.




Explanation and recommended action

The printhead is missing or faulty

- Turn off the printer, and then turn it on again.
- If the error persists, contact HP support for service or replacement. For more information, see <u>HP support</u> on page 48.

The Power light and the Alert light blink, and the ink cartridge lights blink one after the other, from left to right.



• The printhead is incompatible.

- Turn off the printer, and then turn it on again.
- If the error persists, contact HP support for service or replacement. For more information, see <u>HP support</u> on page 48.
- The ink cartridge is faulty, needs attention, incorrect, or incompatible.
 - Ensure the ink cartridge is properly installed, and then try to print. Remove and re-insert the ink cartridge a few times if necessary.
 - If the error persists, replace the ink cartridge.

The Power light is on, the Alert light and one or more of the ink cartridge lights blink.



One or more of the ink cartridges are missing.

- Install the indicated ink cartridge, and then try to print. Remove and re-insert the ink cartridge a few times if necessary.
- If the error persists, replace the indicated ink cartridge.

Ink level is depleted.


 Replace the indicated ink cartridge. For ordering information, see <u>Supplies</u> on page 133.

NOTE: You do not need to replace the ink cartridges until you are prompted to.

The Power light is on and one or more of the ink cartridge lights are on.



The Power light is on, and the Resume light and one or more ink cartridge lights blink.



Explanation and recommended action

One or more of the ink cartridges are low on ink and will need to be replaced soon.

NOTE: Ink level alerts and indicators provide estimates for planning purposes only. When you receive a low-ink alert, consider having a replacement cartridge available to avoid possible printing delays.

One or more ink cartridges are out of ink.

- If the black ink cartridge or one or more color ink cartridges are out of ink, continue to print using the remaining ink cartridges, but the printer will print more slowly. Also, the quality of printed documents might be affected.
 For more information, see <u>Printing with</u> <u>black or color ink only on page 42</u>.
- If both the black ink cartridge and a color ink cartridge are out of ink, purchase new ink cartridges and replace the depleted ones when prompted to do so. For information on how to install new cartridges, see Replace the ink cartridges on page 43.

One or more used, refilled, or counterfeit ink cartridges are detected.

 Either replace the refilled or non-HP cartridges with original HP ink cartridges, or press the (Resume) button to continue using the cartridge. For more information, see Replace the ink cartridges on page 43.

All lights blink.



The HP ePrint light is off.



A non-recoverable error has occurred. Unplug the power cord, and then plug the power cord back in, and try printing.

HP ePrint has not been set up.

To set up HP ePrint, press the (HP) ePrint) button, and then follow the instructions on the information page that prints.

HP ePrint has been set up but has been turned off.

To turn on HP ePrint, press the (HP ePrint) button.

HP ePrint is turned on but is unable to connect.

 HP ePrint is unable to connect, possibly because the server is unavailable or

Explanation and recommended action

the network is not functioning properly.

If your network uses proxy settings when connecting to the Internet, make sure the proxy settings you are entering are valid. For more information, see the getting started guide provided with the printer or check with the IT administrator or person who set up your network.

Press the (HP ePrint) button to try connecting again.

- If the printer can connect, the HP ePrint light turns on, and the printer prints an information page.
- If the printer still cannot connect, the HP ePrint light blinks and then turns off, and the printer prints an information page.

HP ePrint has been set up but has been turned off because the printer has not been updated.

 If a mandatory update for the printer is available but has not been installed, HP ePrint is turned off. After the update has been installed, HP ePrint turns on automatically.

For more information about installing the printer update, press the (HP ePrint) button.

The HP ePrint light is on.



HP ePrint is turned on.

If you press the (HP ePrint) button once, the printer prints an information page that includes the email address you will use for printing documents using HP ePrint.

To turn off HP ePrint, press and hold the (HP ePrint) button. The light blinks for five seconds before turning off.

The HP ePrint light blinks.



HP ePrint is trying to connect.

The HP ePrint light blinks when you turn on or turn off HP ePrint.

If HP ePrint is able to connect successfully, the light blinks and then turns on. If HP ePrint cannot connect, the light blinks and then turns off.

A Technical information

This section contains the following topics:

- Warranty information
- Printer specifications
- Regulatory information
- Environmental product stewardship program
- Third-party licenses

ENWW 97

Warranty information

This section contains the following topics:

- Hewlett-Packard limited warranty statement
- Ink cartridge warranty information

Hewlett-Packard limited warranty statement

HP product	Duration of limited warranty
Software Media	90 days
Printer	1 year
Print or Ink cartridges	Until the HP ink is depleted or the "end of warranty" date printed on the cartridge has been reached, whichever occurs first. This warranty does not cover HP ink products that have been refilled, remanufactured, refurbished, misused, or tampered with.
Printheads (only applies to products with customer replaceable printheads)	1 year
Accessories	1 year unless otherwise stated

- Extent of limited warranty
 Hewlett-Packard (HP) warrants to the end-user customer that the HP products specified above will be free from defects in materials and workmanship for the duration specified above, which duration begins on the date of purchase by the customer.

 - 2. For software products, HP's limited warranty applies only to a failure to execute programming instructions. HP does not warrant that the operation of any product will be interrupted or error free.

 3. HP's limited warranty covers only those defects that arise as a result of normal use of the product, and does not cover any other problems, including those that arise as a result of:

 a. Improper maintenance or modification;

 - Software, media, parts, or supplies not provided or supported by HP;
 - Operation outside the product's specifications;
 - d. Unauthorized modification or misuse.
 - Unauthonized modification or misuse.
 For HP printer products, the use of a non-HP cartridge or a refilled cartridge does not affect either the warranty to the customer or any HP support contract with the customer. However, if printer failure or damage is attributable to the use of a non-HP or refilled cartridge or an expired link cartridge, HP will charge its standard time and materials charges to service the printer for the particular failure or damage.
 If HP receives, during the applicable warranty period, notice of a defect in any product which is covered by HP's warranty, HP shall either repair or replace the product, at HP's option.

 - 6. If HP is unable to repair or replace, as applicable, a defective product which is covered by HP's warranty, HP shall, within a reasonable time after being notified of the defect, refund the purchase price for the product.
 7. HP shall have no obligation to repair, replace, or refund until the customer returns the defective product to HI.

 - 8. Any replacement product may be either new or like-new, provided that it has functionality at least equal to that of

 - 8. Any replacement product may be easier new or interact, postated an activation of the product being replaced.

 9. HP products may contain remanufactured parts, components, or materials equivalent to new in performance.

 10. HP's Limited Warranty Statement is valid in any country where the covered HP product is distributed by HP. Contracts for additional warranty services, such as on-site service, may be available from any authorized HP service facility in countries where the product is distributed by HP or by an authorized importer.

B. Limitations of warranty

TO THE EXTENT ALLOWED BY LOCAL LAW, NEITHER HP NOR ITS THIRD PARTY SUPPLIERS MAKES ANY OTHER WARRANTY OR CONDITION OF ANY KIND, WHETHER EXPRESS OR IMPLIED WARRANTIES OR CONDITIONS OF MERCHANTABILITY, SATISFACTORY QUALITY, AND FITNESS FOR A PARTICULAR

C. Limitations of liability

- To the extent allowed by local law, the remedies provided in this Warranty Statement are the customer's sole and exclusive remedies
- 2. TO THE EXTENT ALLOWED BY LOCAL LAW, EXCEPT FOR THE OBLIGATIONS SPECIFICALLY SET FORTH IN THIS WARRANTY STATEMENT, IN NO EVENT SHALL HP OR ITS THIRD PARTY SUPPLIERS BE LIABLE FOR DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, WHETHER BASED ON CONTRACT, TORT, OR ANY OTHER LEGAL THEORY AND WHETHER ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

D. Local law

- This Warranty Statement gives the customer specific legal rights. The customer may also have other rights
 which vary from state to state in the United States, from province to province in Canada, and from country to country elsewhere in the world.
- To the extent that this Warranty Statement is inconsistent with local law, this Warranty Statement shall be deemed modified to be consistent with such local law. Under such local law, certain disclaimers and limitations of this Warranty Statement may not apply to the customer. For example, some states in the United States, as well as some governments outside the United States (including provinces in Canada), may:

 a. Preclude the discialmers and limitations in this Warranty Statement from limiting the statutory rights of a
 - consumer (e.g., the United Kingdom);
 - Otherwise restrict the ability of a manufacturer to enforce such disclaimers or limitations; or
 - Grant the customer additional warranty rights, specify the duration of implied warranties which the
 manufacturer cannot disclaim, or allow limitations on the duration of implied warranties.
- 3. THE TERMS IN THIS WARRANTY STATEMENT, EXCEPT TO THE EXTENT LAWFULLY PERMITTED, DO NOT EXCLUDE, RESTRICT, OR MODIFY, AND ARE IN ADDITION TO, THE MANDATORY STATUTORY RIGHTS APPLICABLE TO THE SALE OF THE HP PRODUCTS TO SUCH CUSTOMERS. HP Limited Warranty

The name and address of the HP entity responsible for the performance of the HP Limited Warranty in your country is as


United Kingdom: Hewlett-Packard Ltd Cain Road Bracknell GB-Berks RG12 1HN Eire: Hewlett-Packard Ireland Limited, 63-74 Sir John Rogerson's Quay, Dublin 2 Maita: Hewlett-Packard International Trade B.V. Maita Branch, 48, Amery Street, Silema SLM 1701, MALTA

You may have additional statutory rights against the seller based on your purchase agreement. Those rights are not in any way affected by this HP Limited Warranty.

Ink cartridge warranty information

The HP cartridge warranty is applicable when the product is used in its designated HP printing device. This warranty does not cover HP ink products that have been refilled, remanufactured, refurbished, misused, or tampered with.

ENWW Warranty information During the warranty period the product is covered as long as the HP ink is not depleted and the end of warranty date has not been reached. The end of warranty date, in YYYY-MM format, may be found on the product as indicated:



Printer specifications

This section contains the following topics:

- Physical specifications
- Product features and capacities
- Processor and memory specifications
- System requirements
- Network protocol specifications
- Embedded web server specifications
- Paper specifications
- Print resolution
- HP ePrint and HP website specifications
- Environmental specifications
- <u>Electrical specifications</u>
- Acoustic emission specifications

Physical specifications

Printer size (width x height x depth)

585 x 189 x 419 mm (23 x 7.4 x 16.5 inches)

Printer weight (does not include printing supplies)

• 8.1 kg (17.9 lb)

Product features and capacities

Feature	Capacity	
Connectivity	USB 2.0-compliant high speed	
	• Wireless (802.11b/g/n ¹) network	
	Ethernet(802.3) network	
	¹ This product supports the 802.11n 2.4 GHz frequency band.	
Print method	Drop-on-demand thermal inkjet printing	
Ink cartridges	Four ink cartridges (one each for black, cyan, magenta, and yellow)	
	NOTE: Not all ink cartridges are supported in all countries/ regions.	
Printheads	One printhead	

ENWW Printer specifications 101

Feature	Capacity
Supply yields	Visit <u>www.hp.com/go/learnaboutsupplies/</u> for more information on estimated ink cartridge yields.
Printer languages	HP PCL 3
Font support	US fonts: CG Times, CG Times Italic, Universe, Universe Italic, Courier, Courier Italic, Letter Gothic, Letter Gothic Italic.
Duty cycle	Up to 12,000 pages per month

Processor and memory specifications

Printer processor

ARM R4

Printer memory

128 MB built-in RAM

System requirements

Software and system requirements are located in the Readme file.



Network protocol specifications

Software and system requirements are located in the Readme file.

Embedded web server specifications

Requirements

- A TCP/IP-based network (IPX/SPX-based networks are not supported)
- A web browser (either Microsoft Internet Explorer 7.0 or higher, Mozilla Firefox 3.0 or higher, Safari 3.0 or higher, or Google Chrome 5.0 or higher)
- A network connection (cannot be used with a printer connected to a computer using a USB cable)
- An Internet connection (required for some features)
- **NOTE:** You can open the embedded web server without being connected to the Internet. However, some features are not available.
- **NOTE:** The embedded web server must be on the same side of a firewall as the printer.

Paper specifications

Use these tables to determine the correct paper to use with your printer, and determine what features work with your paper.

- Understand specifications for supported paper
- Set minimum margins
- Guidelines for printing on both sides of a page

Understand specifications for supported paper

Use the tables to determine the correct paper to use with your printer, and to determine what features work with your paper.

- Understand supported sizes
- <u>Understand supported paper types and weights</u>

Understand supported sizes

TIP: If you are using the duplexer, the minimum top and bottom margins must be at least 16 mm (0.63 inches).

Input tray	Duplexer
~	
~	
V	✓
~	✓
V	✓
V	✓
V	✓
~	
✓	✓
V	✓
V	
V	
✓	
✓	✓
✓	
✓	✓
~	✓

ENWW Printer specifications 103

Paper size	Input tray	Duplexer
Super B (13 x 19 inches) *	V	
A3 (297 x 420 mm; 11.69 x 16.54 inches) *	V	✓
A3+ (330 x 483 mm; 12.99 x 18.98 inches) *	V	
Edge-to-Edge Tabloid (11 x 17 inches)*	V	
Edge-to-Edge A3*	V	
Envelopes		
U.S. #10 Envelope (105 x 241 mm; 4.12 x 9.5 inches)	V	
Monarch Envelope (98 x 191 mm; 3.88 x 7.5 inches)	✓	
No. 6 3/4 Envelope (92 x 165 mm; 3.63 x 6.5 inches)	V	
Card Envelope (111 x 152 mm; 4.4 x 6 inches)	V	
A2 Envelope (111 x 146 mm; 4.37 x 5.75 inches)	✓	
DL Envelope (110 x 220 mm; 4.3 x 8.7 inches)	V	
C5 Envelope (162 x 229 mm; 6.4 x 9 inches)		
C6 Envelope (114 x 162 mm; 4.5 x 6.4 inches)	✓	
Japanese Envelope Chou #3 (120 x 235 mm; 4.7 x 9.3 inches)	V	
Japanese Envelope Chou #4 (90 x 205 mm; 3.5 x 8.1 inches)	V	
Cards		
Index card (76.2 x 127 mm; 3 x 5 inches)	V	
Index card (102 x 152 mm; 4 x 6 inches)	V	
Index card (127 x 203 mm; 5 x 8 inches)	V	
A6 card (105 x 148.5 mm; 4.13 x 5.83 inches)*	✓	
A6 card (105 x 148.5 mm; 4.13 x 5.83 inches) *	V	
A4 index card (210 x 297 mm; 8.3 x 11.7 inches)	V	
Letter index card (8.5 x 11 inches)	V	
Hagaki (100 x 148 mm; 3.9 x 5.8 inches) **	✓	
Also supports Borderless printing.		
Ofuku Hagaki (200 x 148 mm; 7.8 x 5.8 inches) **	V	
Photo paper		
Photo paper (76.2 x 127 mm; 3 x 5 inches)	✓	
Photo paper (102 x 152 mm; 4 x 6 inches) *		

Paper size	Input tray	Duplexer
Photo paper (5 x 7 inches) *	V	
Photo paper (8 x 10 inches) *	V	
Photo paper (8.5 x 11 inches) *	V	
Photo L (89 x 127 mm; 3.5 x 5 inches) *	V	
Photo 2L (127 x 178 mm) *	✓	
Cabinet size (120x165mm)*	✓	
13 x 18 cm *	✓	
Brochures		
B5 (JIS) (182 x 257 mm; 7.17 x 10.12 inches) *	V	✓
11 x 14 inches*	✓	✓
Tabloid (11 x 17 inches) *	✓	✓
A3 (297 x 420 mm; 11.69 x 16.54 inches) *	V	✓
Other paper		
NOTE: Defining custom-size paper sizes is only available in the	HP printing software in M	ac OS X.
Custom-sized paper between 76.2 to 330 mm wide and 127 to 1118 mm long (3 to 13 inches wide and 5 to 44 inches long)	~	

^{*}These sizes can be used for borderless printing.

Understand supported paper types and weights

Tray	Туре	Weight	Capacity
Input tray	Paper	60 to 105 g/m ²	Up to 250 sheets of 20lb
		(16 to 28 lb bond)	HP Multipurpose Paper
		,	(25 mm or 1 inch stacked)
	Photo paper	280 gsm	Up to 60 sheets of 280 gsm
	(75 lb bond)	HP Premium Plus Photo Paper	
	(75 to Solite)	(17 mm or 0.67 inch stacked)	
	Envelopes	75 to 90 g/m²	Up to 30 sheets
		(20 to 24 lb bond envelope)	(17 mm or 0.67 inch stacked)
	Cards	Up to 200 g/m²	Up to 80 cards
		(110 lb index)	


ENWW Printer specifications 105

^{**} The printer is compatible with plain and inkjet hagaki from Japan Post only. It is not compatible with photo hagaki from Japan Post.

Tray	Type	Weight	Capacity
	Brochures	180 gsm	Up to 65 sheets of 180 gsm HP Brochure and Flyer Paper Matte
Duplexer	Plain and brochure	60 to 180 g/m²	Not applicable
		(16 to 48 lb bond)	
Output-tray	All supported paper		Up to 75 sheets of plain paper (text printing)

Set minimum margins

The document margins must match (or exceed) these margin settings in portrait orientation.



Paper	(1) Left margin	(2) Right margin	(3) Top margin	(4) Bottom margin
U.S. Letter	3.3 mm (0.13 inch)	3.3 mm (0.13 inch)	3.3 mm (0.13 inch)	3.3 mm (0.13 inch) Windows and
U.S. Legal				12mm (0.47 inch)
A4				Mac and Linux
U.S. Executive				
U.S. Statement				
8.5 x 13 inch				
B5				
A5				
Cards				
Custom-sized paper				
Photo paper				

Paper	(1) Left margin	(2) Right margin	(3) Top margin	(4) Bottom margin
11 x 14 inches	5 mm (0.197 inch) ¹	5 mm (0.197 inch) ¹	5 mm (0.197 inch) ²	5 mm (0.197 inch) ²
12 x 12 Inches				
B4 (JIS)				
Tabloid				
Super B				
A3				
A3+				
Edge-to-Edge Tabloid				
Edge-to-Edge A3				
Envelopes	3.3 mm (0.13 inch)	3.3 mm (0.13 inch)	16.5 mm (0.65 inch)	16.5 mm (0.65 inch)

¹ The margins for plain and brochure paper are 13 mm (0.51 inch) for simplex and duplex.

Guidelines for printing on both sides of a page

- Always use paper that conforms to the printer specifications. For more information, see <u>Paper</u> specifications on page 102.
- Specify two-sided printing options in your application or in the printer driver.
- Do not print on both sides of envelopes, photo paper, glossy paper, or paper lighter than 16 lb bond (60 g/m²) or heavier than 28 lb bond (105 g/m²). Jams might occur with these paper types.
- Several kinds of papers require a specific orientation when you print on both sides of a page. These
 include letterhead, preprinted paper, and paper with watermarks and prepunched holes. When you print
 from a computer running Windows, the printer prints the first side of the paper first. Load the paper with
 the print side facing down.
- For auto-duplexing, when printing finishes on one side of the paper, the printer holds the paper and
 pauses while the ink dries. Once the ink dries, the paper is pulled back into the printer and the second
 side is printed. When printing is complete, the paper is dropped onto the output tray. Do not grab it
 before printing is complete.
- You can print on both sides of supported custom-size paper by turning the paper over and feeding it into the printer again. For more information, see <u>Paper specifications on page 102</u>.

Print resolution

Table A-1 Print resolution

Draft mode	•	Color Input/Black Render: 300x300dpi
	•	Output (Black/Color): Automatic

ENWW Printer specifications 107

² The margins for plain paper are 16 mm (0.63 inch) for simplex and 22 mm (0.87 inch) for duplex. For brochure paper, the margins are 16 mm (0.63 inch) for simplex and duplex.

Table A-1 Print resolution (continued)

Normal mode	• (Color Input/Black Render: 600x600dpi	
	• (Output (Black/Color): Automatic	
Best mode	• (Color Input/Black Render: 600x600dpi	
	• (Output (Black/Color): Automatic	
Max DPI mode	• (Color Input/Black Render: 1200x1200dpi	
	• (Output: Automatic (Black), 4800x1200 optimized dpi (Color)	


HP ePrint and HP website specifications

This section contains the following topics:


- **HP** ePrint specifications
- **HP** website specifications

HP ePrint specifications

- An Internet connection using either an Ethernet or wireless connection.
- Maximum size of email and attachments: 5 MB
- Maximum number of attachments: 10



- Supported file types:
 - PDF
 - HTML
 - Standard text file formats
 - Microsoft Word, PowerPoint
 - Image files, such as PNG, JPEG, TIFF, GIF, BMP



HP website specifications

- A web browser (either Microsoft Internet Explorer 6.0 or higher, Mozilla Firefox 2.0 or higher, Safari 3.2.3 or higher, or Google Chrome 3.0) with the Adobe Flash plug-in (version 10 or higher).
- An Internet connection

Environmental specifications

Operating environment

Operating temperature: 5° to 40° C (41° to 104° F)

Recommended operating conditions: 15° to 32° C (59° to 90° F)

Recommended relative humidity: 25 to 75% noncondensing

Storage environment

Storage temperature: -40° to 60° C (-40° to 140° F)

Storage relative humidity: Up to 90% noncondensing at a temperature of 60° C (140° F)

Electrical specifications

Power supply

Universal power adapter (external)

Power requirements

Input voltage: 100 to 240 VAC (± 10%), 50/60 Hz (± 3 Hz) (Worldwide); 200 to 240 VAC, 50/60 Hz (China and India only)

Output voltage: +32Vdc / +12Vdc (1094mA / 250mA)

Power consumption

30 watts printing (Fast Draft Mode)

Acoustic emission specifications

Print in Draft mode, noise levels per ISO 7779

- Sound pressure (bystander position)
 - LpAm 54 (dBA) (mono Draft print)
- Sound power
 - LwAd 6.7 (BA)

ENWW Printer specifications 109

Regulatory information

The printer meets product requirements from regulatory agencies in your country/region.

This section contains the following topics:

- Regulatory model number
- **FCC** statement
- Notice to users in Korea
- VCCI (Class B) compliance statement for users in Japan
- Notice to users in Japan about the power cord
- Noise emission statement for Germany
- **GS** Declaration (Germany)
- **European Union Regulatory Notice**
- **Regulatory information for wireless products**
 - **Exposure to radio frequency radiation**
 - Notice to users in Brazil
 - Notice to users in Canada
 - Notice to users in Taiwan
 - Notice to users in Mexico
 - Notice to users in Japan

Regulatory model number

For regulatory identification purposes, your product is assigned a Regulatory Model Number. The Regulatory Model Number for your product is SNPRC-1103-02. This regulatory number should not be confused with the marketing name (HP Officeiet 7110 Wide Format ePrinter) or product number (CR768A).

FCC statement

FCC statement

The United States Federal Communications Commission (in 47 CFR 15.105) has specified that the following notice be brought to the attention of users of this product.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and the receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

For further information, contact:

Manager of Corporate Product Regulations Hewlett-Packard Company 3000 Hanover Street Palo Alto, Ca 94304 (650) 857-1501

Modifications (part 15.21)

The FCC requires the user to be notified that any changes or modifications made to this device that are not expressly approved by HP may void the user's authority to operate the

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Notice to users in Korea

B 급 기기

이 기기는 가정용(B급)으로 전자파적합등록을 한 기기로서 주 로 가정에서 사용하는 것을 목적으로 하며. (가정용 방송통신기기) 모든 지역에서 사 용할 수 있습니다.

VCCI (Class B) compliance statement for users in Japan

この装置は、クラスB情報技術装置です。この装置は、家庭環境で使用することを目的として いますが、この装置がラジオやテレビジョン受信機に近接して使用されると、受信障害を引き 起こすことがあります。取扱説明書に従って正しい取り扱いをして下さい。

VCCI-B

Notice to users in Japan about the power cord

製品には、同梱された電源コードをお使い下さい。 同梱された電源コードは、他の製品では使用出来ません。

Noise emission statement for Germany

Geräuschemission

LpA < 70 dB am Arbeitsplatz im Normalbetrieb nach DIN 45635 T. 19

GS Declaration (Germany)

GS-Erklärung (Deutschland)

Das Gerät ist nicht für die Benutzung im unmittelbaren Gesichtsfeld am Bildschirmarbeitsplatz vorgesehen. Um störende Reflexionen am Bildschirmarbeitsplatz zu vermeiden, darf dieses Produkt nicht im unmittelbaren Gesichtsfeld platziert werden.

European Union Regulatory Notice

Products bearing the CE marking comply with the following EU Directives:

- Low Voltage Directive 2006/95/EC
- EMC Directive 2004/108/EC
- Ecodesign Directive 2009/125/EC, where applicable

CE compliance of this product is valid if powered with the correct CE-marked AC adapter provided by HP.

If this product has wired and/or wireless telecommunications functionality, it also complies with the essential requirements of the following EU Directive:

R&TTE Directive 1999/5/EC

Compliance with these directives implies conformity to applicable harmonized European standards (European Norms) that are listed in the EU Declaration of Conformity issued by HP for this product or product family and available (in English only) either within the product documentation or at the following web site: www.hp.com/go/certificates (type the product number in the search field).

The compliance is indicated by one of the following conformity markings placed on the product:

C€	For non-telecommunications products and for EU harmonized telecommunications products, such as Bluetooth® within power class below 10mW.			
C € ①	For EU non-harmonized telecommunications products (If applicable, a 4-digit notified body number is inserted between CE and !).			

Please refer to the regulatory label provided on the product.

The telecommunications functionality of this product may be used in the following EU and EFTA countries: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Liechtenstein, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovak Republic, Slovenia, Spain, Sweden, Switzerland, and United Kingdom.

The telephone connector (not available for all products) is intended for connection to analogue telephone networks.

Products with wireless LAN devices

 Some countries may have specific obligations or special requirements about the operation of Wireless LAN networks such as indoor use only or restrictions of the channels available. Please make sure that the country settings of the wireless network are correct.

France

For 2.4-GHz Wireless LAN operation of this product, certain restrictions apply: This product may be used indoors for the entire 2400-MHz to 2483.5-MHz frequency band (channels 1 to 13). For outdoor use, only the 2400-MHz to 2454-MHz frequency band (channels 1 to 7) may be used. For the latest requirements, see www.arcep.fr.

The point of contact for regulatory matters is:

Hewlett-Packard GmbH, Dept./MS: HQ-TRE, Herrenberger Strasse 140, 71034 Boeblingen, GERMANY

Regulatory information for wireless products

This section contains the following regulatory information pertaining to wireless products:

- Exposure to radio frequency radiation
- Notice to users in Brazil
- Notice to users in Canada
- Notice to users in Taiwan
- Notice to users in Mexico
- Notice to users in Japan

Exposure to radio frequency radiation

Exposure to radio frequency radiation



Caution The radiated output power of this device is far below the FCC radio frequency exposure limits. Nevertheless, the device shall be used in such a manner that the potential for human contact during normal operation is minimized. This product and any attached external antenna, if supported, shall be placed in such a manner to minimize the potential for human contact during normal operation. In order to avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antenna shall not be less than 20 cm (8 inches) during normal operation.

ENWW Regulatory information 113

Notice to users in Brazil

Aviso aos usuários no Brasil

Este equipamento opera em caráter secundário, isto é, não tem direito à proteção contra interferência prejudicial, mesmo de estações do mesmo tipo, e não pode causar interferência a sistemas operando em caráter primário. (Res.ANATEL 282/2001).

Notice to users in Canada

Notice to users in Canada/Note à l'attention des utilisateurs canadiens

Under Industry Canada regulations, this radio transmitter may only operate using an antenna of a type and maximum (or lesser) gain approved for the transmitter by Industry Canada. To reduce potential radio interference to other users, the antenna type and its gain should be so chosen that the equivalent isotropically radiated power (e.i.r.p.) is not more than that necessary for successful communication.

This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device.

WARNING! Exposure to Radio Frequency Radiation The radiated output power of this device is below the Industry Canada radio frequency exposure limits. Nevertheless, the device should be used in such a manner that the potential for human contact is minimized during normal operation.

To avoid the possibility of exceeding the Industry Canada radio frequency exposure limits, human proximity to the antennas should not be less than 20 cm (8 inches).

Conformément au Règlement d'Industrie Canada, cet émetteur radioélectrique ne peut fonctionner qu'avec une antenne d'un type et d'un gain maximum (ou moindre) approuvé par Industrie Canada. Afin de réduire le brouillage radioélectrique potentiel pour d'autres utilisateurs, le type d'antenne et son gain doivent être choisis de manière à ce que la puissance isotrope rayonnée équivalente (p.i.r.e.) ne dépasse pas celle nécessaire à une communication réussie.

Cet appareil est conforme aux normes RSS exemptes de licence d'Industrie Canada. Son fonctionnement dépend des deux conditions suivantes : (1) cet appareil ne doit pas provoquer d'interférences nuisibles et (2) doit accepter toutes interférences reçues, y compris des interférences pouvant provoquer un fonctionnement non souhaité de l'appareil.

AVERTISSEMENT relatif à l'exposition aux radiofréquences. La puissance de rayonnement de cet appareil se trouve sous les limites d'exposition de radiofréquences d'Industrie Canada. Néanmoins, cet appareil doit être utilisé de telle sorte qu'il soit mis en contact le moins possible avec le corps humain.

Afin d'éviter le dépassement éventuel des limites d'exposition aux radiofréquences d'Industrie Canada, il est recommandé de maintenir une distance de plus de 20 cm entre les antennes et l'utilisateur.

Notice to users in Taiwan

低功率電波輻射性電機管理辦法

第十二條

經型式認證合格之低功率射頻電機,非經許可,公司、商號或使用者均不得擅自變更頻 率、加大功率或變更設計之特性及功能。

第十四條

低功率射頻電機之使用不得影響飛航安全及干擾合法通信;經發現有干擾現象時,應立 即停用,並改善至無干擾時方得繼續使用。

前項合法通信,指依電信法規定作業之無線電通信。低功率射頻電機須忍受合法通信或 工業、科學及醫藥用電波輻射性電機設備之干擾。

Notice to users in Mexico

Aviso para los usuarios de México

La operación de este equipo está sujeta a las siguientes dos condiciones: (1) es posible que este equipo o dispositivo no cause interferencia perjudicial y (2) este equipo o dispositivo debe aceptar cualquier interferencia, incluyendo la que pueda causar su operación no deseada.

Para saber el modelo de la tarjeta inalámbrica utilizada, revise la etiqueta regulatoria de la impresora.

Notice to users in Japan

この機器は技術基準適合証明又は工事設計認証を受けた無線設備を搭載しています。

Environmental product stewardship program

Hewlett-Packard is committed to providing quality products in an environmentally sustainable manner:

- Design for recycling has been incorporated into this product.
- The number of materials has been kept to a minimum while ensuring proper functionality and reliability.
- Dissimilar materials have been designed to separate easily.
- Fasteners and other connections are easy to locate, access, and remove using common tools.
- High priority parts have been designed to access quickly for efficient disassembly and repair.

For more information, visit www.hp.com/ecosolutions

This section contains the following topics:

- European Union Commission Regulation 1275/2008
- Paper use
- **Plastics**
- Material safety data sheets
- Recycling program
- HP inkjet supplies recycling program
- Disposal of waste equipment by users in private households in the European Union
- Power consumption
- **Chemical Substances**
- **Battery information**
- RoHS notices (China only)
- RoHS notices (Ukraine only)

European Union Commission Regulation 1275/2008

For product power data, including the power consumption of the product in networked standby if all wired network ports are connected and all wireless network ports are activated, please refer to section P14 'Additional Information' of the product IT ECO Declaration at www.hp.com/hpinfo/globalcitizenship/ environment/productdata/itecodesktop-pc.html.

Paper use

This product is suited for the use of recycled paper according to DIN 19309 and EN 12281:2002.

Plastics

Plastic parts over 25 grams are marked according to international standards that enhance the ability to identify plastics for recycling purposes at the end of product life.

Material safety data sheets

Material safety data sheets (MSDS) can be obtained from the HP Web site at:

www.hp.com/go/msds

Recycling program

HP offers an increasing number of product return and recycling programs in many countries/regions, and partners with some of the largest electronic recycling centers throughout the world. HP conserves resources by reselling some of its most popular products. For more information regarding recycling of HP products, please visit:

www.hp.com/hpinfo/globalcitizenship/environment/recycle/

HP inkjet supplies recycling program

HP is committed to protecting the environment. The HP Inkjet Supplies Recycling Program is available in many countries/regions, and lets you recycle used print cartridges and ink cartridges free of charge. For more information, go to the following Web site:

www.hp.com/hpinfo/globalcitizenship/environment/recycle/

Disposal of waste equipment by users in private households in the European Union



Disposal of Waste Equipment by Users in Private Households in the European Union
This symbol on the product or on its packaging indicates that this product must not be disposed of with your other household waste. Instead, it is your responsibility to dispose of your waste expired to hording it over to a designated collection point for the encyding of waste electrical and electroric equipment. The supported collection and recycling of your waste expired in the lime of disposal with high to conserve ratival resources and enserve that it is neverthed in an enamed heal protest furname health and the environment, for more information about whe you can drop of your waste equipment for recycling, please contact your local city office, your household waste the hop where you purchased the product.

Securation des équipements usagés par les utilisateurs dans les foyers privés au sein de l'Union européenne
La présence de ce symbole sur le produit ou sur son emballage indique que vous ne pouvez par vous débarrasser de ce produit de la même façon que vos déchets courants.
Au contraire, vous êtes reopresable de l'évacación de vos équipements usagés e, à cet effet, vous étes teru dementér à un point de callecte agrée pour le recyclage des équipements édectiques et éactiques et éactiques et éactiques et éactiques et éactiques usagés. Le hi, l'évacuation et le recyclage séparés de vos équipements suggés permetent de préserver les resources naturelles et de s'assure que ces équipements sont recycles des les équipements sont recycles des les des équipements au le magain du vous arez achété le aractia.

vote many, votre service de traitement des deschets nenages not le registrin ou vous arvez achtet le produit.

Entitorgung von Elektrogerähen durch Bronizer in privatien Haushaltun in der Elektrogerähen der Bronizer in privatien Haushaltun in der Elektrogerähen Produkt oder dessen Verpackung gibt an, dass das Padukt nicht zusammen nit dem Restmüll ertsorgt werden darf. Es abliegt daher Ihrer Verantwartung, destit an einer entsprechence solelle für die Entorgung oder Wiederverwert nig von Elektrogerähen der Art abzugeben (z.B. ein Werstsoffhol). Die separate Sammlung und aus Rescrieh Ihrer allen Elektrogerähe zum Zeitpunkt finet Entorgung intägt zum Schutz der Umweit bei und gewährleitelt, dass sie auf eine Art und Weise ercycelt werden, die keine Gefährdung für die Gesundhalt des Merschen und der Umweit damtellt. Weiser ein Fromationen darüber, wo Sie alte Elektrogerähe zum Recyceln abgeben können, erhalten Sie bei den Behörden, Wertstoffholen oder dort, wo Sie das Gerät erworben haben.

centralization electronic, vertectionate operator, se activaries revirates nation.

Smallimento di appareschiature de rottamere da parte di privotti nell'Unione Europea

Questa simbolo che apparesuli prodotto a sulla confezione indica che il procotto non deve essere smallita

smallimento delle appareschiature de rottamene postandole al luogo di roccotto indicato per il ricicloggio delle appareschiature de arottamene postandole al luogo di roccotto indicato per il ricicloggio delle appareschiature de arottamene in fese di smallimento ferenziazione della indicato per il ricicloggio delle appareschiature de rottamene in fese di smallimento ferenziazione della sisseme naturali a granviazione che bili appareschiature wargeno rottamato

nel ispatto della dembierte de della tutale della solate. Per utilenti informazioni in i punti di roccotto della appareschiature da rottamare, contattare il provio comune di residenza,
il servizio di smallimento dei rifiuti locale o il regozio presso il quale è stato acquistato il prodotto.

Eliminación de residuos de aparetos eléctricos y electrónicos par parte de usuarios domésticos en la Unión Europea Este simbola en el producto a en el embaloje indica que no se puede deserbar el producto junto con los residuos domésticos. De rel contrario, si debe eliminar este tipo de residuo, es responsibilidad de usuario entregarlo en un purto ce recogidad desegnado os recicidado de apartores electrónicos. De recidios y la recogida por reparado de estos residuos en el mamento de la eliminación ayudarda a preservar recursos anturdes electronicos que el reciciós proteja la solud y el media ambiente. Si desec información adicional sobre los lugares donde puede dejar relos nesidous para su miciclado, pórgase en corriscio con las autoridades locacides de cutadod, con el eservicio de gestific de residuos demensicos con al las contracidades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensicos con las autoridades locacides de cutadod, con el eservicio de gestifica de residuos demensións con las autoridades locacides de cutadod, con el eservicio de gestifica el eservicio de gestifica de residuos demensións con las autoridades locacides de cutados, con el eservicio de gestifica de recidios demensións con las autoridades locacides de cutados, con el eservicio de gestifica de recidios demensións con el eservicio de las electros describes de las electros de la electros de la electros de las electros de las electros de las electros de las el

nema aomae adquiro el praducto.

Ikuldace vyelausšláho zařízoní ušívateli v domácností v zemích EU

Tak znacka na produktu něso na jeho obalu oznacije, že tento produkt nesmí byl likuldován prostýn vyhozením do běžného domovního odpadu. Odpovidáte za to, že vyslaužílé zařízení bude předáno k likuldoci do stanovených sběrných mist určených k srojklad vyslaužílých elektrických a elektronických zařízení. Likuldace vyslaužílého zařízení samostatným soběem a resyklací napomáho zahování přírodních zdrojí a zajířuje, že resyklací vyslaužílé zařízení předat k sovyklací, můžete záskat ad úřadů místní samosprávy, od společnosti provádějící svoz a likuldací domovního odpadu nebo v obchodě, kde jste pradukt zakusjili.

Botaskaffelse af affaldsudstyr for brugere i private husholdninger i EU
Delts symbol på produktet elser på dels emballage irdikrere, at produktet ikke må borliskaffes sammen med andet husholdningsaffald. I stedet er det di ansvar at bortskaffe affoldsudstyr
det at allevere del på dertil beregnede indsamlingsseder med herblik på genbrug af elskrinsk og elskronisk affoldsudstyr. Den separate indsamling ag genbrug af dit affoldsudstyr på
tidspunistet for bortskaffelse er med til at bevære natuliga ensanner og sikke, at genbrug finder sted på en måde, der beskyrte mennesken helberd som i miljæet. Hvis du vil vice mere
om, have du kan aflevere dit fillodsudstyr i gjenbrug finden sted på en måde, der beskyrte av du batte produktet.

**Tortile og delta for delta

Afvoer van afgedankte apparatuur door gebruikers in particuliere huishoudens in de Europese Unie
Di symbool op het product of de verpekking geeft and dat die product niet may worden afgedandelis, drive. Het is uw verantwoordelijtheid uw afgedankte apparat of le ieveren op een aangewezen inzameljunt voor de verwerking van afgedankte elektrische en elektronische apparatuur. De gescheiden izameling en verwerking van uw agsedan apparatuur draagt bij tot het spoen van andurunglie beronnen en tot het heregelenische van autorische avore uw van disedands apparatuur draagt bij tot het spoen van andurunglie beronnen en tot het heregelenische van unterstand op een wijze de volksgesconheid en het millie beschemt. Voor meer informatie uwar u uw afgedankte apparatuur kunt inleween voor recycling kunt u contad opnemen met het gemeertefnuis in uw woorpicats, de reinigingsdierst of de wirkel waar u het product hebt aangescheid.

Eranajapidamistes kasutuselt kõrvaldatavate seadmete käitlemine Euroopa Liidus
Kui toole palandili on see sümbol, ei lohi seda toodet visata olmejätimete huku. Teie kohu on viia tarbetuks muuturud seade selleks ettenähtud elektri- ja elektroonikaseadmete
ulliseeriniskohla. Ulliseeritorate seadmete eratid kogumine ja käitlemine alab säästa loodusvarasid ning tagada, et käitlemine toimub inimeste tervisele ja teekkorraale ohutut.
Lisaeavet selle kohta, kuhu saale ulliseerinisya seadmete käitlemiseks viia, saate käisea kohalikset omaalitusest, olmejäätmete ulliseerinisyantiist või kauplusest, kut te seadme

Hävitettävien laitteiden käsittely kotitalouksissa Euroopan unionin alueella
Tärä tuotiessa tai sen pakkusksessa oleva merkintä osaitiaa, että tuoteta ei saa hävittää talousjätteiden mukana. Käyttäjän vekollisuus on huolehta iiitä, että hävitettävä laits
tairittataan sähkö- ja elektroniikkalaiteromun keräyspäteessen. Hävitettävien bittieden erillinen keräysja kierrätys sääsitää luonnonvaraja. Näin toimimalla varmistetaan myös,
että kierrätys tapahtuu tavalta, joka suojelee ihmisten terveyttä ja ympäristöä. Saat tarvittaessa läätietaja jäteiden kierrätyspakoista paikallisilta viranomaisilta, jäteyhtiöittä tai tuotteen
jälleenmyyjältä.

Απόρριση όχρηστων συσκευών στην Ευρωταϊκή Έγωση. Το παρόν αυτό δεν πρέπει νε πεταχεί μαζί με άλλα οκιακά απαρρίμματα. Ανείθετα, ευθύνη σας είναι να απορρίμετε τος έχρηστες ουκευίας σε με ακδρασμούς με τος απορρίμετε τος έχρηστες συσκευίας σε με ακδρασμούς γυσκού και ηλικερονικού εξεπλευμού. Η χωρατή αλλογή και απορρίμετε τος έχρηστες συσκευία θα συμβάλει στή διατήρηση των φυσκεύ πόρων και στη διασφάλιση ότι θα σνακειλιματίν με είναι να προσιστέεται η υγεία των συβμάλωση τος έχρηστες συσκευία θα συσκευία θα συσκευία θα συσκευία θα συσκευία συσκευία τος τος τος συσκευία τος τος τος συσκευία συσκευία θα συσκευία δια τος τος τος τος συσκευία που συσκευία τος συσκευία τος τος τος συσκευία τος συσκευία τος τος συσκευία τος συσκε

agya; p. ar tostataminga en to cinica opopodate inpiazov.

A hulladékanyagok kezélése a magánhástartásokban az Európai Unióban.

Ez a szimbólum, amely a teméken vagy arnok csorragolátán von lelitrietve, azi jelzi, hagy a temék nem kezelhető egyült az egyéb háztartási huladékanyagok ás az elektronók a berendezések újrohostrosításával loglalloztik.

A huladékanyagok elkülöniket gyűjése és újrahaztrosítása hozzájárul a ternészeti erőforrások megirzéselhez, egyúttal azt it biztasítja, hagy a hulladék újrahaztrosítási a cz egéséségy és a környesette nem éstenlena motor tötténik. Ha tagáhaztabat assenten kapári asakolt a hayárásávál olyakoltásávál asakoltásávál asakoltásá

Lietotāju arbrīvošanās no nederīgām ierīcēm Eiropa Savienības privātajās mājadīmniecībās.

Se simbās uz ierīces vai lāt iepakojuma norāda, ka so ierīci nedrībal tizmest vapā or pārējiem māja miniecības distribuniem "is esat arbitātīgs par arbrīvosanos no nederīgās erīces, to redadat nordātajā savaitanas vielā, lai tilku veida nederīgās elektrisku ne delektrisku gartiscijuma orinetājā pāretīdas. Speciāla nederīgās ierīces savaitātana un orinetībajā pāretīdas. Speciāla nederīgās ierīces savaitātana un orinetībajā pāretīda palāta taupār delektrisku palāta taupār delektrisku palāta taupār delektrisku palāta palāta palāta palāta izvaitāta palāta palata palāta palā

Europas Sąjungas vartotojų ir privačių namų ūkių atliekamas įrangas lāmetimas.
Sis simbolis art produkto arba jo paksvėtes nurodo, kala produktas negali būti simestas kartu su kitosmis namy ūkio afliekamis, ūs privalote išmesti svoo afliekamą įrangą atliakama terinalis ir ekstronikas riekalinas privalos išmesti paraga bas atskiras varekama ir peratribama, bus tissuogomi natūralias tissultas ir variktinomas, kad jaraga vap perlititot zimogas variktinos privalos is atskiras varekama ir peratribama, bus tissuogomi natūralias tissultas ir variktinomas, kad jaraga vap perlititot zimogas variktinos tarpas paraga taseopanču būdu. Dėl informacijos opie tai, kur galtie išmesti atliekama perdirbti skirią jaraga kreipkilės į attirkamą vietos tarmybą, ramy ūki atliekų sirvalios tarpas quata ja productusų, kuriosi pirkote produktių.

Utylizacja zużytego sprzetu przez użytkowników domowych w Unii Europejskiej Symbol ten umieszczony na produkcie lub opakowariu oznacza, że tego produktu nie rależy wyrz

Symbol ten umieszczeny na pradukcie lub apakowaniu oznacza, że lego praduklu nie należy wyrzucać razem z innymi odpadami domowymi. Użytkownik jet odpowiedzialny za dostarzamie zużytego sprzętu do wyznaczonego punktu gromadzenia zużytych urządzeń elektycznych i elektronicznych, Goomadzenia osobno i recykling lego typu odpadów przyczynia się do odrony zasobów maturalnych i jet bezpierznych gla zdrowia i ratowalnego. Dalsze informacje na tema posobu utylizacji zużytych urządzeń macha uzyklać u odpowiednich władz. lokalnych, w przedziębionitwie zajmującym się usuwaniem odpadów lub w miejscu zakupu produktu.

Descarte de equipmentos por usuários em residências da Unido Européia
Este imbolo no produto ou na embalagem indica que o produto nao pode ser descañado jumo com o lixo domestico. No entanto, e sua responsabilidade levar os equipmentos o serem descardados a um portados a um portados a descardados a um portados a um portados a um portados a descardados a um portados a um portado

Postup používateľ ev v kraljinách Európskej únie pri vyhodzovaní zariadenia v domácom používaní do odpadu

Tenb symbol na produkte alibo na jeho obde zramená, že nesmie by vyhodený s irým komunálnym odpadom. Namiesto loho mále povinnos odovzda toto zariadenie na zberno
mieste, kde s zabezpecije regyládcia elektronických záriadení. Separovaný žive a revyládcia za zabezpeci na odpad pomôže chrání prírodné zdroje c
zabezpeci toký spôsob necyládcia, ktorý bude chrání ľudské zdrové a žkotné prostredné. Dalšie informácie a separovanom zbere a recykládií získate na miestnom obecnom úrade,
vo firme zabezpeciújosí jake veišbo komunálnáho odpodu alebbo v predejní, kde sa produkt kla se produkt kla

Ramanje z odpadno opremo v gospodinjstvih znotraj Evropske unije
Ta znok na izdeku ali embadzi izdekla pomeni, da izdekla ne smete odagoti skapaj z drugimi gospodinjskimi odpadki. Odpadno opremo ste dolizri oddati na določenem zbirmem
mete za necikiranje odpadne sletkrine in ekstorale opreme. Z bosem ziziranjem in necikiranjem odpadne opreme ob odlaganju boste pomagali ohraniti narame vine in zagatovili,
da bo odpadna oprema necikirana istao, da se varuse zdravje ljudi in okolje. Vec informacij o mestih, kjer faloko oddate odpadna opremo za reckliranje, lahko dobite na obć ni,
v komunarieme podejtju dili gayvini, kjer ste izdelek kapili.

Kassering av förbrukningsmaterial, för hem- och privatanvändare i EU
Produkte eller produktirpadvingar med den här symbolen far inte kasseras med vanligt hushälkarfall. I stället har du ansvar för att produkten lämnas till en behärig ätervinningsstation för hantering av 6- och elektronisgrandukter. Genom att lämna kasserade produkter till diervinning hjäper du till att bevara vära gemensamma naturneurser. Dessutam skyddas både miterialen och miljän när produkter ätervinns på rätt sätt. Kommunale myndigheter, sophenteringsfäretag eller buttlan där varan häptes kan ge mer in armation om var du lämnar besamela endeltide för återvinning hanterinningsfäretag eller buttlan där varan häptes kan ge mer in armation om var du lämnar

Изжеърляне на оборудеане за отпадъци ат потребители в часни домакчиства в Европейския съюз
Тоз симал върху продукта или спасоката му показа, че продукта не раба да се исяърга зовун о домакнистие о падъцы. Вме имате отпогрността да изквъртиле
обрудомено за отпадъцы, ило по предодне на отредене пиркта за рециотиране на енестренесо или меженно оборудоне за отпадъци. Отделното събиране и е передорическо или меженно оборудоне за отпадъци. Отделното събиране и е передори на оборудането за отпадъци при изявърпенето му почнота за запазаснието ка природни ресурси и гарантира рециотиране, извършено така, че да не застрашава чаленското
съберане на отпадъци при изявърпенето му почнот за съответ съответния обреждения от отпадъци при изявършено така, че да не застрашава чаленското
съберане на отпадъци или з магазина, от който се закритили продукта

cuargase sa antiagajar una z sacrantent, or konto cis sacynania npogytata
Infaltrurarea achipamentelor uzate de achie etilizazioni casnici dili Uniunea Europeană
Acest similad de pe produc sau de pe embaleija preduculai indicia tepula esi escat produs nu trebuie eruncat alături de celefata depour ceenice. În les să pracedeții astitol, aveți responsabilitătore alăt vi debarantal de achipamentul uzat predadul la un certur de acestatare desenrant pertru reciclarea deșeunior electrice și a echipamentulor ale encelerantelul un acestatore la contratore desenrantelul un acestatore electronice.
Colectarea și recidarea separată a echipamentulul azat atunci când doriți să îl aruncații ajulă la conservarea resunselor naturale și asigură recidarea schipamentului înfro manieră care problejeză sândatea unand și mediul, Pertru informății suplimentare despre locul în care se poale pseda echipamentul uzat pertru recidare, ludți legătura cu primăria locală, cu servicul de solubitariale sau cu vânzătorul de la care ali achizitorul produsul.

Power consumption

Hewlett-Packard printing and imaging equipment marked with the ENERGY STAR® logo is qualified to the U.S. Environmental Protection Agency's ENERGY STAR specifications for imaging equipment. The following mark appears on ENERGY STAR qualified imaging products:



Additional ENERGY STAR qualified imaging product model information is listed at:

www.hp.com/go/energystar

Chemical Substances

HP is committed to providing our customers with information about the chemical substances in our products as needed to comply with legal requirements such as REACH (Regulation EC No 1907/2006 of the European Parliament and the Council). A chemical information report for this product can be found at: www.hp.com/go/ reach.

Battery information

This section contains the following topics:

- Battery disposal in Taiwan
- Attention California users
- Battery disposal in the Netherlands

Battery disposal in Taiwan



廢電池請回收

Please recycle waste batteries.

Attention California users

California Perchlorate Material Notice

Perchlorate material - special handling may apply. See: http://www.dtsc.ca.gov/hazardouswaste/perchlorate/

This product's real-time clock battery or coin cell battery may contain perchlorate and may require special handling when recycled or disposed of in California.

Battery disposal in the Netherlands



Dit HP Product bevat een lithium-manganese-dioxide batterij. Deze bevindt zich op de hoofdprintplaat. Wanneer deze batterij leeg is, moet deze volgens de geldende regels worden afgevoerd.

RoHS notices (China only)

Figure A-1 Toxic and hazardous substance table

	-	电子信息产品		里办法》		
		质和元素				
	铅	汞	镉	六价铬	多溴联苯	多2
	0	0	0	0	0	
1	0	Δ.	_	0	_	

L	零件描述	有毒有害物质和元素					
L		铅	汞	镉	六价铬	多溴联苯	多溴联苯醚
l	外壳和托盘*	0	o	0	0	0	0
L	电线*	0	0	0	0	0	0
L	印刷电路板*	X	0	0	0	0	0
l	打印系统*	Х	0	0	0	0	0
L	显示器*	X	0	0	0	0	0
l	喷墨打印机墨盒*	0	0	0	0	0	0
L	驱动光盘*	Х	0	0	0	0	0
L	扫描仪*	Х	х	٥	0	0	0
l	网络配件*	Х	0	0	0	0	0
L	电池板*	Х	o	0	0	0	0
l	自动双面打印系统*	o	o	Ö	0	Ō	0
l	外部电源*	Х	0	0	0	0	0
1				•			

右害右害物质害

RoHS notices (Ukraine only)

Технічний регламент щодо обмеження використання небезпечних речовин (Україна)

Обладнання відповідає вимогам Технічного регламенту щодо обмеження використання деяких небезпечних речовин в електричному та електронному обладнанні, затвердженого постановою Кабінету Міністрів України від 3 грудня 2008 № 1057

^{0:} 指此部件的所有均一材质中包含的这种有毒有害物质,含量低于SJ/T11363-2006 的限制

X: 指此部件使用的均一材质中至少有一种包含的这种有毒有害物质,含量高于SJ/T11363-2006 的限制注:环保使用期限的参考标识取决于产品正常工作的温度和湿度等条件

^{*}以上只适用于使用这些部件的产品

Third-party licenses

```
LICENSE.aes-pubdom--crypto
/* rijndael-alg-fst.c
* @version 3.0 (December 2000)
* Optimised ANSI C code for the Rijndael cipher (now AES)
* @author Vincent Rijmen <vincent.rijmen@esat.kuleuven.ac.be>
* @author Antoon Bosselaers <antoon.bosselaers@esat.kuleuven.ac.be>
* @author Paulo Barreto <paulo.barreto@terra.com.br>
* This code is hereby placed in the public domain.
* THIS SOFTWARE IS PROVIDED BY THE AUTHORS "AS IS" AND ANY EXPRESS
* OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED
* WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE
* ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHORS OR CONTRIBUTORS BE
* LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
* CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
* SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
* BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
* WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE
* OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE.
* EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.
*/
LICENSE.expat-mit--expat
```

ENWW Third-party licenses 121

Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

LICENSE.hmac-sha2-bsd--nos_crypto

/* HMAC-SHA-224/256/384/512 implementation

* Last update: 06/15/2005

* Issue date: 06/15/2005

* Copyright (C) 2005 Olivier Gay <olivier.gay@a3.epfl.ch>

* All rights reserved.

- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. Neither the name of the project nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- * without specific prior written permission.

*

- * THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS" AND
- * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
- * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
- * PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS
- * BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
- * CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
- * SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR
- * BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY,
- * WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR
- * OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF
- * ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

*/

LICENSE.open_ssl--open_ssl

Copyright (C) 1995-1998 Eric Young (eay@cryptsoft.com)

All rights reserved.

This package is an SSL implementation written

ENWW Third-party licenses 123

by Eric Young (eay@cryptsoft.com).

The implementation was written so as to conform with Netscapes SSL.

This library is free for commercial and non-commercial use as long as the following conditions are aheared to. The following conditions apply to all code found in this distribution, be it the RC4, RSA, lhash, DES, etc., code; not just the SSL code. The SSL documentation included with this distribution is covered by the same copyright terms except that the holder is Tim Hudson (tjh@cryptsoft.com).

Copyright remains Eric Young's, and as such any Copyright notices in the code are not to be removed.

If this package is used in a product, Eric Young should be given attribution as the author of the parts of the library used.

This can be in the form of a textual message at program startup or in documentation (online or textual) provided with the package.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1. Redistributions of source code must retain the copyright notice, this list of conditions and the following disclaimer.
- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3. All advertising materials mentioning features or use of this software must display the following acknowledgement:

"This product includes cryptographic software written by Eric Young (eay@cryptsoft.com)"

The word 'cryptographic' can be left out if the rouines from the library being used are not cryptographic related :-).

4. If you include any Windows specific code (or a derivative thereof) from the apps directory (application code) you must include an acknowledgement: "This product includes software written by Tim Hudson (tjh@cryptsoft.com)"

THIS SOFTWARE IS PROVIDED BY ERIC YOUNG ``AS IS" AND
ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE AUTHOR OR CONTRIBUTORS BE
LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE
POSSIBILITY OF SUCH DAMAGE.

The licence and distribution terms for any publically available version or derivative of this code cannot be changed. i.e. this code cannot simply be copied and put under another distribution licence [including the GNU Public Licence.]

Copyright (c) 1998-2001 The OpenSSL Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

 Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

ENWW Third-party licenses 125

- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3. All advertising materials mentioning features or use of this software must display the following acknowledgment: "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)"
- 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact openssl-core@openssl.org.
- 5. Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.
- 6. Redistributions of any form whatsoever must retain the following acknowledgment:
- "This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/)"

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES;

LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION)
HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT,
STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED
OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes cryptographic software written by Eric Young (eay@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com).

Copyright (c) 1998-2006 The OpenSSL Project. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- 1. Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.
- 2. Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.
- 3. All advertising materials mentioning features or use of this software must display the following acknowledgment:"This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (http://www.openssl.org/)"

ENWW Third-party licenses 127

- 4. The names "OpenSSL Toolkit" and "OpenSSL Project" must not be used to endorse or promote products derived from this software without prior written permission. For written permission, please contact openssl-core@openssl.org.
- 5. Products derived from this software may not be called "OpenSSL" nor may "OpenSSL" appear in their names without prior written permission of the OpenSSL Project.
- 6. Redistributions of any form whatsoever must retain the following acknowledgment:

"This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit (http://www.openssl.org/)"

THIS SOFTWARE IS PROVIDED BY THE OpenSSL PROJECT ``AS IS" AND ANY EXPRESSED OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE OpenSSL PROJECT OR ITS CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

This product includes cryptographic software written by Eric Young (eay@cryptsoft.com). This product includes software written by Tim Hudson (tjh@cryptsoft.com).

Copyright 2002 Sun Microsystems, Inc. ALL RIGHTS RESERVED.

ECC cipher suite support in OpenSSL originally developed by

SUN MICROSYSTEMS, INC., and contributed to the OpenSSL project.

LICENSE.sha2-bsd--nos_crypto

/* FIPS 180-2 SHA-224/256/384/512 implementation

* Last update: 02/02/2007

* Issue date: 04/30/2005

*

- * Copyright (C) 2005, 2007 Olivier Gay <olivier.gay@a3.epfl.ch>
- * All rights reserved.

*

- * Redistribution and use in source and binary forms, with or without
- * modification, are permitted provided that the following conditions
- * are met:
- * 1. Redistributions of source code must retain the above copyright
- * notice, this list of conditions and the following disclaimer.
- * 2. Redistributions in binary form must reproduce the above copyright
- * notice, this list of conditions and the following disclaimer in the
- * documentation and/or other materials provided with the distribution.
- * 3. Neither the name of the project nor the names of its contributors
- * may be used to endorse or promote products derived from this software
- * without specific prior written permission.

*

* THIS SOFTWARE IS PROVIDED BY THE PROJECT AND CONTRIBUTORS ``AS IS" AND

ENWW Third-party licenses 129

- * ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE
- * IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR
- * PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE PROJECT OR CONTRIBUTORS BE
- * LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR
- * CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF
- * SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS
- * INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN
- * CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE)
- * ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF
- * THE POSSIBILITY OF SUCH DAMAGE.

*/

LICENSE.zlib--zlib

zlib.h -- interface of the 'zlib' general purpose compression library version 1.2.3, July 18th, 2005

Copyright (C) 1995-2005 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied warranty. In no event will the authors be held liable for any damages arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.

- 2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
- 3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly Mark Adler jloup@gzip.org madler@alumni.caltech.edu

The data format used by the zlib library is described by RFCs (Request for Comments) 1950 to 1952 in the files http://www.ietf.org/rfc/rfc1950.txt (zlib format), rfc1951.txt (deflate format) and rfc1952.txt (gzip format).

HP supplies and accessories B

This section provides information on HP supplies and accessories for the printer. The information is subject to changes, visit the HP website (www.hpshopping.com) for the latest updates. You may also make purchases through the website.



NOTE: Not all cartridges are available in all countries/regions.

This section contains the following topics:

- Order printing supplies online
- Supplies

ENWW 131

Order printing supplies online

To order supplies online or create a printable shopping list, open the HP software that came with your printer and click **Shopping**. Select **Shop for Supplies Online**. The HP software uploads, with your permission, printer information, including model number, serial number, and estimated ink levels. The HP supplies that work in your printer are pre-selected. You can change quantities, add or remove items, and then print the list or purchase online at the HP Store or other online retailers (options differ by country/region). Cartridge information and links to online shopping also appear on ink alert messages.

You can also order online by visiting www.hp.com/buy/supplies. If prompted, select your country/region, follow the prompts to select your printer, and then the supplies you need.



NOTE: Ordering cartridges online is not supported in all countries/regions. However, many countries have information on ordering by telephone, locating a local store and printing a shopping list. In addition, you can select the 'How to Buy' option at the top of the www.hp.com/buy/supplies page to obtain information about purchasing HP products in your country.

Supplies


- Ink cartridges
- HP paper

Ink cartridges

Ordering cartridges online is not supported in all countries/regions. However, many countries have information on ordering by telephone, locating a local store and printing a shopping list. In addition, you can select the How to Buy option at the top of the www.hp.com/buy/supplies page to obtain information about purchasing HP products in your country.

Use only the replacement cartridges that have the same cartridge number as the ink cartridge you are replacing. You can find the cartridge number in the following places:

- In the embedded web server, click the Tools tab, and then, under Product Information click Ink Gauge.
 For more information, see Embedded web server on page 149.
- On the label of the ink cartridge you are replacing.
- On the printer status page (see Understand the Printer Status Report on page 79).



HP paper

To order paper such as HP Premium Paper, go to www.hp.com.



HP recommends plain papers with the ColorLok logo for printing everyday documents. All papers with the ColorLok logo are independently tested to meet high standards of reliability and print quality, and produce documents with crisp, vivid color, bolder blacks, and that dry faster than ordinary plain papers. Look for papers with the ColorLok logo in a variety of weights and sizes from major paper manufacturers.

C Network setup

You can manage network settings for the printer through the printer control panel as described in the next section. Additional advanced settings are available in the embedded web server, a configuration and status

ENWW Supplies 133

tool you access from your web browser using an existing network connection to the printer. For more information, see <u>Embedded web server on page 149</u>.

This section contains the following topics:

- Change basic network settings
- <u>Change advanced network settings</u>
- Set up the printer for wireless communication
- HP wireless direct printing

Change basic network settings

The control panel options enable you to set up and manage a wireless connection and to perform a variety of network management tasks. This includes viewing the network settings, restoring the network defaults, turning the wireless radio on and off, and changing the network settings.

This section contains the following topics:

- View and print network settings
- Turn the wireless radio on and off

View and print network settings

You can display a summary of the network settings on the HP software that came with the printer. You can print a more detailed network configuration page, which lists all of the important network settings such as the IP address, link speed, DNS, and mDNS. For more information, see <u>Understand the network configuration</u> page on page 81.

Turn the wireless radio on and off

The wireless radio is on by default, as indicated by the blue light on the front of the printer. To stay connected to a wireless network, the radio must stay on. However, if your printer is connected to an Ethernet network or you have a USB connection, the radio is not used. In this case you might want to turn the radio off. To turn the wireless radio off, press and hold the 🕪 (Wireless) button until the light goes off.

Change advanced network settings

CAUTION: Network settings are provided for your convenience. However, you should not change some of these settings (such as the link speed, IP settings, default gateway, and firewall settings).

This section contains the following topics:

- Set link speed
- View IP settings
- Change IP settings
- Reset network settings

Set link speed

You can change the speed at which data is transmitted over the network. The default is **Automatic**.

- 1. Open the embedded web server (EWS). For more information, see Embedded web server on page 149.
- 2. Click the **Network** tab, and then click **Advanced** in the **Wired (802.3)** section.
- 3. In the Link Settings section, click Manual.
- **4.** Click to select the link speed that matches your network hardware:
 - 2. 10-Full
 - 3. 10-Half
 - 4, 100-Full
 - 5. 100-Half

View IP settings

To view the IP address of the printer:

- Print the network configuration page. For more information, see <u>Understand the network configuration</u> page on page 81.
- Or, open the HP software (Windows), click the Network Settings tab, click the Wired or Wireless tab (depending on the current connection), and then click IP Settings.

Change IP settings

The default IP setting for the IP settings is **Automatic**, which sets the IP settings automatically. However, you might want to manually change settings such as the IP address, subnet mask, or the default gateway.

- **CAUTION:** Be careful when manually assigning an IP address. If you enter an invalid IP address during the installation, your network components cannot connect with the printer.
 - 1. Open the embedded web server. For more information, see Embedded web server on page 149.
 - 2. Click the **Network** tab, and then click **IPv4 Configuration** in the **Wired (802.3)** section.
 - 3. In the IP Address Configuration section, click Manual.

- A message appears warning that changing the IP address removes the printer from the network. Click **OK** to continue.
- **5.** Change the IP settings:
 - **Manual IP Address**
 - **Manual Subnet Mask**
 - **Manual Default Gateway**
- Click **Apply**.

Reset network settings

To reset the administrator password and network settings, press and hold the (1) (Wireless) button and the ★ (Cancel) button for three seconds.

NOTE: Print the network configuration page and verify that the network settings have been reset. For more information, see Understand the network configuration page on page 81.

By default, the network name (SSID) is "HP-Print-**-Officejet 7110", where "**" is a random number generated by the printer.

Set up the printer for wireless communication

You can set up the printer for wireless communication.

This section contains the following topics:

- Before you begin
- Set up the printer on your wireless network
- Change the connection type
- Test the wireless connection
- Guidelines for ensuring wireless network security
- Guidelines for reducing interference on a wireless network
- **NOTE:** If you encounter problems connecting the printer, see <u>Solve wireless problems on page 69</u>.
- **TIP:** For more information about setting up and using the printer wirelessly, visit the HP Wireless Printing Center (www.hp.com/go/wirelessprinting).

Before you begin

Before you begin setting up the wireless connection, check the following:

- The printer is not connected to the network using a network cable.
- The wireless network is set up and functioning correctly.
- The printer and the computers that use the printer are on the same network (subnet).

While connecting the printer, you might be prompted to enter the wireless network name (SSID) and a wireless password.

- The wireless network name is the name of your wireless network.
- The wireless password prevents other people from connecting to your wireless network without your permission. Depending on the level of security required, your wireless network might use either a WPA key or WEP passphrase.

If you have not changed the network name or the security passkey since setting up your wireless network, you can sometimes find them on the back or side of the wireless router.

If you cannot find the network name or the security passkey or cannot remember this information, see the documentation available with your computer or with the wireless router. If you still cannot find this information, contact your network administrator or the person who set up the wireless network.

TIP: If you are using a computer running Windows, use the HP Print and Scan Doctor to help diagnose and get assistance in installing and using HP printers on your home network. To use this tool, visit the HP Wireless Printing Center (www.hp.com/go/wirelessprinting), and then click Print and Scan Doctor in the Quick Links section.

Set up the printer on your wireless network

To set up the printer on your wireless network, use one of the following methods:

- Set up the printer using the HP printer software
- Set up the printer using WiFi Protected Setup (WPS)
- Set up the printer using the embedded web server (EWS)
- **NOTE:** Make sure you have installed the HP software that came with the printer and the printer network drives. For more information about how to installed the drives, see After resolving the problems on page 75.
- **NOTE:** If you have already been using the printer with a different type of connection, such as a USB connection, follow the instructions in Change the connection type on page 140 to set up the printer on your wireless network.


Set up the printer using the HP printer software

In addition to enabling key printer features, you can use the HP printer software that came with your printer to set up wireless communication.

If you have already been using the printer with a different type of connection, such as a USB connection, follow the instructions in Change the connection type on page 140 to set up the printer on your wireless network.

Set up the printer using WiFi Protected Setup (WPS)

Wi-Fi Protected Setup (WPS) allows you to quickly set up the printer on your wireless network, without having to enter the wireless network name (SSID), wireless password (WPA passphrase, WEP key), or other wireless settings.



NOTE: To use WPS, make sure your wireless router or wireless access point supports WPS. Routers that support WPS often have a **WPS**) button or a button labeled "WPS".

You can use one of the following methods to set up the printer using WPS:

- **Push Button Method:** Use the **(WPS)** or WPS button, if available, on your router.
- **PIN Method:** Enter the PIN generated by the printer in the router's configuration software.

To connect the printer using the Push Button Method

- On the printer control panel, press and hold the (1) (Wireless) button for 3 seconds. The wireless light starts blinking.
- On the wireless router or wireless access point, press and hold the WPS button for 3 seconds.

Wait for about 2 minutes. If the printer connects successfully, the wireless light stops blinking but remains lit.

To connect the printer using the PIN Method

- Print the network configuration page and locate the pin for WPS. For more information, see Understand the network configuration page on page 81.
 - A WPS PIN is printed at the top of the page.
- On the printer control panel, press and hold the (1) (Wireless) button for 3 seconds. The Wireless light starts blinking.
- Open the configuration utility or software for the wireless router or wireless access point, and then enter the WPS PIN.
- **NOTE:** For more information about using the configuration utility, see the documentation provided with the router or wireless access point.

Wait for about 2 minutes. If the printer connects successfully, the wireless light stops blinking but remains lit.

Set up the printer using the embedded web server (EWS)

If the printer is connected to a network, you can use the printer's embedded web server (EWS) to set up wireless communication.

- Open the EWS. For more information, see Embedded web server on page 149.
- On the **Home** tab, click **Wireless Setup Wizard** in the **Setup** box. 2.
- 3. Follow the on-screen instructions.
- \Im **TIP:** You can also set up wireless communication by entering or changing individual wireless settings. To change these settings, on the Network tab, click Advanced in the Wireless (802.11) section on the left, change the wireless settings, and then click Apply.

Change the connection type

After you have installed the HP software and connected the printer to your computer or to a network, you can use the HP software to change the connection type (for example, from a USB connection to a wireless connection).



NOTE: If you are changing to a wireless connection, make sure that an Ethernet cable has not been connected to the printer. Connecting an Ethernet cable turns off the printer's wireless capabilities. Also, you might be prompted to temporarily connect a USB cable during the setup process.

To change the connection type, do one of the following:

- To change from an Ethernet connection to a wireless connection
- To change from a USB connection to a wireless connection
- To change from a wireless connection to a USB or Ethernet connection

To change from an Ethernet connection to a wireless connection

Windows

On the computer desktop, click Start, select Programs or All Programs, click HP, select your printer name, and then click **Printer Setup & Software**.

- Or -

On the Start screen, click Printer Setup & Software.

- Click **Connect a new printer**, and then select the type of connection you want to use. 2.
- Follow the display instructions to complete the setup. 3.

Mac OS X

- 1. Open HP Utility. For more information, see HP Utility (Mac OS X) on page 148.
- Click the **Applications** icon on the HP Utility toolbar. 2.
- Double-click **HP Setup Assistant**, and then follow the on-screen instructions.

To change from a USB connection to a wireless connection

Follow the instructions for your operating system.

Windows

On the computer desktop, click Start, select Programs or All Programs, click HP, select your printer name, and then click **Printer Setup & Software**.

- Or -

On the Start screen, click Printer Setup & Software.

- 2. Click Convert a USB connected printer to wireless.
- 3. Follow the display instructions to complete the setup.

Mac OS X

- 1. Open HP Utility. For more information, see HP Utility (Mac OS X) on page 148.
- 2. Click the **Applications** icon on the HP Utility toolbar.
- Double-click **HP Setup Assistant**, and then follow the on-screen instructions. 3.

To change from a wireless connection to a USB or Ethernet connection

To change from a wireless connection to a USB or Ethernet connection, connect the USB or Ethernet cable to the printer.

NOTE: If you are using a computer with Mac OS X, add the printer to the print queue. Click **System** Preferences in the Dock, click Print & Fax or Print & Scan in the Hardware section, click +, and then select the printer.

Test the wireless connection

Print the wireless test page for information about the printer's wireless connection. The wireless test page provides information about the printer's status, hardware (MAC) address, and IP address. If the printer is connected to a network, the test page displays details about the network settings.

To print the wireless test page, press the 🌇 (Network Information) button when the network is enabled.

Guidelines for ensuring wireless network security

The following information can help you keep your wireless network and wireless printer secure from unauthorized use.

For more information, visit www.hp.com/go/wirelessprinting.

This section contains the following topics:

- Overview of security settings
- Add hardware addresses to a wireless router (MAC filtering)
- Other wireless security guidelines

Overview of security settings

To help improve the security of the wireless network and prevent unauthorized access, the printer supports many common types of network authentication, including WEP, WPA, and WPA2.

- WEP: Provides security by encrypting data sent over radio waves from one wireless device to another wireless device. Devices on a WEP-enabled network use WEP keys to encode data. If your network uses WEP, you must know the WEP key(s) it uses.
- WPA: Increases the level of over-the-air data protection and access control on existing and future wireless networks. It addresses all known weaknesses of WEP, the original native security mechanism in the 802.11 standard. WPA uses the Temporal Key Integrity Protocol (TKIP) for encryption and employs 802.1X authentication with one of the standard Extensible Authentication Protocol (EAP) types available today.
- WPA2: Provides enterprise and consumer wireless users with a high level of assurance that only authorized users can access their wireless networks. WPA2 provides the Advanced Encryption Standard (AES). AES is defined in counter cipher-block chaining mode (CCM) and supports the Independent Basic Service Set (IBSS) to enable security between client workstations operating connected wirelessly without a wireless router (such as a Linksys wireless router or Apple AirPort Base Station).

Add hardware addresses to a wireless router (MAC filtering)

MAC filtering is a security feature in which a wireless router or wireless access point is configured with a list of hardware addresses (also called "MAC addresses") of devices that are allowed to gain access to the network through the router.

If the router filters hardware addresses, then the printer's hardware address must be added to the router's list of accepted hardware addresses. If the router does not have the hardware address of a printer attempting to access the network, the router denies the printer access to the network.

CAUTION: This method is not recommended, however, because your MAC addresses can easily be read and falsified by unwanted users outside your network.

To add hard addresses to a wireless router or wireless access point

- Print the network configuration page, and then locate the printer's hardware address. For more information, see Understand the network configuration page on page 81.
- **NOTE:** The printer maintains separate hardware addresses for the Ethernet connection and for wireless connection. Both hardware addresses are listed on the printer's network configuration page.
- Open the configuration utility for the wireless router or wireless access point, and add the printer's hardware address to the list of accepted hardware addresses.
- **NOTE:** For more information about using the configuration utility, see the documentation provided with the router or wireless access point.

Other wireless security guidelines

To keep the wireless network secure, follow these guidelines:

- Use a wireless password with at least 20 random characters. You can use up to 64 characters in a wireless password.
- Avoid any common words or phrases, easy sequences of characters (such as all 1s), and personallyidentifiable information for wireless passwords. Always use random strings composed of uppercase and lowercase letters, numbers, and if allowed, special characters such as punctuation.
- Change the default wireless password provided by the manufacturer for administrator access to the access point or wireless router. Some routers let you change the administrator name as well.
- Turn off administrative access over wireless if possible. If you do this, you need to connect to the router with an Ethernet connection when you want to make configuration changes.
- Turn off remote administrative access over the Internet on your router, if possible. You can use Remote Desktop to make an encrypted connection to a computer running behind your router and make configuration changes from the local computer you are accessing over the Internet.
- To avoid accidentally connecting to another party's wireless network, turn off the setting to automatically connect to non-preferred networks. This is disabled by default in Windows XP.

Guidelines for reducing interference on a wireless network

The following tips will help reduce the chances for interference in a wireless network:

- Keep the wireless devices away from large metal objects, such as filing cabinets, and other electromagnetic devices, such as microwaves and cordless telephones, as these objects can disrupt radio signals.
- Keep the wireless devices away from large masonry structures and other building structures as these objects can absorb radio waves and lower signal strength.
- Position the access point or wireless router in a central location in line of sight with the wireless devices on the network.
- Keep all wireless devices on the network within range of one another.

HP wireless direct printing

With HP wireless direct printing, you can print wirelessly from a computer, smart phone, tablet, or other wireless-capable device—without connecting to an existing wireless network.

When using HP wireless direct printing, note the following guidelines:

- Make sure your computer or mobile device has the necessary software:
 - If you are using a computer, make sure you have installed the HP printer software provided with the printer.
- If you are using a mobile device, make sure you have installed a compatible printing app. For more information about mobile printing, visit www.hp.com/global/us/en/eprint/mobile_printing_apps.html.
- Make sure HP wireless direct printing is turned on in the printer and, if necessary, security is enabled. For more information, see Turn on HP wireless direct printing on page 144.
- Up to five computers and mobile devices can use the same HP wireless direct printing connection.
- HP wireless direct printing can be used while the printer is also connected to a computer using USB cable or to a network (using a wireless or Ethernet connection).
- HP wireless direct printing cannot be used to connect a computer, mobile device, or printer to the Internet.



Click here to go online for more information.

For more information about wireless printing, see Set up the printer using the embedded web server (EWS) on page 140.



NOTE: At this time, these websites might not be available in all languages.

This section contains the following topics:

- Turn on HP wireless direct printing
- Print from a wireless-capable mobile device
- Print from a wireless-capable computer

Turn on HP wireless direct printing

- Open the EWS. For more information, see Embedded web server on page 149.
- 2. Click the **Network** tab.
- In the Wireless Direct Printing section, click Status.
- Select On (with security) or On (without security) from the Wireless Direct Printing Status.
- $rac{1}{2}$ **TIP:** If you would like to use HP wireless direct printing with greater security and if the computer or mobile device supports WPA2 encryption, select the option that will enable security. With security enabled, only users with the password can connect wirelessly to the printer. Without enabling security, anyone with a wireless device within the wireless range of the printer can connect to the printer.
- Click **Apply**.

Print from a wireless-capable mobile device

Make sure you have installed a compatible printing app on your mobile device. For more information, visit www.hp.com/global/us/en/eprint/mobile_printing_apps.html.

- Make sure you have turned on HP wireless direct printing on the printer. For more information, see Turn on HP wireless direct printing on page 144.
- Turn on the wireless connection in your mobile device. For more information, see the documentation provided with the mobile device.
- From the mobile device, search for and connect to the HP wireless direct printing name, such as HP-Print-**-Officejet 7110 series (where ** are the unique characters to identify your printer).
 - If HP wireless direct is turned on with security, enter the password when prompted.
- From your mobile device's print app, confirm your HP printer is the default printer, and then print your document.

Print from a wireless-capable computer

Follow the instructions for your operating system.

- Print from a wireless-capable computer (Windows)
- Print from a wireless-capable computer (Mac OS X)

Print from a wireless-capable computer (Windows)

- Make sure you have turned on HP wireless direct printing on the printer. For more information, see Turn on HP wireless direct printing on page 144.
- Turn on the wireless connection in your computer. For more information, see the documentation provided with the computer.
- From the computer, click the wireless icon on your task tray, select the HP wireless direct printing name, such as HP-Print-**-Officejet 7110 series (where ** are the unique characters to identify your printer).
 - If HP wireless direct is turned on with security, enter the password when prompted.
- If the printer has been installed and connected to your computer with a USB cable, enable HP wireless direct printing in the HP printer software. Proceed to step 5 if the printer has been installed and connected to the computer over a network (Ethernet or wireless).
 - From the computer desktop, click Start, select Programs or All Programs, click HP, click the folder for the printer, and then select **Printer Setup & Software**.
 - Or -

On the Start screen, right-click an empty area on the screen, click All Apps on the app bar, and then click the icon with the printer's name.

Select Connect New Printer.

When the **Connection Options** software screen appears, select **Wireless**.

Select the printer from the list of detected printers, such as HP-Print-**-Officejet 7110 series (where ** are the unique characters to identify your printer).

- Follow the on-screen instructions.
- Print your document. 5.

Print from a wireless-capable computer (Mac OS X)

- Make sure you have turned on HP wireless direct printing on the printer. For more information, see Turn on HP wireless direct printing on page 144.
- Turn on AirPort. For more information, see the documentation provided by Apple. 2.
- Click the AirPort icon and select the HP wireless direct printing name, such as HP-Print-**-Officejet 7110 3. series (where ** are the unique characters to identify your printer).

If HP wireless direct is turned on with security, enter the password when prompted.

- Add the printer.
 - In System Preferences, select Print & Fax or Print & Scan, depending on your operating system.
 - Click + below the list of printers at the left. b.
 - Select the printer from the list of detected printers (the word "Bonjour" is listed the right column beside the printer name), and click **Add**.
- Print your document. 5.

Printer management tools D

This section contains the following topics:

- Toolbox (Windows)
- HP Utility (Mac OS X)
- Embedded web server

Toolbox (Windows)

The Toolbox provides maintenance information about the printer.

NOTE: The Toolbox can be installed from the HP Software CD if the computer meets the system requirements.

Open the Toolbox

Open the Toolbox

- Open the HP printer software by doing one of the following:
 - From the computer desktop, click Start, select Programs or All Programs, click HP, click the folder for the printer, and then select the icon with the printer's name.
 - On the **Start** screen, right-click an empty area on the screen, click **All Apps** on the app bar, and then click the icon with the printer's name.
- In the window that appears, select Print, Scan & Fax or Print & Scan, and then select Maintain Your Printer under Print.

ENWW Toolbox (Windows) 147

HP Utility (Mac OS X)

HP Utility contains tools to configure print settings, calibrate the printer, order supplies online, and find website support information.



NOTE: The features available in HP Utility vary depending on the selected printer.

Ink level warnings and indicators provide estimates for planning purposes only. When you receive a low-ink warning message, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace cartridges until prompted to do so.

To open HP Utility

Double-click the HP Utility icon. This icon is located in the Hewlett-Packard folder in the Applications folder at the top level of the hard disk.

Embedded web server

When the printer is connected to a network, you can use the printer's home page (embedded web server or EWS) to view status information, change settings, and manage it from your computer.



NOTE: For a list of system requirements for the embedded web server, see Embedded web server specifications on page 102.

To view or change some settings, you might need a password.

You can open and use the embedded web server without being connected to the Internet. However, some features are not available.

This section contains the following topics:

- **About cookies**
- To open the embedded web server

About cookies

The embedded web server (EWS) places very small text files (cookies) on your hard drive when you are browsing. These files let the EWS recognize your computer the next time you visit. For example, if you have configured the EWS language, a cookie helps remember which language you have selected so that the next time you access the EWS, the pages are displayed in that language. Though some cookies are cleared at the end of each session (such as the cookie that stores the selected language), others (such as the cookie that stores customer-specific preferences) are stored on the computer until you clear them manually.



NOTE: The cookies that the EWS stores on your computer are only used for saving settings on your computer or for sharing information between the printer and the computer. These cookies are not sent to any HP websites.

You can configure your browser to accept all cookies, or you can configure it to alert you every time a cookie is offered, which allows you to decide which cookies to accept or refuse. You can also use your browser to remove unwanted cookies.



NOTE: Depending on your printer, if you disable cookies, you also disable one or more of the following features:

- Starting where you left the application (especially useful when using setup wizards)
- Remembering the EWS browser language setting
- Personalizing the EWS Home page

For information about how to change your privacy and cookie settings and how to view or delete cookies, see the documentation available with your web browser.

To open the embedded web server



NOTE: The printer must be on a network and must have an IP address. The IP address and hostname for the printer are listed on the status report. For more information, see <u>Understand the network configuration page</u> on page 81.

In a supported web browser on your computer, type the IP address or hostname assigned to the printer.

ENWW Embedded web server 149 For example, if the IP address is 123.123.123.123, type the following address into the web browser: http://123.123.123.123.

TIP: After opening the embedded web server, bookmark it so that you can return to it quickly.

TIP: If you are using the Safari web browser in Mac OS X, you can also use the Bonjour bookmark to open the EWS without typing the IP address. To use the Bonjour bookmark, open Safari, and then from the **Safari** menu, click **Preferences**. On the **Bookmarks** tab, in the **Bookmarks bar** section, select **Include Bonjour**, and then close the window. Click the **Bonjour** bookmark, and then select your networked device to open the EWS.

E How do I?

- Get started on page 1
- Change basic network settings on page 135
- Use HP ePrint on page 38
- Work with ink cartridges on page 39
- Maintain the printer on page 18

F Errors (Windows)

- Low on ink
- <u>Cartridge Problem</u>
- Replace the ink cartridge
- Paper Mismatch
- The cartridge cradle cannot move

- Paper Jam
- The printer is out of paper
- Printer Offline
- Printer Paused
- Document failed to print
- Printer failure
- Door or cover open
- Previously used ink cartridge installed
- Ink cartridges depleted
- Ink cartridge failure
- Printer supply upgrade
- Printer supply upgrade successful
- Printer supply upgrade problem
- Non-HP ink cartridges installed
- Using Original HP Cartridges has its Rewards
- Counterfeit Cartridge Advisory
- Used, Refilled or Counterfeit Cartridge Detected
- <u>Use SETUP cartridges</u>
- Do not use SETUP cartridges
- Not enough ink at startup
- Use black ink only?
- Use color ink only?
- Incompatible ink cartridges
- Unable to Communicate with Printer
- Ink sensor failure
- Ink sensor warning
- Problem with printer preparation
- Color cartridge out of ink
- Black cartridge out of ink
- Problem with ink system

ENWW 151

Low on ink

The ink cartridge identified in the message is low on ink.

Ink level warnings and indicators provide estimates for planning purposes only. When you receive a low ink warning message, consider having a replacement cartridge available to avoid possible printing delays. You do not need to replace cartridges until prompted to do so.

For information about replacing ink cartridges, see Replace the ink cartridges on page 43. For information about ordering ink cartridges, see Order printing supplies online on page 132. For information about recycling used ink supplies, see HP inkjet supplies recycling program on page 117.



NOTE: Ink from the cartridges is used in the printing process in a number of different ways, including in the initialization process, which prepares the printer and cartridges for printing. In addition, some residual ink is left in the cartridge after it is used. For more information, see www.hp.com/go/inkusage.

Cartridge Problem

The ink cartridge identified in the message is missing, damaged, incompatible, or inserted into the wrong slot in the printer.



NOTE: If the cartridge is identified in the message as incompatible, see <u>Order printing supplies online</u> on page 132 for information about obtaining cartridges for the printer.

To solve this problem, try the following solutions. Solutions are listed in order, with the most likely solution first. If the first solution does not solve the problem, continue trying the remaining solutions until the issue is resolved.

- Solution 1: Turn the printer off and on
- Solution 2: Install the ink cartridges correctly
- Solution 3: Replace the ink cartridge

Solution 1: Turn the printer off and on

Turn off the printer, and then turn it on again.

If the problem persists, try the next solution.

Solution 2: Install the ink cartridges correctly

Make sure all of the ink cartridges are properly installed:

- Gently pull open the ink cartridge access door.
- Remove the ink cartridge by pushing it in to release it, and then pulling it firmly toward you. 2.
- Insert the cartridge into the slot. Press firmly on the cartridge to ensure proper contact. 3.
- Close the ink cartridge access door and check if the error message has gone away.

ENWW Cartridge Problem 153

Replace the ink cartridge

Replace the indicated ink cartridge. For more information, see Replace the ink cartridges on page 43.



NOTE: If your cartridge is still under warranty, contact HP support for service or replacement. For more information about ink cartridge warranty, see ink cartridge warranty information. If the problem persists after you replace the cartridge, contact HP support. For more information, see HP support on page 48.

Paper Mismatch

The paper size or type selected in the printer driver does not match the paper loaded in the printer. Make sure that the correct paper is loaded in the printer, and then print the document again. For more information, see Load paper on page 11.



NOTE: If the paper loaded in the printer is the correct size, change the selected paper size in the printer driver, and then print the document again.

ENWW Paper Mismatch 155

The cartridge cradle cannot move

Something is blocking the ink cartridge cradle (the part of the printer that holds the ink cartridges).

To clear the obstruction, press the \bigcirc (Power) button to turn off the printer, and then check the printer for jams.

For more information, see <u>Clear jams on page 88</u>.

Paper Jam

Paper has become jammed in the printer.

Before you try to clear the jam, check the following:

- Make sure that you have loaded paper that meets specifications and is not wrinkled, folded, or damaged.
- Make sure that the printer is clean.
- Make sure that the trays are loaded correctly and are not too full. For more information, see <u>Load paper</u> on page 11.

For instructions on clearing jams, as well as more information about how to avoid jams, see <u>Clear jams</u> on page 88.

ENWW Paper Jam 157

The printer is out of paper

The default tray is empty.

Load more paper. For more information, see <u>Load paper on page 11</u>.

Printer Offline

The printer is currently offline. While offline, the printer cannot be used.

To change the printer's status, complete the following steps.

1. Click Start , and then click Printers, Printers and Faxes , or Devices and Printers .

- Or -

Click Start, click Control Panel, and then double-click Printers.

- Or -

On the Start screen, click Control Panel, and then click View devices and printers.

- 2. If the printers listed in the dialog box are not being displayed in Details view, click the **View** menu, and then click **Details**.
- **3.** If the printer is Offline, right-click the printer, and click **Use Printer Online**.
- **4.** Try using the printer again.

ENWW Printer Offline 159

Printer Paused

The printer is currently paused. While paused, new jobs are added to the queue but are not printed.

To change the printer's status, complete the following steps.

- 1. Click Start, and then click Printers, Printers and Faxes, or Devices and Printers.
 - Or -

Click Start, click Control Panel, and then double-click Printers.

- Or -

On the Start screen, click Control Panel, and then click View devices and printers.

- If the printers listed in the dialog box are not being displayed in Details view, click the View menu, and then click Details.
- **3.** If the printer is paused, right-click the printer, and click **Resume Printing**.
- **4.** Try using the printer again.

Document failed to print

The printer could not print the document because a problem occurred in the printing system.

For information about solving printing problems, see <u>Solve printer problems on page 52</u>.

Printer failure

There was a problem with the printer. Usually, you can resolve such problems by completing the following steps:

- 1. Press the () (Power) button to turn off the printer.
- **2.** Unplug the power cord, and then plug in the power cord again.
- 3. Press the (1) (Power) button to turn on the printer.

If this problem persists, write down the error code provided in the message, and then contact HP support. For more information, see <u>HP support on page 48</u>.

Door or cover open

Before the printer can print documents, all doors and covers must be closed.

TIP: When completely closed, most doors and covers snap into place.

If the problem persists after you've securely closed all doors and covers, contact HP support. For more information, see <u>HP support on page 48</u>.

ENWW Door or cover open 163

Previously used ink cartridge installed

The ink cartridge identified in the message was previously used in a different printer.

You can use ink cartridges in different printers, but if the cartridge was left outside of a printer for an extended period of time, the print quality of your documents might be affected. Also, if you use ink cartridges that have been used in a different printer, the ink level indicator might be inaccurate or unavailable.

If the print quality is unsatisfactory, try cleaning the printheads. For more information, see Clean the printhead on page 84.



NOTE: Ink from the cartridges is used in the printing process in a number of different ways, including in the initialization process, which prepares the printer and cartridges for printing, and in printhead servicing, which keeps print nozzles clear and ink flowing smoothly. In addition, some residual ink is left in the cartridge after it is used. For more information, see www.hp.com/go/inkusage.

For more information, see Supplies on page 133.

Ink cartridges depleted

The cartridges listed in the message must be replaced to resume printing. HP recommends that you do not remove an ink cartridge until a replacement is ready to install.

See Replace the ink cartridges on page 43

Ink cartridge failure

The cartridges listed in the message are damaged or have failed.

See Replace the ink cartridges on page 43

Printer supply upgrade

The cartridge listed in the message can only be used to upgrade one printer. Click OK to use it on this printer. If you do not wish to proceed with the supply upgrade for this printer, click Cancel Print and then remove the cartridge.

ENWW Printer supply upgrade 167

Printer supply upgrade successful

The supply upgrade was successful. The cartridges listed in the message can now be used in the printer.

Printer supply upgrade problem

The supply upgrade was not successful. The cartridges listed in the message can still be used in this printer. Replace the Supply Upgrade cartridge. For more information, see Replace the ink cartridges on page 43.

Non-HP ink cartridges installed

HP cannot guarantee the quality or reliability of non-HP supplies. Printer service or repairs required as a result of using a non-HP supply will not be covered under warranty. If you believe you purchased original HP ink cartridges, visit HP at www.hp.com/qo/anticounterfeit for more information or to report fraud.

Using Original HP Cartridges has its Rewards

HP rewards loyal customers for using original HP supplies. Click the button below the message to view Rewards online. Reward may not be available in all regions.

Counterfeit Cartridge Advisory

The installed cartridge is not a new, original HP cartridge. Contact the store where this cartridge was purchased. To report suspected fraud, visit HP at www.hp.com/go/anticounterfeit. To continue using the cartridge, click **Continue**.

Used, Refilled or Counterfeit Cartridge Detected

The original HP ink in the cartridge has been depleted. The solution for this problem is to replace the ink cartridge or click OK to continue using the cartridge. For more information about replacing the cartridge, see Replace the ink cartridges on page 43. HP rewards loyal customers for using original HP supplies. Click the button below the message to view Rewards online. Rewards may not be available in all regions.



MARNING! HP's ink cartridge warranty does not cover non-HP ink or cartridges. HP's printer warranty does not cover repairs or service due to use of non-HP cartridges or ink. HP does not guarantee the quality or reliability of non-HP ink. Information about non-HP ink levels will not be available.

Use SETUP cartridges

When you first setup the printer, you must install the cartridges that shipped in the box with the printer. These cartridges are labeled SETUP, and they calibrate your printer before the first print job. Failure to install the SETUP cartridges during the initial product setup causes an error. If you installed a set of regular cartridges, remove them and install the SETUP cartridges to complete printer setup. After printer setup is complete, the printer can use regular cartridges.

if you still receive error messages and the printer cannot complete ink system initialization, contact HP support. For more information, see HP support on page 48.

Click here to go online for more information.

Do not use SETUP cartridges

SETUP cartridges cannot be used after the printer has been initialized. Remove and install non-SETUP cartridges. For more information, see Replace the ink cartridges on page 43.

Not enough ink at startup

The used cartridges listed in the message might not have enough ink to complete one-time startup processes.

Solution: Install new cartridges or click **OK** to use installed cartridges.

If startup cannot complete with installed cartridges, new cartridges will be needed. For information on how to install new cartridges, see <u>Replace the ink cartridges on page 43</u>.

Use black ink only?

The cartridges listed in the message are out of ink.

Solutions: To print in color, replace the empty cartridges. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

To temporarily print using Black ink only, click **Use Black Only**. The printer will replace color with grayscale. The empty cartridges will need to be replaced soon.

CAUTION: Do not remove the empty color cartridge to print in Use Black Only mode.

ENWW Use black ink only? 177

Use color ink only?

The black cartridge is out of ink.

Solutions: To temporarily replace black with color, click Use Color Only. Black will be simulated. Text and photo quality will differ from those printed when using all cartridges. The black cartridge will need to be replaced

To print with black, replace the black ink cartridge. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

CAUTION: Do not remove the empty black cartridge to print in Use Color Only mode.

Incompatible ink cartridges

The ink cartridge is not compatible with your printer.

Solution: Remove this cartridge immediately and replace with a compatible ink cartridge. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

Unable to Communicate with Printer

The computer cannot communicate with the printer because one of the following events has occurred:

- The printer has been turned off.
- The cable connecting the printer, such as a USB cable or a network (Ethernet) cable, has been disconnected...
- If the printer is connected to a wireless network, the wireless connection has been broken.

To solve this problem, try the following solutions:

- Make sure the printer is turned on and that the (1) (Power button) light is on.
- Make sure the power cord and other cables are working and are firmly connected to the printer.
- Make sure the power cord is connected firmly to a functioning, alternating current (AC) power outlet.
- If the printer is connected to a network, make sure the network is functioning properly. For more information, see Solve Ethernet network problems on page 69.
- If the printer is connected to a wireless network, make sure the wireless network is functioning properly. For more information, see Solve wireless problems on page 69.

Ink sensor failure

The ink sensor has failed and the printer can no longer print.

Contact HP support. For more information, see www.hp.com/support.

ENWW Ink sensor failure 181

Ink sensor warning

The ink sensor is reporting an unexpected condition. This could be caused by the cartridge, or the sensor may have failed. If the sensor has failed, it can no longer sense when your cartridges are out of ink. Printing with an empty cartridge will cause air to enter the ink system, which causes poor print quality. Significant amounts of ink will be used up to recover from this condition, which will deplete much of the ink supply for all cartridges.

Solution: Click OK to continue printing or replace the cartridge. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

Problem with printer preparation

The printer clock has failed and ink preparation may not be complete. The estimated Ink Level gauge might be inaccurate.

Solution: Check the print quality of your print job. If it is not satisfactory, running the printhead cleaning procedure from the toolbox might improve it. For more information, see <u>Clean the printhead on page 84</u>.

Color cartridge out of ink

The cartridges listed in the message are out of ink.

Solutions: To print in color, replace the empty cartridges. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

To temporarily print using black ink only, click Cancel Print and then re-send the print job. The **Use black ink only?** message appears before the job prints. The empty cartridges will need to be replaced soon.

CAUTION: Do not remove the empty color cartridge to print in Use Black Only mode.

Black cartridge out of ink

The black cartridge is out of ink.

Solutions: Replace the black ink cartridge. For information about how to install new cartridges, see Replace the ink cartridges on page 43.

To temporarily replace black with color, click Cancel Print and re-send the print job. The Use color ink only? message appears before the job prints. The black cartridge will need to be replaced soon.

CAUTION: Do not remove the empty black cartridge to print in Use Color Only mode.

Problem with ink system

Please remove the ink cartridges and examine them for any sign of leaks. If any cartridges have leaks, contact HP support. Do not use cartridges that are leaking.

If there are no leaks, re-install cartridges and close the printer cover. Turn the printer off then on again. If you get this message a second time, contact HP support.

For more information about contacting HP support, see <u>HP support on page 48</u>.

Index

A	custom-size paper	fonts supported 102
accessibility 2	sizes supported 105	
accessories	custom-sized paper	G
installation 16	Mac OS 27	glass, scanner
printer status report 79	print on 27	clean 18
turn on and off in driver 16	customer support	
warranty 99	electronic 48	Н
acoustic emissions 109	cut-off pages, troubleshoot 55	head 84
after the support period 50		HP software
align printhead 85	D	uninstall from Windows 86
	diagnostic page 59	HP Utility (Mac OS X)
В	double-sided printing 31	opening 148
B sizes	driver	humidity specifications 109
sizes supported 103	accessories settings 16	
blank pages, troubleshoot	warranty 99	1
print 54	duplexer	ink cartridge access door, locating
both sides, print on 31	installation 16	5
Brochures	turn on and off in driver 16	Ink cartridges
sizes supported 105	duty cycle 102	warranty 99
		ink cartridges 6
C	E	check ink levels 41
capacity	electrical specifications 109	lights 91
trays 105	embedded web server	locating 5
cards	about 149	ordering online 132
sizes supported 104	opening 149	part numbers 133
tray supporting 105	troubleshoot, cannot be opened	replace 43
cartridges. See ink cartridges	67	supported 101
clean	envelopes	tips 40
exterior 18	sizes supported 104	yields 102
printhead 84	tray supporting 105	ink delivery
scanner glass 18	environmental specifications 109	expiration dates 80
Configure	environmental sustainability	part numbers 80
firewall 66	program 116	status 80
connection type	EWS. See embedded web server	ink levels, check 41
change 140		input tray
connectors, locating 6	F	capacity 105
control panel	Firewall	paper sizes supported 103
illustration 91	configure 66	paper types and weights
lights, understanding 91	firewalls, troubleshoot 53	supported 105

ENWW Index 187

installation	memory	photo paper
accessories 16	specifications 102	sizes supported 104
duplexer 16	missing or incorrect information,	ports, specifications 101
hardware installation	troubleshoot 55	power
suggestions 77	model number 79	specifications 109
HP software installation	multi-feeds, troubleshoot 63	troubleshoot 52
suggestions 77	,	power input, locating 6
troubleshooting issues 77	N	print
IP address	networks	diagnostic page 59
checking for printer 67	advanced settings 136	double-sided 31
IP settings 136	connector illustration 6	print quality report 59
ii seemigs 130	firewalls, troubleshoot 53	printer status report 79
J	IP settings 136	troubleshoot 52
jams	link speed 136	Print borderless
clear 88	settings, change 135	Mac OS 29
paper 88, 89	solve problems 69	Windows 29
paper to avoid 10		Print brochures
L	wireless communication setup	print 21
	138	Print envelope 23
language, printer 102	wireless settings 81	Print envelopes
lights on control panel	noise information 109	Mac OS 23
illustration 91	•	Print photos
understanding 91	0	Mac OS 25
lights reference 91	operating environment	Windows 25
link speed, setting 136	specifications 109	print quality report 59
	operating systems supported 102	print settings
M	output tray	print quality 57
Mac OS 21	locating 5	printer control panel
custom-sized paper 27	paper supported 106	locating 5
Print borderless 29	_	network settings 135
Print photos 25	P	printer driver
print settings 20	pages per month (duty cycle) 102	accessories settings 16
turn accessories on and off in	paper	warranty 99
driver 16	clear jams 88	printer software (Windows)
Mac OS X	HP, order 133	opening 19
HP Utility 148	jams 88, 89	printer status report
maintain	load tray 11	information on 79
printhead 84	selecting 10	print 79
maintenance	skewed pages 62	printhead
align printhead 85	specifications 102, 103	clean 84
check ink levels 41	supported sizes 103	printhead, align 85
clean printhead 84	troubleshoot feeding 62	printheads
diagnostic page 59	types and weights supported	lights 91
print quality report 59	105	ordering online 132
printhead 84	paper-feed problems, troubleshoot	supported 101
replace ink cartridges 43	62	printing
margins	PCL 3 support 102	slow, troubleshoot 53
setting, specifications 106	phone support 48	processor specifications 102
media	phone support period	processor specifications 102
duplexing 31	period for support 49	
print on custom-sized 27	period to pappore is	

188 Index ENWW

R	printer status report 79	HP software installation
radio interference	yields 102	suggestions 77
reducing 143	support 48	installation issues 77
regulatory information 113	system requirements 102	lights 91
radio, turn off 135	_	solve network problems 69
rear access panel	T	wireless problems 69
clear jams 88	temperature specifications 109	two-sided printing 31
illustration 6	text	
recycle	troubleshoot 55	U
ink cartridges 117	Toolbox (Windows)	uninstall HP software
regulatory information 110, 113	about 147	Windows 86
regulatory model number 110	opening 147	USB connection
replace ink cartridges 43	tray 2	port, locating 5, 6
report	turn on and off in driver 16	specifications 101
wireless test 142	trays	
reports	capacities 105	V
diagnostic 59	clear jams 88	view
print quality 59	load paper 11	network settings 135
printhead 84	locating 5	voltage specifications 109
	paper guides illustration 5	
S	paper sizes supported 103	W
scanner glass	paper types and weights	warranty 99
clean 18	supported 105	websites
security	troubleshoot feeding 62	accessibility information 2
wireless communication 142	turn on and off in driver 16	customer support 48
serial number 79	troubleshoot	environmental programs 116
settings	blank pages printed 54	order supplies and accessories
network 135	cut-off pages, incorrect text or	131
skew, troubleshoot	graphics placement 55	supply yield data sheet 102
print 62	embedded web server 67	Windows 23
software	firewalls 53	borderless 29
accessories settings 16	jams, paper 89	print brochures 21
warranty 99	missing or incorrect	Print photos 25
sound pressure 109	information 55	print settings 20
specifications	multiple pages are picked 63	system requirements 102
acoustic emissions 109	network configuration page 81	turn accessories on and off in
electrical 109	nothing prints 52	driver 16
operating environment 109	paper not picked up from tray	uninstall HP software 86
paper 102, 103	62	wireless communication
physical 101	paper-feed problems 62	advanced wireless
processor and memory 102	power 52	troubleshooting 71
storage environment 109	print 52	basic wireless troubleshooting
system requirements 102	printer status report 79	70
status	skewed pages 62	radio, turn off 135
network configuration page 81	tips 51	reducing interference 143
printer status report 79	troubleshooting	regulatory information 113
	Ethernet network 69	security 142
storage environment specifications 109	hardware installation	set up 138
		wireless test report
supplies	suggestions 77	print 142
ordering online 132		print 172

ENWW Index 189

190 Index ENWW

© Copyright 2016 HP Development Company, L.P.

