

# HP Pavilion Desktop PCs - Motherboard Specifications

---

<b>Motherboard Supplier</b>	MSI
<b>System BIOS Supplier</b>	MSI/Award
<b>Form Factor</b>	uATX
<b>Processor Brand</b>	Intel
<b>Processor Socket Type</b>	mPGA478
<b>Processor Family</b>	P4 and Celeron
<b>Proc. Front Side Bus Freq.</b>	400/533MHz
<b>Chipset Name</b>	SiS651
<b>Chipset "North Bridge"</b>	SiS651
<b>revision/stepping</b>	B0
<b>Chipset "South Bridge"</b>	SiS962
<b>revision/stepping</b>	B1
<b>Super I/O</b>	Winbond
<b>revision/stepping</b>	W83697HF
<b>Flash BIOS Device</b>	4MB Flash EEPROM
<b>Memory Type</b>	DDR
<b>Memory Speed</b>	PC2700/PC2100/PC1600
<b>Memory Sockets</b>	2 DIMM
<b>Maximum Memory</b>	2GB
<b>Graphics Supplier</b>	SiS UMA
<b>Graphics Configuration</b>	Down, In Chipset
<b>Onboard Graphics Memory</b>	UMA/up to 64MB
<b>Graphics Connector (AGP)</b>	AGP4x
<b>TV-Out Device</b>	No
<b>TV-Out Configuration</b>	(N/A)
<b>Audio</b>	AC'97 Down
<b>AC'97 CODEC Device</b>	Realtek ALC650F
<b>Audio Jacks (Mic,Line-In,Line-Out,Spkr,MIDI/Game)</b>	M,LI,LO
<b>External audio connectors(Headphone, Mic, Line-in)</b>	M,LI,HP
<b>Ethernet 10/100 LAN Supplier</b>	Realtek RTL8201BL
<b>Ethernet Configuration</b>	PCI, Down
<b>IDE UDMA Modes</b>	ATA-66/100/133
<b>Expansion Slots (AGP/PCI/Exten)</b>	AGP, 3 PCI
<b>USB Ports</b>	6 USB 2.0
<b>USB Front/Back Options</b>	2F+4B
<b>Serial, Parallel, Floppy, PS2 Kbd &amp;Mouse</b>	1S,1P,1F,PS2 K+M, 1394
<b>Serial Port Front Chassis Option</b>	No
<b>Available Mfg Options</b>	-GLE6

---

Copyright Hewlett-Packard Co. 1994-2003  
This information is subject to change without notice and  
is provided "as is" with no warranty.  
Hewlett-Packard shall not be liable for any direct,  
indirect, special, incidental or consequential damages  
in connection with the use of this material.