Technical Specifications

Model t280d	DK260A
Processor & Speed	2.6HT GHz/800 Intel® Pentium® 4 Processor – PGA478
Chipset	Intel® 865G
Motherboard	P4SD-LA-GL6E
RAM	512/2700 MB DDR SDRAM
Maximum	4 GB (4x1024MB DDR SDRAM)
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	Two
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 1 MB L2 Integrated or
	Processor module
Hard Drive - 1	80 GB (7200 RPM)
Optical Drive	DVD+R/RW Drive
Transfer rates	Write: Up to 10x (CD-RW)
Halisiel Tales	Write: Up to 16x (CD-R)
	Write: Up to 4x (DVD+RW)
	Read: Up to 40x (CD-RW)
	Read: Up to 40x (CD-R/CD-ROM)
	Read: Up to 8x (DVD+RW)
Optical Drive - 2	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Access Speed	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
6 in 1 Card Reader	Compact Flash I/II; Memory Stick; MMC/SD; Smart
	Media
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V .42
EIA Fax Commands	Class 1
Video Graphics	AGP 8X Graphics Card
Controller	ATI R9200
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - PAL
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
MPEG-1/2	MPEG-2 for full-screen, full-motion digital video
TV Tuner	TV Tuner Card
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	
Front I/O Connector	6= USB, 1= serial, 1= parallel, 2=1394
TION I/ O CONNECTOR	2= USB, 1= 1394; 6 in 1 Card Reader; 1= Microphone;
Expansion Slots (Total)	1= Line In; 1= Headphone 3= PCI, 1= AGP
Expansion Slots (Total)	·
Expansion Slots (FREE)	1= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external,
Drive Bove (EDEE)	Two 3.5" internal
Drive Bays (FREE)	One 3.5" internal HP Wireless Internet command center; One-touch Internet
Keyboard/Mouse	