

Technical Specifications

Model t202k	DK234A
Processor & Speed	2.4 GHz/400 Intel® Celeron™ Processor – PGA478
Chipset	Intel® 845GE
Motherboard	MS6577-4-GL6E
RAM	256/2700 MB DDR SDRAM
Maximum	2 GB (2x1024 MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	None
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 128 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-RW Drive: 48x-Write / 12X-Re-write/CD-ROM speed =48x max.
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
Diskette Drive	None
6 in 1 Card Reader	Compact Flash I/II; Memory Stick; MMC/SD; Smart Media
Video Graphics	Intel® Extreme Graphics
Controller	Integrated w/845GE Chipset
Video Memory	Dynamic up to 48MB UMA
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
MPEG-1/2	MPEG-1 for full-screen, full-motion digital video
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	5= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	1= USB, 1= 1394; 6 in 1 Card Reader; 1= Microphone; 1= Line In
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI, 1=AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Technical Specifications

Model t202k	DK234A
Processor & Speed	2.4 GHz/400 Intel® Celeron™ Processor – PGA478
Chipset	Intel® 845GE
Motherboard	MS6577-4-GL6E
RAM	256/2700 MB DDR SDRAM
Maximum	2 GB (2x1024 MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	None
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	8KB Data Cache + Trace Cache L1, 128 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-RW Drive: 48x-Write / 12X-Re-write/CD-ROM speed =48x max.
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
Diskette Drive	None
6 in 1 Card Reader	Compact Flash I/II; Memory Stick; MMC/SD; Smart Media
Video Graphics	Intel® Extreme Graphics
Controller	Integrated w/845GE Chipset
Video Memory	Dynamic up to 48MB UMA
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
MPEG-1/2	MPEG-1 for full-screen, full-motion digital video
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	5= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	1= USB, 1= 1394; 6 in 1 Card Reader; 1= Microphone; 1= Line In
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI, 1=AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.