

# Technical Specifications

<b>Model a305l</b>	<b>DN062A</b>
<b>Processor &amp; Speed</b>	2.6 GHz/400 Intel® Celeron™ Processor – PGA478
<b>Chipset</b>	Intel® 845GL
<b>Motherboard</b>	Echo-GL (P4GS33-LA)
<b>RAM</b>	128/2700 MB 333DDR SDRAM (runs @266)
Maximum	1 GB (2x512MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256 and 512 MB DDR DIMMs
<b>Free DIMM Sockets</b>	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
<b>Cache</b>	8KB Data Cache + Trace Cache L1, 128 KB L2 Integrated on Processor module
<b>Hard Drive</b>	40 GB
<b>Optical Drive</b>	CD-ROM Drive: 48x maximum speed
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
<b>Diskette Drive</b>	3.5" (1.44MB)
<b>Fax/Data Modem</b>	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
<b>Video Graphics</b>	Intel® Extreme Graphics
Controller	Integrated w/845G Chipset
Video Memory	Dynamic up to 64MB UMA
<b>Network Card</b>	10/100 BaseT, Integrated
<b>Sound</b>	AC'97 Integrated on MB
Controller	Realtek ALC202A
<b>Chassis</b>	Panther, 250HV PSU
<b>USB Interface Specification</b>	USB 2.0
<b>External Ports</b>	6= USB, 1= serial, 1= parallel
Front I/O Connector	2= USB
<b>Expansion Slots (Total)</b>	3= PCI
<b>Expansion Slots (FREE)</b>	2= PCI
<b>Drive Bays (Total)</b>	Two 5.25" external, One 3.5" external, Two 3.5" internal
<b>Drive Bays (FREE)</b>	One 5.25" external, One 3.5" internal
<b>Keyboard/Mouse</b>	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003

This information is subject to change without notice and is provided "as is" with no warranty.

Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.