## **Technical Specifications**

Model t317k	DN047A
Processor & Speed	AMD Athlon(B) XP2800+ 2.08 GHz/333
Chipset .	nForce2-IGP
Motherboard	Explorer2-GL6E (A7NBX-LA)
RAM	256/2700 MB 333 DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 256 KB L2 Integrated on Processor module
Hard Drive	80 GB (7200 RPM)
Optical Drive	CD-RW/DVD-ROM Drive 48x24x16x48
	48X- Write /24X - Re-write /16x- DVD Read
	48X - CD-ROM Read
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
7 in 1 Card Reader	Compact Flash I/II; Memory Stick/Pro; MMC/SD; Smart Media
Video Graphics	AGP 8X Graphics Card
Controller	nVidia GeForce4™ MX-440
Video Memory	64 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650F
Chassis	Jaguar, 250HV
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel; 2= 1394
Front I/O Connector	2= USB, 1=1394, 7 in 1 Card Reader, 1= Line-In,
	1=Microphone; 1= Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
	T 5 05"
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.