Technical Specifications

Processor & Speed Chipset Motherboard RAM Maximum Sockets Size Free DIMM Sockets Pairs Required Type Supported Cache	2.6 GHz/400 Intel® Pentium® 4 Processor – PGA478 Intel® 865PE Yale-UL6E(P4SD-LA) 256/2700 MB 333DDR SDRAM (runs@266MHz) 2 GB (2x1024MB DDR SDRAM) Two 184-pin DDR DIMMs 128, 256, 512 and 1024 MB DDR DIMMs One No
Motherboard RAM Maximum Sockets Size Free DIMM Sockets Pairs Required Type Supported	Yale-UL6E(P4SD-LA) 256/2700 MB 333DDR SDRAM (runs@266MHz) 2 GB (2x1024MB DDR SDRAM) Two 184-pin DDR DIMMs 128, 256, 512 and 1024 MB DDR DIMMs One No
RAM Maximum Sockets Size Free DIMM Sockets Pairs Required Type Supported	256/2700 MB 333DDR SDRAM (runs@266MHz) 2 GB (2x1024MB DDR SDRAM) Two 184-pin DDR DIMMs 128, 256, 512 and 1024 MB DDR DIMMs One No
Maximum Sockets Size Free DIMM Sockets Pairs Required Type Supported	2 GB (2x1024MB DDR SDRAM) Two 184-pin DDR DIMMs 128, 256, 512 and 1024 MB DDR DIMMs One No
Sockets Size Free DIMM Sockets Pairs Required Type Supported	Two 184-pin DDR DIMMs 128, 256, 512 and 1024 MB DDR DIMMs One No
Size Free DIMM Sockets Pairs Required Type Supported	128, 256, 512 and 1024 MB DDR DIMMs One No
Free DIMM Sockets Pairs Required Type Supported	One No
Pairs Required Type Supported	No
Type Supported	
,, ,,	
Cache	JEDEC unbuffered DDR SDRAM DIMM specification
	8KB Data Cache + Trace Cache L1, 512 KB L2 Integrated on Processor module
Hard Drive	80 GB (7200 RPM)
Optical Drive	CD-RW/DVD-ROM Drive 48x24x16x48
	48X- Write /24X - Re-write /16x- DVD Read
	48X - CD-ROM Read
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
7 in 1 Card Reader	Compact Flash I/II; Memory Stick/Pro; MMC/SD; Smar Media
Video Graphics	AGP 8X Graphics Card
Controller	nVidia GeForce4™ MX-440
Video Memory	64 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Jaguar, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	5= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	2= USB, 1= 1394; 7 in 1 Card Reader; 1= Microphone; 1= Line In, 1=Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external,
Drive Bays (FREE)	One 5.25" external, One 3.5" internal, One 3.5" external
, , ,	One-touch Enhanced Keyboard, PS/2 Optical scrolling

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.