

Technical Specifications

Model t302cn	DN078A
Processor & Speed	AMD Athlon XP2400+ 2.0 GHz/266
Chipset	nForce2-IGP
Motherboard	Explorer2-GL6E (A7NBX-LA)
RAM	256/2700 MB 333 DDR SDRAM
Maximum	2 GB (2x1024 MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 256 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-ROM Drive: 48x maximum speed
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
Diskette Drive	None
7 in 1 Card Reader	Compact Flash I/II; Memory Stick/Pro; MMC/SD; Smart Media
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	AGP 8X, Integrated
Controller	nVidia nForce2
Video Memory	64MB UMA, not upgradeable
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650F
Chassis	Jaguar, 250HV + PFC PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel; 2= 1394
Front I/O Connector	2= USB, 1=1394, 7 in 1 Card Reader, 1= Line-In, 1=Microphone; 1= Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	2= PCI, 1= AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal, One 3.5" external
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.