

Technical Specifications

Model S6010IL	DT106A
Processor & Speed	AMD Athlon(T) XP2000+ 1.67GHz/266
Chipset	VIA KM266
Motherboard	Crossfire-GLA (MS-6390)
RAM	128/2700 MB 333DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 256 KB L2 Integrated on Processor module
Hard Drive	40 GB
Optical Drive	CD-ROM Drive: 48x maximum speed
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
Diskette Drive	3.5" (1.44MB)
Fax/Data Modem	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
Video Graphics	AGP 4X Graphics
Controller	Integrated w/KM266 Chipset
Video Memory	UMA 32 MB
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650/658
Chassis	Chameleon, 250HV PSU
USB Interface Specification	USB 2.0
External Ports	6= USB, 1= serial, 1= parallel
Front I/O Connector	2= USB
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	2= PCI, 1= AGP
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal
Keyboard/Mouse	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

Copyright Hewlett-Packard Co. 1994-2003
This information is subject to change without notice and is provided "as is" with no warranty.
Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.