

# HP Pavilion f1723



- **Superior quality** The HP Pavilion F1723 monitor delivers superior quality images and excellent sound thanks to its 17-inch active matrix LCD with anti-glare coating and built-in high-quality, high-fidelity speakers
- **Best-in-class performance** Experience best-in-class performance with an impressive 17-inch display that delivers flicker-free performance at 1280 x 1024 resolution, 0.264mm dot pitch and 450:1 contrast for photo-realistic quality
- **Stylish and ergonomic** With a stylish and elegant design, the HP Pavilion F1723 lends a high-tech vibe to any home. Thanks to ergonomic and space-saving features, such as integrated speakers and streamlined cabling, your desk remains clutter-free
- **A perfect match for your HP Pavilion PC** The sleek design has been styled to provide the perfect match for your HP Pavilion home PC for a complementary and unified desktop look and feel

Christmas 2003

# HP Pavilion f1723

<b>Specifications</b>	Display Size : 17" (43.2 cm) diagonal and viewable image Surface treatment : Thin Film Transistor LCD active matrix Faceplate treatment : Antiglare, antistatic Pixel pitch : 0.264 mm Refresh response time : 25ms (typical) Brightness : 300 nits (typical) Contrast ratio : 450:1 (typical)
<b>Interface specifications</b>	Video input signal : 15-pin mini D-SUB VGA Display resolution : 1280x1024 @ 60Hz (recommended) Recommended resolution : 1280 x 1024 @ 75Hz max Color : Support true colour, 16.7 Million Horizontal scan rates : 56-76 Hz vertical, 30-81 KHz horizontal
<b>Features</b>	Multimedia : Integrated active speakers Physical security features : Kensington lock ready Display moving angle : Vertical tilt range -5 degrees to 30 degrees  Plug and play : Yes
<b>Power</b>	Power Supply and Power Requirements : 100-240V, auto-ranging, 50-60Hz – External brick Power Consumption : 50 watts maximum on operating mode; 2 watts max in power saving mode
<b>User controls</b>	Display User Control Options : Contrast, brightness, colour settings, colour palette, horizontal and vertical image position, clock and phase, auto-config, power saver, power on recall, backlight info, 6 languages
<b>Mechanical specifications</b>	Weight : 6.0 kg Package Dimensions (W x D x H) : 454 x 454 x 175 mm Package Weight : 8.0 kg Operating Temperature Range : 5° C to 35° C, 20%-80% relative humidity non-condensing Storage Temperature Range : - 20° C to 60° C, 5%-95% relative humidity non-condensing
<b>Regulatory</b>	Compliance Industry Standards : CE Marking, TUV-GS (disclaimer « not intended for office use »), MPR II, TCO99, ISO 9241, CISPR, VCCI, MIC, CSA (or CUL), ACA, Energy Star
<b>Additional information</b>	Warranty : Limited one-year part and repair labour warranty (certain restrictions and exclusions apply) Box Content : Monitor, AC power cord, audio cable, driver and documentation Ordering info : P9623A#ABB (Europe), UPC 8 29160-05269 4 P9623A#ABU (UK & Ireland), UPC 8 29160-05270 0 P9623A#AR8 (Switzerland), UPC 8 29160-05272 4 P9623A#ABY (Denmark), UPC 8 29160-05271 7

© 2003 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. All brand names and product names are trademarks or registered trademarks of their respective companies. All performance specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.  
09/03