Technical Specifications

Model t422k	DT089A
Processor & Speed	AMD Athlon(B) XP3000+ 2.167 GHz/333
Chipset	nforce2-ISP
Motherboard	Focus-UL6E (A7NBX-LA)
RAM	512/2700 MB 333 DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	128 KB L1, 512 KB L2 Integrated on Processor module
Hard Drive	80 GB (7200 RPM)
Optical Drive	CD-RW/DVD-ROM Drive 48x24x16x48
	48X- Write /24X - Re-write /16x- DVD Read
	48X - CD-ROM Read
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Diskette Drive	None
7 in 1 Card Reader	Compact Flash I/II; Memory Stick/Pro; MMC/SD; Smart Media
Video Graphics	AGP 8X Graphics Card
Controller	ATI R9200SE
Video Memory	128 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650F
Chassis	Jaguar, 250HV
USB Interface Specification	USB 2.0
External Ports	5= USB, 1= serial, 1= parallel; 2= 1394
Front I/O Connector	1= USB, 1=1394, 7 in 1 Card Reader, 1= Line-In,
	1=Microphone; 1= Headphone
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 5.25" external, One 3.5" internal, One 3.5" external

Copyright Hewlett-Packard Co. 1994-2003 This information is subject to change without notice and is provided "as is" with no warranty. Hewlett-Packard shall not be liable for any direct, indirect, special, incidental or consequential damages in connection with the use of this material.