

# Technical Specifications

Model S6110IN	DY010A
<b>Processor &amp; Speed</b>	AMD Athlon(T) XP2000+ 1.67GHz/266
<b>Chipset</b>	nForce2-IGP
<b>Motherboard</b>	Explorer2-GL6E (A7NBX-LA)
<b>RAM</b>	128/2700 MB 333DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 AND 1024 MB DDR DIMMs
<b>Free DIMM Sockets</b>	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
<b>Cache</b>	128 KB L1, 256 KB L2 Integrated on Processor module
<b>Hard Drive</b>	40 GB
<b>Optical Drive</b>	CD-ROM Drive: 48x maximum speed
Average Random Access	75ms
Transfer Rate	7.2 MB/sec
<b>Diskette Drive</b>	3.5" (1.44MB)
<b>Fax/Data Modem</b>	V.92 56Kbps
Fax Speed	Up to 14.4Kbps
Data Compression	V.42 bis
Error Correction	V.42
EIA Fax Commands	Class 1
<b>Video Graphics</b>	AGP 8X, Integrated
Controller	nVidia nForce2
Video Memory	64MB UMA, not upgradeable
<b>Network Card</b>	10/100 BaseT, Integrated
<b>1394 Card</b>	IEEE-1394, Integrated
<b>Sound</b>	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650/658
<b>Chassis</b>	Chameleon, 250HV PSU
<b>USB Interface Specification</b>	USB 2.0
<b>External Ports</b>	6= USB, 1= serial, 1= parallel, 2=1394
Front I/O Connector	2= USB, 1= 1394; 1= Microphone; 1=Headphone
<b>Expansion Slots (Total)</b>	3= PCI, 1= AGP
<b>Expansion Slots (FREE)</b>	2= PCI, 1= AGP
<b>Drive Bays (Total)</b>	Two 5.25" external, One 3.5" external, Two 3.5" internal
<b>Drive Bays (FREE)</b>	One 5.25" external, One 3.5" internal
<b>Keyboard/Mouse</b>	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

---

Copyright Hewlett-Packard Co. 1994-2003  
 This information is subject to change without notice and  
 is provided "as is" with no warranty.  
 Hewlett-Packard shall not be liable for any direct,  
 indirect, special, incidental or consequential damages  
 in connection with the use of this material.