Technical Specifications

Model SR1088AP	DY085A
Processor & Speed	3.0HT GHz/800 Intel® Pentium® 4(P) Processor -
•	PGA478
Chipset	Intel® 865G
Motherboard	Cobra-GL6E (4PSD-LA)
RAM	512/3200 MB 400DDR SDRAM (2x256)
Maximum	4 GB (4x1024MB DDR SDRAM)
Sockets	Four 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
Free DIMM Sockets	Two
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
Cache	16KB Data Cache + Trace Cache L1, 1MB L2 Integrated on Processor module
Hard Drive	160 GB (7200 RPM)
Optical Drive	DVD-ROM Drive: DVD (16x max.) / CD-ROM (48x max.)
Average Random Access	DVD =115ms / CD-ROM =95ms
Transfer Rate	DVD = 21.6/sec. / CD-ROM = 7.2MB/sec.
Optical Drive	CD-RW Drive: 48x-Write / 24X-Re-write/CD-ROM speed =48x max.
Average Random Access	110ms
Transfer Rate	6.0MB/sec.
Diskette Drive	None
9 in 1 Card Reader	Compact Flash I/II, Memory Stick/PRO, MMC/SD, Smart Media, xD, Microdrive
Video Graphics	AGP 8X Graphics Card
Controller	nVidia FX5500
Video Memory	256 MB DDR, not upgradeable
Video Connectors	Composite & S-Video - NTSC
Network Card	10/100 BaseT, Integrated
1394 Card	IEEE-1394, Integrated
Sound	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650
Chassis	Gobi, 250HV PSU
USB Interface Specification	USB 2.0
External I/O Rear Connectors	4= USB, 1=1394, Serial, Parallel, Line-In, Line-Out; Microphone
External I/O Front Connectors	2=USB;1= 1394, Line In, Microphone, Headphone, 9 in 1 Card Reader w/USB
Expansion Slots (Total)	3= PCI, 1= AGP
Expansion Slots (FREE)	3= PCI
Drive Bays (Total)	Two 5.25" external, One 3.5" external, Two 3.5" internal
Drive Bays (FREE)	One 3.5" external, One 3.5" internal
Keyboard/Mouse	USB Wireless Internet command center; One-touch Internet keyboard, Wireless optical scrolling
	mouse