HP LF Printing Knowledge Center



Proof another printer

Application: Adobe Illustrator CS


<u>Printer:</u> HP Designjet 30/90/130 series <u>Software</u>: EFI Designer Edition for HP

Operating System: Windows




- 1. First recommendations:
 - Some paper types are better than others for proofing, see the <u>Media type functionality & features</u> and choose the most appropriate media.
 - It is essential to have the media type correctly calibrated with the printer and print mode, consult the <u>Calibrate my printer</u> section.
- 2. Open the EFI Designer Edition RIP.
- 3. EFI Designer Edition RIP settings, **Preferences**:
 - Color:
 - Check the Active Color Management checkbox.
 - Paper name: Select the paper type that is loaded on the printer (always calibrated) and "Best" print quality.
 - o Print resolution: 600 x 600.
 - Color output mode: Proof.
 - CMYK: Click the Add profile button and browse to the printer profile you want to emulate.

Select the **Relative Colorimetric** intent (select **Absolute Colorimetric** if you want to emulate the white of the paper).





- OK
- 4. Open Adobe Illustrator CS.
- 5. Configure the Color Settings, Edit menu > Color Settings...:
 - Make sure the **Advanced Mode** check box is ticked.
 - Working Space > RGB: select Adobe RGB (1998).

- Working Space > CMYK: Euroscale Coated v2 (for Europe), U.S. Web Coated (SWOP) v2 (for US) and Japan Standard v2 (for Japan).
- Color Management Policies: Preserve the Embedded Profiles.
- Profile Mismatches: check Ask When Opening and Ask When Pasting.
- Missing Profiles: check Ask When Opening.
- Conversion Options > Intent: Perceptual (for RGB images) or Relative Colorimetric (for CMYK images).




- Click **OK**
- 6. Open the image, **File menu > Open**...:
 - If the document has an embedded color profile that does not match the current working space, select **Use the embedded profile**. Otherwise, select **Assign working space**.





- Click OK
- Make sure to have configured the **Document Setup** appropriately for your document, **File**menu > **Document Setup...**.
- 8. Printer settings, **File menu > Print... > Setup...** button:
 - Select Printer...: Select the printer (ex. EFI Designer Edition).
 - Preferences:
 - o Layout tab:
 - Orientation: Select the orientation of your document on the paper.
 - Advanced...:
 - Paper/Output > Paper Size: Select the paper size of the media loaded on the printer.
 - Document Options > Printer Features:
 - Paper Size: Setup
 - Select RIP's Default on the others settings.



Click **OK** until the Illustrator **Print** dialog box.


- 9. Adobe Illustrator **Print...** settings:
 - General (left hand menu):
 - o **Media > Size:** Defined by Driver.
 - Options: Select the scaling option you need.
 - Output (left hand menu):
 - o Mode: Composite.
 - Color Management (left hand menu):
 - o **Print Space > Profile**: Select the printer profile you want to emulate. If you need to add the printer profile to the application, copy it to the next folder:

Windows 98: WINDOWS>System>Color

Windows NT: WinNT>System32>Color

Windows 2000: C: > WINDOWS > System32 > Spool > Drivers > Color Windows XP: C: > WINDOWS > System32 > Spool > Drivers > Color

 Print Space > Intent: Perceptual (for RGB images) or Relative Colorimetric (for CMYK images).



• Click Print.

For more information on HP Designjet products

www.hp.com/go/designjet

© 2005 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Adobe Photoshop and PostScript are trademarks of Adobe Systems Incorporated. PANTONE is Pantone, Inc.'s check-standard trademark for color.

Rev. 1.0, 09/2005

