HP Compaq 2510p Notebook PC Maintenance and Service Guide

© Copyright 2008 Hewlett-Packard Development Company, L.P.

Bluetooth is a trademark owned by its proprietor and used by Hewlett-Packard Company under license. Intel and Core are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Java is a US trademark of Sun Microsystems, Inc. Microsoft, Windows, and Windows Vista are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. SD Logo is a trademark of its proprietor.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

First Edition: June 2007 Third Edition: July 2008

Document Part Number: 447219-003

MSG revision history

Revision	Publication date	Description
451722-001. The information was updated in the following locations		The fingerprint reader board cable is included in the Cable Kit, spare part number 451722-001. The information was updated in the following locations: lllustrated parts catalog on page 18, Cable Kit on page 26, Sequential part number listing on page 29, and Top cover on page 67.
		The modem cable, LED cable, and capacity board cable are included in the Cable Kit, spare part number 451722-001. The information was updated in the following location: <u>Cable Kit on page 26</u> .
В	February 2011	The Intel Core Duo U7700 1.33-GHz processor with 533-MHz FSB and 2-MB L2 cache was added in the following location: Product description on page 1. The system board with the Intel Core Duo U7700 1.33-GHz processor, spare part number 464764-001, was added in the following locations: Computer major components on page 19, Sequential part number listing on page 29, and System board on page 70.

Safety warning notice

⚠ WARNING! To reduce the possibility of heat-related injuries or of overheating the computer, do not place the computer directly on your lap or obstruct the computer air vents. Use the computer only on a hard, flat surface. Do not allow another hard surface, such as an adjoining optional printer, or a soft surface, such as pillows or rugs or clothing, to block airflow. Also, do not allow the AC adapter to contact the skin or a soft surface, such as pillows or rugs or clothing, during operation. The computer and the AC adapter comply with the user-accessible surface temperature limits defined by the International Standard for Safety of Information Technology Equipment (IEC 60950).

Table of contents

1 Pr	oduct description	
	•	
2 Ex	ternal component identification	5
	Display components	
	Top components	6
	Buttons and fingerprint reader	6
	Keys	7
	Lights	8
	Pointing devices	10
	Front components	11
	Left-side components	12
	Rear components	13
	Right-side components	14
	Bottom components	16
3 IIIu	ustrated parts catalog	18
•	Serial number location	
	Computer major components	
	Plastics Kit	
	Cable Kit	
	Mass storage devices	
	Miscellaneous parts	
	Sequential part number listing	
4 Do	emoval and replacement procedures	24
4 110	Preliminary replacement requirements	
	Tools required	
	Service considerations	
	Plastic parts	
	Cables and connectors	
	Drive handling	
	Grounding guidelines	
	Electrostatic discharge damage	
	Liculosialic discription del mante de la companya del companya de la companya de la companya del companya de la	

	Packaging and transporting guidelines	37
	Workstation guidelines	37
	Equipment guidelines	38
	Unknown user password	39
	Component replacement procedures	40
	Serial number	40
	Computer feet	40
	Battery	41
	SIM	42
	Bluetooth module	43
	Memory module	45
	RTC battery	47
	WLAN module	48
	Hard drive	52
	WWAN module	54
	Optical drive	56
	Switch cover	57
	Keyboard	59
	Display assembly	
	Top cover	
	System board	70
	Speaker assembly	73
	Fan/heat sink assembly	74
	PC Card assembly	76
	Modem module	78
5 (Computer Setup	80
	Starting Computer Setup	
	Using Computer Setup	
	Navigating and selecting in Computer Setup	
	Restoring factory settings in Computer Setup	
	Computer Setup menus	
	File menu	
	Security menu	
	Diagnostics menu	
	System Configuration menu	
6	Specifications	98
•		
	Computer specifications	
	12.1-inch, WXGA display specifications	
	Hard drive specifications	
	DVD±RW and CD-RW Double-Layer Combo Drive specifications	
	DVD/CD-RW Combo Drive specifications	90

	DVD-ROM Drive	91
	System DMA specifications	92
	System interrupt specifications	93
	System I/O address specifications	94
	System memory map specifications	96
7 S	crew listing	97
	Phillips PM2.0×5.0 captive screw	98
	Phillips PM2.0×5.0 screw	100
	Phillips PM2.5×4.0 screw	101
	Torx T8M2.5×7.0 screw	103
	Torx T8M2.5×4.0 screw	106
	Phillips PM2.0×3.0 screw	108
	Phillips PM1.5×3.0 screw	109
	Torx T6M2.0×5.0 screw	110
	Phillips PM2.0×4.0 screw	111
	Phillips PM2.0×2.0 broad-head screw	112
	Phillips PM2.0×10.0 screw	113
8 B	ackup and recovery	114
	Backup and recovery using Windows Vista	
	Creating recovery discs	
	Backing up your information	114
	When to back up	115
	Backup suggestions	115
	Backing up specific files or folders	115
	Backing up the entire hard drive	116
	Creating recovery points	117
	Scheduling backups	117
	Performing a recovery	117
	Performing a recovery from the recovery discs	118
	Performing a recovery from the hard drive	118
	Initiating a recovery in Windows	119
	Initiating a recovery from the hard drive recovery partition	119
	Backup and recovery using Windows XP	120
	Creating recovery discs	120
	Backing up your information	120
	When to back up	121
	Backup suggestions	
	Backing up specific files or folders	121
	Backing up the entire hard drive	122
	Creating recovery points	
	Scheduling backups	123

	Performing a recovery	123
	Performing a recovery from the recovery discs	124
	Performing a recovery from the hard drive	124
	Initiating a recovery in Windows	125
	Initiating a recovery from the hard drive recovery partition	125
9 Co	nnector pin assignments	126
	Audio-out (headphone)	126
	Audio-in (microphone)	126
	External monitor	127
	RJ-11 (modem)	128
	RJ-45 (network)	128
	Universal Serial Bus	129
10 Pc	ower cord set requirements	130
	Requirements for all countries and regions	130
	Requirements for specific countries and regions	131
11 R	ecycling	132
	Battery	132
	Display	
Index	(138

1 Product description

Category	Description	
Branding	Long name: HP Compaq 2510p Notebook PC	
	Short name: HP Compaq 2510p	
	Logo badge: Compaq 2510p	
Processors	Intel® Core™ Duo processors:	
	 U7700 1.33-GHz processor with 533-MHz Front Side Bus (FSB) and 2-MB L2 cache 	
	 U7600 1.20-GHz processor with 533-MHz FSB and 2-MB L2 cache 	
	 U7500 1.06-GHz processor with 533-MHz FSB and 2-MB L2 cache 	
Chipsets	Northbridge: Intel Crestline GM	
	Southbridge: Intel ICH8-M enhanced	
Graphics	Intel Crestline Graphics, Unified Memory Architecture (UMA), integrated with shared video memory, up to 384-MB shared memory	
Panels	 12.1 WXGA (1280 × 800), configured with 3 WLAN antennas and 2 WWAN antennas 	
	Supports privacy filter	
Memory	One SODIMM slot, customer accessible/upgradable	
	 PC2-5300, 667-MHz, DDRII 	
	Supports single-channel memory	
	Supported configurations:	
	∘ 4096-MB total system memory (4096 MB × 1)	
	 2048-MB total system memory (2048 × 1) 	
	∘ 1024-MB total system memory (1024 MB × 1)	
	∘ 512-MB total system memory (512 MB × 1)	


Category	Description	
Hard drives	Supports all 1.8-inch hard drives	
	Parallel ATA	
	The following hard drives are available:	
	。 100-GB, 4200-rpm	
	。 80-GB, 4200-rpm	
	。 60-GB, 4200-rpm	
Optical drives	9.5-mm tray load	
	Parallel ATA	
	Removable with two screws	
	Supports the following optical formats:	
	DVD±RW and CD-RW Super Multi Double-Layer Combo Drive	
	DVD/CD-RW Combo Drive	
	DVD-ROM Drive	
	Supports no-optical-drive option with blank bezel	
Diskette drive	Supports an external Universal Serial Bus (USB) diskette drive only	
Audio	Azalia ADI1981HD	
	Single speaker	
Integrated monoaural microphone		
	Headphone and microphone jacks	
Modem	• 56K, v.92, data/fax modem (MDC1.5)	
 Modem cable included in Brazil, the Czech Republic, France, Greece, Hungary, Is America, Poland, Russia, Saudi Arabia, Slovakia, Slovenia, South Africa, Turkey, United Kingdom. 		
Ethernet	Intel 10/100/1000 Ethernet	
	Network interface card (NIC) power-down	
	S4/S5 wake on LAN (on AC power only)	
Wireless	Integrated wireless options by way of wireless module	

Category	Description	
	Wireless local area network (WLAN) options:	
	• Broadcom 802.11a/b/g	
	Broadcom 802.11b/g	
	Intel 802.11a/b/g/n with iAMT support	
	Intel 802.11a/b/g with iAMT support	
	 Intel 802.11b/g 	
	Three 2.4-/5.0-GHzWLAN antennas built into display panel	
	Supports no-WLAN option	
	Wireless wide area network (WWAN) options:	
	 Evolution-data optimized (EVDO-A) WWAN module 	
	High-speed downlink packet access (HSPDA) WWAN module	
	Subscriber identity module (SIM)	
	Two 5-band antennas built into display panel	
	Wireless personal area network (WPAN) options:	
	Bluetooth® module	
	Supports no-WPAN option	
External media card	One Type I/II PC Card slot	
Caru	16-bit PCMCIA and 32-bit CardBus	
	Integrated SD flash media slot (SD/MMC support)	
Ports	• 1394a port	
	Docking connector	
	Headphone connector	
	Microphone connector	
	Primary battery connector	
	RJ-11 modem port	
	RJ-45 Ethernet port	
	Smart AC adapter connector	
	USB ports (2)	
	 VGA port (Dsub 15-pin) supporting 1600 × 1200 external resolution @ 75 Hz, hot plug/unpluand auto detect 	
Docking Docking support		

Category Description	
Keyboard/pointing devices	 Spill-resistant keyboard with embedded numeric keypad, TouchPad, pointing stick, and fingerprint reader
	Full-size, 19.05-mm pitch, 4.5-mm height keyboard
	One-way scrolling (vertical)
	Windows Vista™ hardware Start button
	Durable key caps
Power	Primary batteries:
requirements	9-cell, 83-Wh, Li-ion battery with fuel gauge
	6-cell, 55-Wh, Li-ion battery with fuel gauge
	3-cell, 28-Wh Li-ion battery
	65-watt AC adapter with localized cable plug support and 3-wire plug
Security	Support for Kensington security lock
	 Optional integrated active smart card reader (installed in the PC Card slot)
	 Integrated Infineon TPM 1.2 chip (soldered to PCB)
	Integrated USB-based fingerprint reader
Operating system	Preinstalled:
System	Windows Vista Home Basic (32-bit)
	Windows Vista Business (32- and 64-bit)
	Windows® XP Professional
	• FreeDOS
	Certified: Linux
Serviceability	End-user replaceable parts:
	AC adapter
	• Battery
	Bluetooth module
	Hard drive
	Memory module
	Optical drive
	Power cord
	RTC battery
	• SIM
	WLAN module
	WWAN module

2 External component identification

Display components



Item	Component	Function
(1)	Display release latch	Opens the computer.
(2)	Internal display switch	Turns off the display if the display is closed while the computer is on.
(3)	Internal microphone	Records sound.
(4)	Ambient light sensor	When activated, the sensor automatically adjusts the display brightness based on the surrounding lighting conditions.

Top components

Buttons and fingerprint reader




Item	Component	Function
(1)	Power button	 When the computer is off, press the button to turn on the computer.
		 When the computer is on, press the button to shut down the computer.
		 When the computer is in the Sleep state (Windows Vista) or in Standby (Windows XP), press the button briefly to exit the Sleep state or Standby.
		 When the computer is in Hibernation, press the button briefly to exit Hibernation.
		If the computer has stopped responding and Windows® shutdown procedures are ineffective, press and hold the power button for at least 5 seconds to turn off the computer.
		To learn more about power settings, follow these steps:
		 In Windows Vista, select Start > Control Panel > System and Maintenance > Power Options.
		 In Windows XP, select Start > Control Panel > Performance and Maintenance > Power Options.
(2)	Info button	Launches Info Center, which enables you to open various software solutions.
(3)	Wireless button	Turns the wireless feature on or off, but does not establish a wireless connection.
		NOTE: A wireless network must be set up in order to establish a wireless connection.
(4)	Presentation button	Starts the presentation feature.

Item	Component	Function
(5)	TouchPad on/off button	Turns the TouchPad on and off.
(6)	Volume mute button (select models only)	Mutes and restores speaker sound.
(7)	Volume scroll zone	Adjusts speaker volume. Slide your finger to the left to decrease volume and to the right to increase volume.
(8)	HP Fingerprint Sensor	Allows a fingerprint logon to Windows, instead of a password logon.

Keys

NOTE: Your computer may look slightly different from the illustration in this section.



Item	Component	Function
(1)	esc key	Displays system information when pressed in combination with the fn key.
(2)	fn key	Executes frequently used system functions when pressed in combination with a function key or the esc key.
(3)	Windows logo key	Displays the Windows Start menu.
(4)	Windows applications key	Displays a shortcut menu for items beneath the pointer.
(5)	Embedded numeric keypad keys	Can be used like the keys on an external numeric keypad.
(6)	Function keys	Execute frequently used system functions when pressed in combination with the fn key.

Lights



Item	Component	Function
(1)	Wireless lights (2)*	 On: An integrated wireless device, such as a wireless local area network (WLAN) device, the HP Broadband Wireless Module, and/or a Bluetooth® device, is on.
		Off: All wireless devices are off.
(2)	Power lights (2)†	On: The computer is on.
		Blinking: The computer is in Standby.
		 Blinking rapidly: An AC adapter with a higher power rating should be connected.
		Off: The computer is off or in Hibernation.
(3)	Battery light	Amber: A battery is charging.
		Green: A battery is close to full charge capacity.
		 Blinking amber: A battery that is the only available power source has reached a low battery level. When the battery reaches a critical battery level, the battery light begins blinking rapidly.
		 Off: If the computer is plugged into an external power source, the light turns off when all batteries in the computer are fully charged. If the computer is not plugged into an external power source, the light stays off until the battery reaches a low battery level.
(4)	Drive light	 Blinking green: The hard drive or optical drive is being accessed.
		 Amber: HP 3D DriveGuard has temporarily parked the internal hard drive.
(5)	Caps lock light	On: Caps lock is on.

Item	Component	Function
(6)	Num lock light	On: Num lock is on or the embedded numeric keypad is enabled.
(7)	Volume mute light	Off: Computer sound is on.
		On: Computer sound is off.
(8)	Volume down light	On: The volume scroll zone is being used to decrease speaker volume.
(9)	Volume up light	On: The volume scroll zone is being used to increase speaker volume.

^{*}The 2 wireless lights display the same information. The light on the wireless button is visible only when the computer is open. The wireless light on the front of the computer is visible whether the computer is open or closed.

[†]The 2 power lights display the same information. The light on the power button is visible only when the computer is open. The power light on the front of the computer is visible whether the computer is open or closed.

Pointing devices




Item	Component	Function
(1)	TouchPad on/off button	Turns the TouchPad on and off.
(2)	Pointing stick	Moves the pointer and selects or activates items on the screen.
(3)	Left pointing stick button*	Functions like the left button on an external mouse.
(4)	TouchPad*	Moves the pointer and selects or activates items on the screen.
(5)	Left TouchPad button*	Functions like the left button on an external mouse.
(6)	Right TouchPad button*	Functions like the right button on an external mouse.
(7)	TouchPad scroll zone	Scrolls up or down.
(8)	Right pointing stick button*	Functions like the right button on an external mouse.

^{*}This table describes factory settings. View or change pointing device preferences as follows:


- In Windows Vista, select Start > Control Panel > Hardware and Sound > Mouse.
- In Windows XP, select Start > Control Panel > Printers and Other Hardware > Mouse.

Front components



Item	Component	Function
(1)	Wireless light	 On: An integrated wireless device, such as a WLAN device, the HP Broadband Wireless Module, and/or a Bluetooth device, is turned on.
		Off: All wireless devices are turned off.
(2)	Power light	On: The computer is on.
		 Blinking: The computer is in the Sleep state (Windows Vista) or in Standby (Windows XP).
		 Blinking rapidly: An AC adapter with a higher power rating should be connected.
		Off: The computer is off or in Hibernation.
(3)	Battery light	Amber: A battery is charging.
		Green: A battery is close to full charge capacity.
		 Blinking amber: A battery that is the only available power source has reached a low battery level. When the battery reaches a critical battery level, the battery light begins blinking rapidly.
		 Off: If the computer is plugged into an external power source, the light turns off when all batteries in the computer are fully charged. If the computer is not plugged into an external power source, the light stays off until the battery reaches a low battery level.
(4)	Drive light	 Blinking green: The hard drive or optical drive is being accessed.
		 Amber (select models only): HP 3D DriveGuard has temporarily parked the hard drive.
(5)	Bluetooth module (select models only)	Sends and receives Bluetooth device signals.
		WARNING! Exposure to Radio Frequency Radiation. The radiated output power of this device is below the FCC radio frequency exposure limits. Nevertheless, the device should be used in such a manner that the potential for human contact during normal operation is minimized. To avoid the possibility of exceeding the FCC radio frequency exposure limits, human proximity to the antennae should be not less than 20 cm (8 inches) during normal operation, including when the computer display is closed.
(6)	Display release latch	Opens the computer.

Left-side components



Item	Component	Function
(1)	Power connector	Connects an AC adapter.
(2)	RJ-11 (modem) jack	Connects a modem cable.
(3)	USB port	Depending on your computer model, the USB port is either a standard USB port or a powered USB port. A standard USB port connects an optional USB device. A powered USB port provides power to an external device if used with a powered USB cable.
(4)	Vent	Enables airflow to cool internal components.
		NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.
(5)	Optical drive (select models only)	Reads an optical disc.
(6)	Optical drive light	Blinking: The optical drive is being accessed.


Rear components




Item	Component	Function
(1)	RJ-45 (network) jack	Connects a network cable.
(2)	Security cable slot	Attaches an optional security cable to the computer.
		NOTE: The security cable is designed to act as a deterrent, but it may not prevent the computer from being mishandled or stolen.

Right-side components

NOTE: Computer features vary depending on model. Refer to one of the following illustrations.




Item	Component	Function
(1)	PC Card slot (select models only)	Supports optional Type I or Type II PC Cards.
(2)	Media Card Reader	Supports the following optional digital card formats: Secure Digital (SD) Memory Card, MultiMediaCard (MMC).
(3)	1394a port	Connects an optional IEEE 1394 or 1394a device, such as a camcorder.
(4)	Audio-out (headphone) jack	Produces computer sound when connected to optional powered stereo speakers, headphones, ear buds, a headset, or television audio.
(5)	Audio-in (microphone) jack	Connects an optional computer headset microphone, stereo array microphone, or monaural microphone.
(6)	USB port	Connects an optional USB device.
(7)	External monitor port	Connects an external VGA monitor or projector.
(8)	Vent	Enables airflow to cool internal components. NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.
(9)	Docking connector	Connects an optional docking device.



Item	Component	Function
(1)	Smart card reader (select models only)	Supports smart cards and Java™ Cards.
(2)	Media Card Reader	Supports the following optional digital card formats: Secure Digital (SD) Memory Card, MultiMediaCard (MMC).
(3)	1394a port	Connects an optional IEEE 1394 or 1394a device, such as a camcorder.

Item	Component	Function
(4)	Audio-out (headphone) jack	Produces computer sound when connected to optional powered stereo speakers, headphones, ear buds, a headset, or television audio.
(5)	Audio-in (microphone) jack	Connects an optional computer headset microphone, stereo array microphone, or monaural microphone.
(6)	USB port	Connects an optional USB device.
(7)	External monitor port	Connects an external VGA monitor or projector.
(8)	Vent	Enables airflow to cool internal components. NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.
(9)	Docking connector	Connects an optional docking device.

Bottom components




Item	Component	Function
(1)	Speaker	Produces computer sound.
(2)	Memory module/WLAN module compartment	Contains a memory module slot and a WLAN module slot.
		CAUTION: To prevent an unresponsive system, replace the wireless module only with a wireless module authorized for use in the computer by the governmental agency that regulates wireless devices in your country or region. If you replace the module and then receive a warning message, remove the module to restore computer functionality, and then contact technical support through Help and Support.
(3)	Hard drive bay	Holds the hard drive.
(4)	Vents (6)	Enable airflow to cool internal components.
		NOTE: The computer fan starts up automatically to cool internal components and prevent overheating. It is normal for the internal fan to cycle on and off during routine operation.
(5)	Battery release latches (2)	Release the battery from the battery bay.
(6)	Battery bay	Holds the battery.
(7)	SIM slot	Contains a subscriber identity module (SIM). The SIM slot is located inside the battery bay.

Item	Component	Function
(8)	WWAN module compartment	Contains a WWAN module slot.
		CAUTION: To prevent an unresponsive system, replace the wireless module only with a wireless module authorized for use in the computer by the governmental agency that regulates wireless devices in your country or region. If you replace the module and then receive a warning message, remove the module to restore computer functionality, and then contact technical support through Help and Support.
(9)	Business-card holder	Holds a standard-sized business card.
(10)	Bluetooth module compartment (select models only)	Contains a Bluetooth device.


3 Illustrated parts catalog

Serial number location

When ordering parts or requesting information, provide the computer serial number and model number located on the bottom of the computer.



Computer major components



Item	Description	Spare part number
(1)	12.1-inch, WXGA display assembly with AntiGlare (includes wireless antenna transceivers and cables, and microphone and cable)	451741-001
	Display internal components:	
	Display bezel	451733-001
	Display panel cable	451735-001

Item	Description	Spare part numbe			
	Display enclosure (includes WLAN and WWAN antenna transceivers and cables)	451736-001			
	Display hinges	451734-001			
	Display lid switch module	451724-001			
	Display Screw Kit	451737-001			
(2)	Switch cover (includes LED board and cable)	451717-001			
(3)	Keyboards (include pointing stick and pointing stick cable)				
	Belgium	451748-A41			
	Brazil	451748-201			
	The Czech Republic	451748-221			
	Denmark	451748-081			
	France	451748-051			
	French Canada	451748-121			
	Germany	451748-041			
	Greece	451748-151			
	Hungary	451748-211			
	Iceland	451748-DD1			
	The Netherlands and Europe	451748-021			
	Israel	451748-BB1			
	Italy	451748-061			
	Japan	451748-291			
	Latin America	451748-161			
	Norway	451748-091			
	Portugal	451748-131			
	Russia	451748-251			
	Saudi Arabia	451748-171			
	Slovakia	451748-231			
	Slovenia	451748-BA1			
	South Korea	451748-AD1			
	Spain	451748-071			
	Sweden and Finland	451748-B71			
	Switzerland	451748-111			
	Taiwan	451748-AB1			
	Thailand	451748-281			
	Turkey	451748-141			

Item	Description	Spare part number			
	The United Kingdom	451748-031			
	The United States	451748-001			
(4)	Top cover (includes TouchPad and fingerprint reader board)	451723-001			
	NOTE: The fingerprint reader board cable is included in the Cable Kit, spare part number 451722-001.				
(5)	PC Card assembly	451742-001			
	Plastics Kit (see Plastics Kit on page 25 for more Plastics Kit spare part information):	451743-001			
(6a)	PC Card slot bezel				
(6b)	Memory module/WLAN module compartment cover				
(6c)	Bluetooth module compartment cover				
(6d)	Hard drive cover				
(6e)	WWAN module compartment cover				
(7)	System boards (include thermal material and alcohol pad)				
	Equipped with Intel Core Duo U7700 (1.33-GHz) processor (533-MHz FSB and 2-MB L2 cache)	464764-001			
	Equipped with Intel Core Duo U7600 (1.20-GHz) processor (533-MHz FSB and 2-MB L2 cache)	451720-001			
	Equipped with Intel Core Duo U7500 (1.06-GHz) processor (533-MHz FSB and 2-MB L2 cache)	451719-001			
(8)	Speaker assembly	451747-001			
(9)	Modem modules (include modem module cable)				
	For use in all countries and regions except Australia and New Zealand	443899-001			
	For use only in Australia and New Zealand	443899-011			
(10)	Optical drives (include bezel)				
	DVD±RW and CD-RW Double-Layer Combo Drive	451727-001			
	DVD/CD-RW Combo Drive	451725-001			
	DVD-ROM Drive	451726-001			
(11)	Fan/heat sink assembly (includes thermal material)	451731-001			
(12)	Base enclosure (includes front LED board, front LED board cable, and rubber feet)	451712-001			
	Rubber Kit (not illustrated; includes 5 rubber feet and 2 base enclosure screw covers)	451744-001			
(13)	Batteries				
	9-cell, 83-Wh Li-ion	451715-001			
	6-cell, 55-Wh Li-ion	451714-001			
	3-cell, 28-Wh Li-ion	451713-001			
(14)	WLAN modules				

em	Des	scription	Spare part numbe
	802	2.11a/b/g/n Broadcom WLAN modules:	
	•	For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States	441530-001
	•	For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belgium, Belize, Benin, Bermuda, Bolivia, Bosnia & Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Cayman Islands, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guam, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Jamaica, Jordan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Puerto Rico, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe	441530-002
	•	For use in Japan	441530-291
	802	2.11a/b/g/n Intel WLAN modules:	
	•	For use in Antigua and Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, Uruguay, the United States, Venezuela, and Vietnam	441086-001
	•	For use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan	441086-002
	•	For use in Australia, New Zealand, Pakistan, the People's Republic of China, and South Korea	441086-003
	•	For use in Japan	441086-291
	802	2.11a/b/g Broadcom WLAN modules:	
	•	For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States	441075-001

ltem Description Spare part number For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, 441075-002 Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe 441075-291 For use in Japan 802.11a/b/g Intel WLAN modules: For use in Antigua & Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, 441082-001 Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, the United States, Uruguay, Venezuela, and Vietnam For use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia, Cyprus, the 441082-002 Czech Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan For use in Australia, New Zealand, Pakistan, the People's Republic of China, and 441082-003 South Korea 441082-291 For use in Japan 802.11b/g Broadcom WLAN modules: For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, 441090-001 and the United States


Item	Description	Spare part number

441090-002

For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia & Herzegovina Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Thailand, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

	For use in Japan	441090-291
	802.11b/g Intel WLAN module for use in Thailand	448675-004
(15)	RTC battery	451716-001
(16)	Memory modules (667-MHz, PC2-5300, 1-DIMM)	
	2048-MB	451739-001
	1024-MB	451738-001
	512-MB	451740-001
(17)	Bluetooth module (includes Bluetooth module cable)	451721-001
(18)	Hard drives (include hard drive bracket and connector)	
	100-GB, 4200-rpm	453504-001
	80-GB, 4200-rpm	451730-001
	60-GB, 4200-rpm	451729-001
(19)	WWAN modules	
	Verizon EVDO-A WWAN module	451131-001
	Cingular HSPDA WWAN module	448673-002
	Vodafone HSPDA WWAN module	448672-002
	Cable Kit (not illustrated; see Cable Kit on page 26 for more Cable Kit spare part number information)	451722-001
	Smart card reader module (not illustrated)	451746-001

Plastics Kit



Item	Description	Spare part number
	Plastics Kit:	451743-001
(1)	Bluetooth module compartment cover (includes 1 captive screw, secured by a C-clip)	
(2)	Hard drive cover (includes 2 captive screws, secured by C-clips)	
(3)	Memory module/WLAN module compartment cover (includes 2 captive screws, secured by C-clips)	
(4)	WWAN module compartment cover (includes 1 captive screw, secured by a C-clip)	
(5)	PC Card slot bezel	

Cable Kit

Item	Description	Spare part number
	Cable Kit:	451722-001
(1)	Bluetooth module cable	
(2)	Fingerprint reader board cable	
(3)	Modem cable	
(4)	LED cable	
(5)	Capacity board cable	

Mass storage devices



Item	Description	Spare part number
(1)	Optical drives (include bezel)	
	DVD±RW and CD-RW Double-Layer Combo Drive	451727-001
	DVD/CD-RW Combo Drive	451725-001
	DVD-ROM Drive	451726-001
(2)	Hard drives (include isolator and connector cable)	
	100-GB, 4200-rpm	453504-001
	80-GB, 4200-rpm	451730-001
	60-GB, 4200-rpm	451729-001

Miscellaneous parts

Description	Spare part number
65-watt AC adapter (HP Smart Adapter)	412786-001
HP 2400 Ultra-Light Docking Station	412787-001
HP 2500 Ultra-Light Docking Station	455157-001
External MultiBay II	366143-001
External MultiBay II power cable and stand	366144-001
HP Extended Life Battery	367456-001
Label Kit	451732-001
MultiBay 8X DVD-ROM Drive	373314-001
MultiBay 24X DVD/CD-RW Combo Drive	373315-001

Description	Spare part number
Nylon carrying case	325814-001
USB 1.1 diskette drive	359118-001
Power cords:	
For use in Argentina	394279-D01
For use in Australia	394279-011
For use in Brazil	394279-201
For use in Denmark	394279-081
For use in Europe, the Middle East, and Africa	394279-021
For use in Israel	394279-BB1
For use in India	394279-D61
For use in Italy	394279-061
For use in Japan	394279-291
For use in the People's Republic of China	394279-AA1
For use in South Korea	394279-AD1
For use in Switzerland	394279-111
For use in Taiwan	394279-AB1
For use in the United Kingdom	394279-031
For use the United States	394279-001
Screw Kit	451745-001

- Phillips PM2.5×4.0 screw
- Phillips PM2.0×10.0 screw
- Phillips PM2.0×5.0 captive screw
- Phillips PM2.0×5.0 screw
- Phillips PM2.0×4.0 screw
- Phillips PM2.0×3.0 screw
- Phillips PM2.0×2.0 broad-head screw
- Phillips PM2.0×2.0 screw
- Phillips PM1.5×3.0 screw
- Torx T8M2.5×7.0 screw
- Torx T8M2.5×4.0 screw
- Torx T6M2.0×5.0 screw

Sequential part number listing

Spare part number	Description
394279-001	3-wire power cord for use in the United States
394279-011	3-wire power cord for use in Australia
394279-021	3-wire power cord for use in Europe
394279-031	3-wire power cord for use in the United Kingdom
394279-061	3-wire power cord for use in Italy
394279-081	3-wire power cord for use in Denmark
394279-111	3-wire power cord for use in Switzerland
394279-201	3-wire power cord for use in Brazil
394279-291	3-wire power cord for use in Japan
394279-AA1	3-wire power cord for use in the People's Republic of China
394279-AB1	3-wire power cord for use in Taiwan
394279-AD1	3-wire power cord for use in South Korea
394279-BB1	3-wire power cord for use in Israel
394279-D01	3-wire power cord for use in Argentina
394279-D61	3-wire power cord for use in India
412786-001	65-watt AC adapter (HP Smart Adapter)
412787-001	HP 2400 Ultra-Light Docking Station
441075-001	802.11a/b/g Broadcom WLAN module for use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States
441075-002	802.11a/b/g Broadcom WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbeki
441075-291	802.11a/b/g Broadcom WLAN module for use in Japan

Spare part number	Description
441082-001	802.11a/b/g Intel WLAN module for use in Antigua & Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, the United States, Uruguay, Venezuela, and Vietnam
441082-002	802.11a/b/g Intel WLAN module for use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan
441082-003	802.11a/b/g Intel WLAN module for use in Australia, New Zealand, Pakistan, the People's Republic of China, and South Korea
441082-291	802.11a/b/g Intel WLAN module for use in Japan
441086-001	802.11a/b/g/n Intel WLAN module for use in Antigua and Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, Uruguay, the United States, Venezuela and Vietnam
441086-002	802.11a/b/g/n Intel WLAN module for use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia Cyprus, the Czech Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan
441086-003	802.11a/b/g/n Intel WLAN module for use in Australia, New Zealand, Pakistan, the People's Republic of China, and South Korea
441086-291	802.11a/b/g/n Intel WLAN module for use in Japan
441090-001	802.11b/g Broadcom WLAN module for use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States
441090-002	802.11b/g Broadcom WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia & Herzegovina Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Thailand, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arat Emirates, the Unite
	802.11b/g Broadcom WLAN module for use in Japan

Spare part number	Description	
441530-001	802.11a/b/g/n Broadcom WLAN module for use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States	
441530-002	802.11a/b/g/n Broadcom WLAN module for use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belgium, Belize, Benin, Bermuda, Bolivia, Bosnia & Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Cayman Islands, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guam, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Jamaica, Jordan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Puerto Rico, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe	
441530-291	802.11a/b/g/n Broadcom WLAN module for use in Japan	
443899-001	Modem module for use in all countries and regions except Australia and New Zealand (includes modem module cable)	
443899-011	Modem module for use only in Australia and New Zealand (includes modem module cable)	
448672-002	Vodafone HSPDA WWAN module	
448673-002	Cingular HSPDA WWAN module	
448675-004	802.11b/g Intel WLAN module for use in Thailand	
451131-001	Verizon EVDO-A WWAN module	
451712-001	Base enclosure (includes front LED board, front LED board cable, and rubber feet)	
451713-001	3-cell, 28-Wh Li-ion battery	
451714-001	6-cell, 55-Wh Li-ion battery	
451715-001	9-cell, 83-Wh Li-ion battery	
451716-001	RTC battery	
451717-001	Switch cover (includes LED board and cable)	
451719-001	System board equipped with Intel Core Duo U7600 (1.20-GHz) processor (533-MHz FSB and 2-MB L2 cache; includes thermal material and alcohol pad)	
451720-001	System board equipped with Intel Core Duo U7500 (1.06-GHz) processor (533-MHz FSB and 2-MB L2 cache; includes thermal material and alcohol pad)	
451721-001	Bluetooth module (includes Bluetooth module cable)	
451722-001	Cable Kit (see Cable Kit on page 26 for more Cable Kit spare part number information)	
451723-001	Top cover (includes TouchPad and fingerprint reader board)	
	NOTE: The fingerprint reader board cable is included in the Cable Kit, spare part number 451722-001.	

Spare part number	Description
451724-001	Display lid switch module
451725-001	DVD/CD-RW Combo Drive
451726-001	DVD-ROM Drive
451727-001	DVD±RW and CD-RW Double-Layer Combo Drive
451729-001	60-GB, 4200-rpm hard drive (includes hard drive bracket and connector)
451730-001	80-GB, 4200-rpm hard drive (includes hard drive bracket and connector)
451731-001	Fan/heat sink assembly (includes thermal material)
451732-001	Label Kit
451733-001	Display bezel
451734-001	Display hinges
451735-001	Display panel cable
451736-001	Display enclosure (includes WLAN and WWAN antenna transceivers and cables)
451737-001	Display Screw Kit
451738-001	1024-MB memory module (667-MHz, PC2-5300, 1-DIMM)
451739-001	2048-MB memory module (667-MHz, PC2-5300, 1-DIMM)
451740-001	512-MB memory module (667-MHz, PC2-5300, 1-DIMM)
451741-001	12.1-inch, WXGA display assembly with AntiGlare (includes wireless antenna transceivers and cables and microphone and cable)
451742-001	PC Card assembly
451743-001	Plastics Kit (see Plastics Kit on page 25 for more Plastics Kit spare part information):
451744-001	Rubber Kit (includes 5 computer feet and 2 base enclosure screw covers)
451745-001	Screw Kit
451746-001	Smart card reader module
451747-001	Speaker assembly
451748-001	Keyboard for use in the United States
451748-021	Keyboard for use in the Netherlands and Europe
451748-031	Keyboard for use in the United Kingdom
451748-041	Keyboard for use in Germany
451748-051	Keyboard for use in France
451748-061	Keyboard for use in Italy
451748-071	Keyboard for use in Spain
451748-081	Keyboard for use in Denmark
451748-091	Keyboard for use in Norway
451748-111	Keyboard for use in Switzerland

Spare part number	Description
451748-121	Keyboard for use in French Canada
451748-131	Keyboard for use in Portugal
451748-141	Keyboard for use in Turkey
451748-151	Keyboard for use in Greece
451748-161	Keyboard for use in Latin America
451748-171	Keyboard for use in Saudi Arabia
451748-201	Keyboard for use in Brazil
451748-211	Keyboard for use in Hungary
451748-221	Keyboard for use in the Czech Republic
451748-231	Keyboard for use in Slovakia
451748-251	Keyboard for use in Russia
451748-281	Keyboard for use in Thailand
451748-291	Keyboard for use in Japan
451748-A41	Keyboard for use in Belgium
451748-AB1	Keyboard for use in Taiwan
451748-AD1	Keyboard for use in South Korea
451748-B71	Keyboard for use in Sweden and Finland
451748-BA1	Keyboard for use in Slovenia
451748-BB1	Keyboard for use in Israel
451748-DD1	Keyboard for use in Iceland
453504-001	100-GB, 4200-rpm hard drive (includes hard drive bracket and connector)
455157-001	HP 2500 Ultra-Light Docking Station
464764-001	System board equipped with Intel Core Duo U7700 (1.33-GHz) processor (533-MHz FSB and 2-MB L2 cache; includes thermal material and alcohol pad)

4 Removal and replacement procedures

Preliminary replacement requirements

Tools required

You will need the following tools to complete the removal and replacement procedures:

- Flat-bladed screwdriver
- Magnetic screwdriver
- Phillips P0 and P1 screwdrivers
- Torx T8 screwdriver

Service considerations

The following sections include some of the considerations that you must keep in mind during disassembly and assembly procedures.

NOTE: As you remove each subassembly from the computer, place the subassembly (and all accompanying screws) away from the work area to prevent damage.

Plastic parts

Using excessive force during disassembly and reassembly can damage plastic parts. Use care when handling the plastic parts. Apply pressure only at the points designated in the maintenance instructions.

Cables and connectors

△ **CAUTION:** When servicing the computer, be sure that cables are placed in their proper locations during the reassembly process. Improper cable placement can damage the computer.

Cables must be handled with extreme care to avoid damage. Apply only the tension required to unseat or seat the cables during removal and insertion. Handle cables by the connector whenever possible. In all cases, avoid bending, twisting, or tearing cables. Be sure that cables are routed in such a way that they cannot be caught or snagged by parts being removed or replaced. Handle flex cables with extreme care; these cables tear easily.

Drive handling

△ CAUTION: Drives are fragile components that must be handled with care. To prevent damage to the computer, damage to a drive, or loss of information, observe these precautions:

Before removing or inserting a hard drive, shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.

Before handling a drive, be sure that you are discharged of static electricity. While handling a drive, avoid touching the connector.

Before removing a diskette drive or optical drive, be sure that a diskette or disc is not in the drive and be sure that the optical drive tray is closed.

Handle drives on surfaces covered with at least one inch of shock-proof foam.

Avoid dropping drives from any height onto any surface.

After removing a hard drive, an optical drive, or a diskette drive, place it in a static-proof bag.

Avoid exposing a hard drive to products that have magnetic fields, such as monitors or speakers.

Avoid exposing a drive to temperature extremes or liquids.

If a drive must be mailed, place the drive in a bubble pack mailer or other suitable form of protective packaging and label the package "FRAGILE."

Grounding guidelines

Electrostatic discharge damage

Electronic components are sensitive to electrostatic discharge (ESD). Circuitry design and structure determine the degree of sensitivity. Networks built into many integrated circuits provide some protection, but in many cases, ESD contains enough power to alter device parameters or melt silicon junctions.

A discharge of static electricity from a finger or other conductor can destroy static-sensitive devices or microcircuitry. Even if the spark is neither felt nor heard, damage may have occurred.

An electronic device exposed to ESD may not be affected at all and can work perfectly throughout a normal cycle. Or the device may function normally for a while, then degrade in the internal layers, reducing its life expectancy.

△ **CAUTION**: To prevent damage to the computer when you are removing or installing internal components, observe these precautions:

Keep components in their electrostatic-safe containers until you area ready to install them.

Use nonmagnetic tools.

Before touching an electronic component, discharge static electricity by using the guidelines described in this section.

Avoid touching pins, leads, and circuitry. Handle electronic components as little as possible.

If you remove a component, place it in an electrostatic-safe container.

The following table shows how humidity affects the electrostatic voltage levels generated by different activities.

△ CAUTION: A product can be degraded by as little as 700 V.

Typical electrostatic voltage levels

	Relative humidity		
Event	10%	40%	55%
Walking across carpet	35,000 V	15,000 V	7,500 V
Walking across vinyl floor	12,000 V	5,000 V	3,000 V
Motions of bench worker	6,000 V	800 V	400 V
Removing DIPS from plastic tube	2,000 V	700 V	400 V
Removing DIPS from vinyl tray	11,500 V	4,000 V	2,000 V
Removing DIPS from Styrofoam	14,500 V	5,000 V	3,500 V
Removing bubble pack from PCB	26,500 V	20,000 V	7,000 V
Packing PCBs in foam-lined box	21,000 V	11,000 V	5,000 V

Packaging and transporting guidelines

Follow these grounding guidelines when packaging and transporting equipment:

- To avoid hand contact, transport products in static-safe tubes, bags, or boxes.
- Protect ESD-sensitive parts and assemblies with conductive or approved containers or packaging.
- Keep ESD-sensitive parts in their containers until the parts arrive at static-free workstations.
- Place items on a grounded surface before removing items from their containers.
- Always be properly grounded when touching a component or assembly.
- Store reusable ESD-sensitive parts from assemblies in protective packaging or nonconductive foam.
- Use transporters and conveyors made of antistatic belts and roller bushings. Be sure that
 mechanized equipment used for moving materials is wired to ground and that proper materials
 are selected to avoid static charging. When grounding is not possible, use an ionizer to dissipate
 electric charges.

Workstation guidelines

Follow these grounding workstation guidelines:

- Cover the workstation with approved static-shielding material.
- Use a wrist strap connected to a properly grounded work surface and use properly grounded tools and equipment.
- Use conductive field service tools, such as cutters, screwdrivers, and vacuums.
- When fixtures must directly contact dissipative surfaces, use fixtures made only of static-safe materials.
- Keep the work area free of nonconductive materials, such as ordinary plastic assembly aids and Styrofoam.
- Handle ESD-sensitive components, parts, and assemblies by the case or PCM laminate. Handle these items only at static-free workstations.
- Avoid contact with pins, leads, or circuitry.
- Turn off power and input signals before inserting or removing connectors or test equipment.

Equipment guidelines

Grounding equipment must include either a wrist strap or a foot strap at a grounded workstation.

- When seated, wear a wrist strap connected to a grounded system. Wrist straps are flexible straps with a minimum of one megohm ±10% resistance in the ground cords. To provide proper ground, wear a strap snugly against the skin at all times. On grounded mats with banana-plug connectors, use alligator clips to connect a wrist strap.
- When standing, use foot straps and a grounded floor mat. Foot straps (heel, toe, or boot straps)
 can be used at standing workstations and are compatible with most types of shoes or boots. On
 conductive floors or dissipative floor mats, use foot straps on both feet with a minimum of one
 megohm resistance between the operator and ground. To be effective, the conductive strips
 must be worn in contact with the skin.

The following grounding equipment is recommended to prevent electrostatic damage:

- Antistatic tape
- Antistatic smocks, aprons, and sleeve protectors
- Conductive bins and other assembly or soldering aids
- Nonconductive foam
- Conductive tabletop workstations with ground cords of one megohm resistance
- Static-dissipative tables or floor mats with hard ties to the ground
- Field service kits
- Static awareness labels
- Material-handling packages
- Nonconductive plastic bags, tubes, or boxes
- Metal tote boxes
- Electrostatic voltage levels and protective materials

The following table lists the shielding protection provided by antistatic bags and floor mats.

Material	Use	Voltage protection level
Antistatic plastic	Bags	1,500 V
Carbon-loaded plastic	Floor mats	7,500 V
Metallized laminate	Floor mats	5,000 V

Unknown user password

If the computer you are servicing has an unknown user password, follow these steps to clear the password:

- NOTE: These steps also clear CMOS.
 - 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
 - 2. Disconnect all external devices connected to the computer.
 - 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
 - 4. Remove the battery (see <u>Battery on page 41</u>).
 - 5. Remove the real-time clock (RTC) battery (see RTC battery on page 47).
 - 6. Wait approximately 5 minutes.
 - 7. Replace the RTC battery and reassemble the computer.
 - 8. Connect AC power to the computer. Do not reinsert any batteries at this time.
 - **9.** Turn on the computer.

All passwords and all CMOS settings have been cleared.


Component replacement procedures

This chapter provides removal and replacement procedures.

There are as many as 67 screws, in 12 different sizes, that must be removed, replaced, or loosened when servicing the computer. Make special note of each screw size and location during removal and replacement.


Serial number

Report the computer serial number to HP when requesting information or ordering spare parts. The serial number is located on the bottom of the computer.



Computer feet

The computer feet are adhesive-backed rubber pads. The feet are included in the Rubber Kit, spare part number 451744-001. There are 5 rubber feet that attach to the base enclosure in the locations illustrated below.



Battery


Description	Spare part number
9-cell, 83-Ah, Li-ion battery	451715-001
6-cell, 55-Ah, Li-ion battery	451714-001
3-cell, 28-Ah, Li-ion battery	451713-001

Before disassembling the computer, follow these steps:

- Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.

Remove the battery:

- Turn the computer upside down on a flat surface, with the battery bay toward you. 1.
- 2. Slide the battery release latches (1) to release the battery.
- 3. Remove the battery (2) from the computer.



Install the battery by inserting it into the battery bay until you hear a click.

SIM

NOTE: This section applies only to computer models with WWAN capability.


NOTE: If there is a SIM inserted in the SIM slot, it must be removed before disassembling the computer. Be sure that the SIM is reinserted in the SIM slot after reassembling the computer.

Before removing the SIM, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).

Remove the SIM:

- 1. Press in on the SIM (1). (The module is partially ejected from the SIM slot.)
- 2. Remove the SIM (2) from the SIM slot.



Reverse this procedure to install the SIM.

Bluetooth module


Description	Spare part number
Bluetooth (includes Bluetooth module cable)	451721-001

Before removing the Bluetooth module, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- Remove the battery (see <u>Battery on page 41</u>).

Remove the Bluetooth® module:


- 1. Position the computer with the front toward you.
- 2. Loosen the Phillips PM2.0×5.0 captive screw (1) that secures the Bluetooth module compartment cover to the computer.
- 3. Tilt the cover (2) forward to disengage if from the base enclosure.
- 4. Swing the cover (3) up and back to remove it from the base enclosure. The Bluetooth module compartment cover is included in the Plastics Kit, spare part number 451743-001.



5. Disconnect the Bluetooth module cable from the system board (1) and from the Bluetooth module (2).



- 6. Remove the Phillips PM2.0×5.0 screw (1) that secures the Bluetooth module to the Bluetooth module compartment cover.
- 7. Remove the Bluetooth module (2) from the cover.



Reverse this procedure to reassemble and install the Bluetooth module.

Memory module

Description	Spare part number
2048-MB (667-MHz, PC2-5300, 1-DIMM)	451739-001
1024-MB (667-MHz, PC2-5300, 1-DIMM)	451738-001
512-MB (667-MHz, PC2-5300, 1-DIMM)	451740-001

Before removing the memory module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- **4.** Remove the battery (see <u>Battery on page 41</u>).


Remove the memory module:

- 1. Position the computer with the rear panel toward you.
- 2. Loosen the two Phillips PM2.0×5.0 captive screws (1) that secure the memory module/WLAN module compartment cover to the computer.
- 3. Lift the rear edge of the cover (2), swing it up and forward, and remove the cover. The memory module/WLAN module compartment cover is included in the Plastics Kit, spare part number 451743-001.



4. Spread the retaining tabs (1) on each side of the memory module slot to release the memory module. (The edge of the module opposite the slot rises away from the computer.)

- 5. Remove the memory module (2) by pulling the module away from the slot at an angle.
- NOTE: Memory modules are designed with a notch (3) to prevent incorrect installation into the memory module slot.



Reverse this procedure to install the memory module.

RTC battery

NOTE: Removing the RTC battery and leaving it uninstalled for 5 or more minutes causes all passwords and CMOS settings to be cleared.


Description	Spare part number
RTC battery	451716-001

Before removing the RTC battery, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- Remove the memory module (see <u>Memory module on page 45</u>).

Remove the RTC battery:

- 1. Disconnect the RTC battery cable (1) from the system board.
- 2. Release the RTC battery (2) from the clip built into the base enclosure by sliding it forward.
- 3. Remove the RTC battery (3).



Reverse this procedure to install the RTC battery.

WLAN module

△ CAUTION: The WLAN module and the WWAN module are not interchangeable.

Des	scription	Spare part number	
302	.11a/b/g/n Broadcom WLAN modules:		
	For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States	441530-001	
	For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belgium, Belize, Benin, Bermuda, Bolivia, Bosnia & Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Cayman Islands, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guam, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Italy, the Ivory Coast, Jamaica, Jordan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Puerto Rico, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe	441530-002	
	For use in Japan	441530-291	
802	.11a/b/g/n Intel WLAN modules:		
	For use in Antigua and Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, Uruguay, the United States, Venezuela, and Vietnam	441086-001	
	For use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan	441086-002	
	For use in Australia, New Zealand, Pakistan, the People's Republic of China, and South Korea	441086-003	
	For use in Japan	441086-291	
02	.11a/b/g Broadcom WLAN modules:		
,	For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the United States	441075-001	

Description Spare part number

For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antiqua and Barbuda, Argentina, Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia and Herzegovina, Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Pakistan, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Togo, Tonga, Trinidad and Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

441075-002

For use in Japan 441075-291

802.11a/b/g Intel WLAN modules:

For use in Antigua & Barbuda, Argentina, Aruba, the Bahamas, Barbados, Bermuda, Brunei, Canada, the Cayman Islands, Chile, Colombia, Costa Rica, the Dominican Republic, Ecuador, El Salvador, Guam, Guatemala, Haiti, Honduras, Hong Kong, India, Indonesia, Malaysia, Mexico, Panama, Paraguay, Peru, Saudi Arabia, Taiwan, the United States, Uruguay, Venezuela, and Vietnam

441082-001

- For use in Austria, Azerbaijan, Bahrain, Belgium, Brazil, Bulgaria, Croatia, Cyprus, the Czech 441082-002 Republic, Denmark, Egypt, Estonia, Finland, France, Georgia, Germany, Greece, Hungary, Iceland, Ireland, Israel, Italy, Latvia, Lebanon, Liechtenstein, Lithuania, Luxembourg, Malta, Monaco, the Netherlands, Norway, Oman, the Philippines, Poland, Portugal, Qatar, Romania, Russia, Serbia and Montenegro, Singapore, Slovakia, Slovenia, South Africa, Spain, Sri Lanka, Sweden, Switzerland, Turkey, Ukraine, the United Kingdom, and Uzbekistan
 - 441082-003
- Korea

For use in Australia, New Zealand, Pakistan, the People's Republic of China, and South

441082-291

802.11b/g Broadcom WLAN modules:

For use in Japan

For use in Canada, the Cayman Islands, Guam, Puerto Rico, the U.S. Virgin Islands, and the 441090-001 **United States**

Description Spare part number

For use in Afghanistan, Albania, Algeria, Andorra, Angola, Antigua & Barbuda, Argentina, 441090-002 Armenia, Aruba, Australia, Austria, Azerbaijan, the Bahamas, Bahrain, Bangladesh, Barbados, Belarus, Belgium, Belize, Benin, Bermuda, Bhutan, Bolivia, Bosnia & Herzegovina Botswana, Brazil, the British Virgin Islands, Brunei, Bulgaria, Burkina Faso, Burundi, Cambodia, Cameroon, Cape Verde, the Central African Republic, Chad, Chile, Colombia, Comoros, the Congo, Costa Rica, Croatia, Cyprus, the Czech Republic, Denmark, Djibouti, Dominica, the Dominican Republic, East Timor, Ecuador, Egypt, El Salvador, Equitorial Guinea, Eritrea, Estonia, Ethiopia, Fiji, Finland, France, French Guiana, Gabon, Gambia, Georgia, Germany, Ghana, Gibraltar, Greece, Grenada, Guadeloupe, Guatemala, Guinea, Guinea-Bissa, Guyana, Haiti, Honduras, Hong Kong, Hungary, Iceland, India, Indonesia, Ireland, Israel, Italy, the Ivory Coast, Jamaica, Jordan, Kazakhstan, Kenya, Kiribati, Kuwait, Kyrgyzstan, Laos, Latvia, Lebanon, Lesotho, Liberia, Liechtenstein, Lithuania, Luxembourg, Macedonia, Madagascar, Malawi, Malaysia, the Maldives, Mali, Malta, the Marshall Islands, Martinique, Mauritania, Mauritius, Mexico, Micronesia, Monaco, Mongolia, Montenegro, Morocco, Mozambique, Namibia, Nauru, Nepal, the Nether Antilles, the Netherlands, New Zealand, Nicaragua, Niger, Nigeria, Norway, Oman, Palau, Panama, Papua New Guinea, Paraguay, the People's Republic of China, Peru, the Philippines, Poland, Portugal, Qatar, the Republic of Moldova, Romania, Russia, Rwanda, Samoa, San Marino, Sao Tome & Principe, Saudi Arabia, Senegal, Serbia and Montenegro, the Seychelles, Sierra Leone, Singapore, Slovakia, Slovenia, the Solomon Islands, Somalia, South Africa, South Korea, Spain, Sri Lanka, St. Kitts & Nevis, St. Lucia, St. Vincent & Grenada, Suriname, Swaziland, Sweden, Switzerland, Taiwan, Tajikistan, Tanzania, Thailand, Togo, Tonga, Trinidad & Tobago, Tunisia, Turkey, Turkmenistan, Tuvalu, Uganda, Ukraine, the United Arab Emirates, the United Kingdom, Uruguay, Uzbekistan, Vanuatu, Venezuela, Vietnam, Yemen, Zaire, Zambia, and Zimbabwe

• For use in Japan 441090-291
802.11b/g Intel WLAN module for use in Thailand 448675-004


Before removing the WLAN module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- Remove the memory module/WLAN module compartment cover (see <u>Memory module</u> on page 45).


Remove the WLAN module:

- 1. Disconnect the WLAN antenna cables (1) and (2) from the terminals on the WLAN module.
 - NOTE: The WLAN antenna cable labeled (1) is connected to the WLAN module "Main" terminal. The WLAN antenna cable labeled (2) is connected to the WLAN module "Aux" terminal. To easily identify the correct cable locations, matching numbers are displayed on the modules next to the antenna connectors.

2. Remove the two Phillips PM2.0×3.0 screws (3) that secure the WLAN module to the computer. (The edge of the module opposite the slot rises away from the computer.)



- 3. Remove the WLAN module (1) by pulling the module away from the slot at an angle.
- NOTE: WLAN modules are designed with a notch (2) to prevent incorrect installation.



Reverse this procedure to install the WLAN module.

Hard drive


Description	Spare part number
100-GB, 4200-rpm hard drive	453504-001
80-GB, 4200-rpm hard drive	451730-001
60-GB, 4200-rpm hard drive	451729-001

Before disassembling the computer, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).


Remove the hard drive:

- 1. Loosen the two Phillips PM2.0×5.0 captive screws (1) that secure the hard drive cover to the computer.
- 2. Lift the front edge of the hard drive cover (2), swing it up and back, and remove the cover. The hard drive cover is included in the Plastics Kit, spare part number 451743-001.




3. Loosen the two Phillips PM2.0×5.0 captive screws (1) that secure the hard drive bracket to the computer.

4. Remove the hard drive bracket (2).



- 5. Loosen the two Phillips PM2.0×5.0 captive screws (1) that secure the hard drive connector to the system board.
- 6. Disconnect the hard drive connector (2) from the system board.
- 7. Lift the hard drive (3) straight up to remove it from the hard drive.



Reverse this procedure to install the hard drive.

WWAN module

△ CAUTION: The WWAN module and the WLAN module are not interchangeable.


Description	Spare part number
Verizon EVDO-A WWAN module	451131-001
Cingular HSPDA WWAN module	448673-002
Vodafone HSPDA WWAN module	448672-002

Before removing the WWAN module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see Battery on page 41).
- Remove the SIM (see <u>SIM on page 42</u>).


Remove the WWAN module:

- 1. Position the computer with the front toward you.
- Loosen the Phillips PM2.0×5.0 captive screw (1) that secures the WWAN module compartment cover to the computer.
- 3. Lift the left side of the WWAN module compartment cover (2), swing it up and to the right, and remove the cover. The WWAN module compartment cover is included in the Plastics Kit, spare part number 451743-001.




- Disconnect the WWAN antenna cables (1) from the terminals on the WWAN module.
- NOTE: The red WWAN antenna cable is connected to the WWAN module "Main" terminal. The blue WWAN antenna cable is connected to the WWAN module "Aux" terminal.

5. Remove the two Phillips PM2.5×4.0 screws **(2)** that secure the WWAN module to the computer. (The edge of the module opposite the slot rises away from the computer.)



- 6. Remove the WWAN module (1) by pulling the module away from the slot at an angle.
 - NOTE: WWAN modules are designed with a notch (2) to prevent incorrect installation.



Reverse this procedure to install the WWAN module.

Optical drive


Description	Spare part number
DVD±RW and CD-RW Super Multi Double-Layer Combo Drive	451727-001
DVD/CD-RW Combo Drive	451725-001
DVD-ROM Drive	451726-001

Before removing the optical drive, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).


Remove the optical drive:

- 1. Position the computer with the right side toward you.
- 2. Remove the Torx T8M2.5×7.0 screw (1) that secures the optical drive to the computer.
- 3. If present, remove the Torx T8M2.5×4.0 security screw (2) that secures the optical drive to the computer.
- 4. Insert a thin tool, such as a paper clip (3), into the disc tray release access. (The optical drive disc tray is partially ejected from the optical drive.)
- 5. Use the disc tray frame to slide the optical drive (4) out of the computer.



6. If it is necessary to replace the optical drive bracket, position the optical drive with the optical drive bracket toward you.

- Remove the two Phillips PM2.0×3.0 screws (1) that secure the optical drive bracket to the optical drive.
- 8. Remove the optical drive bracket (2).



Reverse this procedure to reassemble and install the optical drive.

Switch cover

Description	Spare part number
Switch cover (includes LED board and cable)	451717-001

Before removing the switch cover, follow these steps:

- Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).


Remove the switch cover:

- 1. Turn the computer right-side up, with the front toward you.
- 2. Open the computer as far as possible.

3. Release the switch cover by lifting and swinging the hinge cover sections up and forward until the switch cover rests upside down on the keyboard.



4. Release the zero insertion force (ZIF) connector **(1)** to which the LED board cable is attached, and disconnect the LED board cable **(2)** from the connector.



5. Remove the switch cover.

Reverse this procedure to install the switch cover.

Keyboard

For use in:	Spare part number	For use in:	Spare part number
Belgium	451748-A41	The Netherlands and Europe	451748-021
Brazil	451748-201	Norway	451748-091
The Czech Republic	451748-221	Portugal	451748-131
Denmark	451748-081	Russia	451748-251
France	451748-051	Saudi Arabia	451748-171
French Canada	451748-121	Slovakia	451748-231
Germany	451748-041	Slovenia	451748-BA1
Greece	451748-151	Spain	451748-071
Hungary	451748-211	Sweden and Finland	451748-B71
Iceland	451748-DD1	Switzerland	451748-111
Israel	451748-BB1	Taiwan	451748-AB1
Italy	451748-061	Thailand	451748-281
Japan	451748-291	Turkey	451748-141
South Korea	451748-AD1	The United Kingdom	451748-031
Latin America	451748-161	The United States	451748-001


Before removing the keyboard, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the switch cover (see Switch cover on page 57).


Remove the keyboard:

1. Turn the computer upside down, with the front toward you.

2. Remove the six Torx T8M2.5×7.0 screws that secure the keyboard to the computer.




- 3. Turn the computer display-side up, with the front toward you.
- 4. Open the computer as far as possible.
- 5. Lift the rear edge of the keyboard (1) and slide it back until the keyboard cable (2) and pointing stick cable (3) are accessible.




6. Release the ZIF connector (1) to which the keyboard cable is attached, and disconnect the keyboard cable (2) from the system board.

7. Release the ZIF connector (3) to which the pointing stick cable is attached, and disconnect the pointing stick cable (4) from the system board.



- 8. Remove the keyboard.
- 9. If it is necessary to replace the LED board cable, turn the keyboard upside down, with the bottom of the keyboard toward you.
- 10. If it is necessary to replace the LED board cable, disconnect the cable (1) from the low insertion force (LIF) connector (2) to which it is attached, and remove the LED board cable (3). The LED board cable is included in the Cable Kit, spare part number 451722-001.



Reverse this procedure to install the keyboard.

Display assembly


Description	Spare part number
12.1-inch, WXGA display assembly with AntiGlare (includes wireless antenna transceivers and cables and microphone and cable)	451741-001

Before removing the display assembly, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- 5. Disconnect the wireless antenna cables from the WLAN module (see <u>WLAN module</u> on page 48) and the WWAN module (see <u>WWAN module</u> on page 54).
- **6.** Remove the following components:
 - a. Switch cover (see Switch cover on page 57)
 - **b.** Keyboard (see Keyboard on page 59)


Remove the display assembly:

- 1. Position the computer with the rear panel toward you and the display in an upright position.
- 2. Remove the two Torx T8M2.5×7.0 screws that secure the display assembly to the computer.




- 3. Position the computer with the front toward you.
- **4.** Remove the WWAN antenna cables **(1)** from the routing channel and clips built into the top cover.
- 5. Disconnect the display panel cable (2) from the system board.

- 6. Remove the WLAN antenna cables (3) from the routing channel and clips built into the top cover.
- 7. Disconnect the microphone cable (4) from the microphone pass-through cable.




- 8. Disconnect the display lid switch module cable (1) from the system board.
- 9. Remove the two Torx T8M2.5×7.0 screws (2) that secure the display assembly to the computer.
- 10. Lift the display assembly straight up and remove it (3).




- 11. If it is necessary to replace the display lid switch module, remove the Phillips PM1.5×3.0 screw (1) that secures the module to the display assembly left hinge.
- **12.** Rotate the module **(2)** ½-turn counterclockwise.

13. Remove the display lid switch module **(3)**. The display lid switch module is available using spare part number 451724-001.




14. If it is necessary to replace the display bezel or any of the display assembly internal components, remove the five rubber screw covers (1) and the five Torx T7M2.0×5.0 screws (2) that secure the display bezel to the display assembly.




15. Flex the inside edges of the left and right sides **(1)** and the top and bottom sides **(2)** of the display bezel until the bezel disengages from the display enclosure.

16. Remove the display bezel **(3)**. The display bezel is available using spare part number 451733-001.




- 17. If it is necessary to replace the display hinges, remove the four Torx T7M2.0×5.0 screws (1) that secure the display panel to the display enclosure.
- 18. Remove the display panel (2).



19. Remove the two Phillips PM2.0×4.0 screws (1) that secure each display hinge to the display panel.

20. Remove the display hinges **(2)**. The left and right display hinges are available using spare part number 451734-001.



Reverse this procedure to reassemble and install the display assembly.

Top cover

Description	Spare part number
Top cover (includes TouchPad, TouchPad cable, and fingerprint reader board)	451723-001
NOTE: The fingerprint reader board cable is included in the Cable Kit, spare part number 451722-001.	

Before removing the top cover, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the following components:
 - a. Hard drive (see Hard drive on page 52)
 - **b.** Optical drive (see Optical drive on page 56)
 - c. Switch cover (see Switch cover on page 57)
 - d. Keyboard (see Keyboard on page 59)
 - e. Display assembly (see <u>Display assembly on page 62</u>)

Remove the top cover:


1. Turn the computer upside down, with the front toward you.

Remove the following:

- (1) Four base enclosure rubber screw covers. The base enclosure rubber screw covers are included in the Rubber Kit, spare part number 451744-001.
- (2) Five Torx T8M2.5×4.0 screws.
- (3) Three Torx T8M2.5×7.0 screw.




- 3. Turn the computer right-side up, with the front toward you.
- 4. Remove the three Torx T8M2.5×7.0 screws that secure the top cover to the computer.



5. Lift the rear edge of the top cover and swing it up and forward until the top cover rests upside down in front of the base enclosure.



6. Release the ZIF connector (1) to which the fingerprint reader board cable is connected and disconnect the fingerprint reader board cable (2) from the system board.



Remove the top cover.

Reverse this procedure to install the top cover.

System board

Description	Spare part number
Equipped with Intel Core Duo U7700 (1.33-GHz) processor (533-MHz FSB and 2-MB L2 cache)	464764-001
Equipped with Intel Core Duo U7600 (1.20-GHz) processor (533-MHz FSB and 2-MB L2 cache)	451720-001
Equipped with Intel Core Duo U7500 (1.06-GHz) processor (533-MHz FSB and 2-MB L2 cache)	451719-001

Before removing the system board, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the following components:
 - a. Hard drive (see Hard drive on page 52)
 - **b.** Optical drive (see Optical drive on page 56)
 - **c.** Switch cover (see Switch cover on page 57)
 - d. Keyboard (see Keyboard on page 59)
 - e. Display assembly (see Display assembly on page 62)
 - **f.** Top cover (see Top cover on page 67)


When replacing the system board, be sure that the following components are removed from the defective system board and installed on the replacement system board:

- SIM (see <u>SIM on page 42</u>)
- Memory module (see <u>Memory module on page 45</u>)
- RTC battery (see <u>RTC battery on page 47</u>)
- WLAN module (see WLAN module on page 48)
- WWAN module (see <u>WWAN module on page 54</u>)
- Fan/heat sink assembly (see <u>Fan/heat sink assembly on page 74</u>)
- PC Card assembly (see <u>PC Card assembly on page 76</u>)
- Modem module (see <u>Modem module on page 78</u>)


Remove the system board:

1. Turn the computer upside down, with the rear panel toward you.


Disconnect the fan cable from the system board.




- Turn the computer right-side up, with the front toward you.
- Press the PC Card eject button (1) twice. The first press releases the PC Card eject button from 4. the PC Card slot. The second press releases the PC Card slot bezel from the PC Card slot. (The PC Card slot bezel is partially ejected from the PC Card slot.) The PC Card slot bezel is included in the Plastics Kit, spare part number 451743-001.
- **5**. Remove the PC Card slot bezel (2).




6. Disconnect the front LED board cable (1) and the speaker cable (2) from the system board.



7. Remove the three Torx T8M2.5×7.0 screws (1) and the two Phillips PM2.0×10.0 screws (2) that secure the system board to the base enclosure.



- 8. Use the optical drive connector (1) to lift the left side of the system board (2) until it rests at an angle.
- 9. Remove the system board (3) by sliding it away from the base enclosure at an angle.



Reverse the preceding procedure to install the system board.

Speaker assembly


Description	Spare part number
Speaker assembly	451747-001

Before removing the speaker assembly, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the following components:
 - a. Hard drive (see Hard drive on page 52)
 - **b.** Optical drive (see Optical drive on page 56)
 - **c.** Switch cover (see Switch cover on page 57)
 - **d.** Keyboard (see <u>Keyboard on page 59</u>)
 - e. Display assembly (see <u>Display assembly on page 62</u>)
 - **f.** Top cover (see Top cover on page 67)
 - **g.** System board (see System board on page 70)

Remove the speaker assembly:

 Remove the Torx T8M2.5×4.0 screw (1) that secures the speaker assembly to the base enclosure. 2. Remove the speaker assembly (2) from the base enclosure.



Reverse this procedure to install the speaker assembly.

Fan/heat sink assembly

NOTE: All fan/heat sink assembly spare part kits include thermal material.


Description	Spare part number
Fan/heat sink assembly	451731-001

Before removing the fan/heat sink assembly, follow these steps:


- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- 2. Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- **4.** Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the following components:
 - a. Hard drive (see <u>Hard drive on page 52</u>)
 - **b.** Optical drive (see Optical drive on page 56)
 - c. Switch cover (see <u>Switch cover on page 57</u>)
 - **d.** Keyboard (see <u>Keyboard on page 59</u>)
 - e. Display assembly (see <u>Display assembly on page 62</u>)
 - f. Top cover (see Top cover on page 67)
 - **g.** System board (see System board on page 70)

Remove the fan/heat sink assembly:

- Remove the two Torx T8M2.5×4.0 screws (1) that secure the fan/heat sink assembly to the base enclosure.
- 2. Remove the fan/heat sink assembly (2) from the base enclosure.



NOTE: The thermal material must be thoroughly cleaned from the surfaces of the heat sink (1) and (3), the processor (2), and graphics system component (4) each time the heat sink is removed. Thermal material is included with all heat sink and processor spare part kits.



Reverse this procedure to install the fan/heat sink assembly.

NOTE: To properly ventilate the computer, allow at least a 7.6-cm (3-inch) clearance on the left and right sides of the computer.

The computer uses an electric fan for ventilation. The fan is controlled by a temperature sensor and is designed to turn on automatically when high temperature conditions exist. These conditions are affected by high external temperatures, system power consumption, power management/battery conservation configurations, battery fast charging, and software requirements. Exhaust air is displaced through the ventilation grill located on the left side of the computer.

PC Card assembly


Description	Spare part number
PC Card assembly	451742-001

Before removing the PC Card assembly, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see <u>Battery on page 41</u>).
- 5. Remove the following components:
 - **a.** Hard drive (see <u>Hard drive on page 52</u>)
 - **b.** Optical drive (see Optical drive on page 56)
 - c. Switch cover (see Switch cover on page 57)
 - **d.** Keyboard (see <u>Keyboard on page 59</u>)
 - e. Display assembly (see <u>Display assembly on page 62</u>)
 - **f.** Top cover (see <u>Top cover on page 67</u>)
 - g. System board (see System board on page 70)

Remove the PC Card assembly:

- 1. Turn the system board upside down, with the front toward you.
- 2. Detach the slots on the PC Card assembly (1) from the tabs on the PC Card connector (2).
- **3.** Remove the PC Card assembly **(3)**.



Reverse this procedure to install the PC Card assembly.

Modem module

NOTE: All modem module spare part kits include a modem module cable.

Description	Spare part number
For use in all countries and regions except Australia and New Zealand	443899-001
For use only in Australia and New Zealand	443899-011


Before removing the modem module, follow these steps:

- 1. Shut down the computer. If you are unsure whether the computer is off or in Hibernation, turn the computer on, and then shut it down through the operating system.
- Disconnect all external devices connected to the computer.
- 3. Disconnect the power from the computer by first unplugging the power cord from the AC outlet and then unplugging the AC adapter from the computer.
- 4. Remove the battery (see Battery on page 41).
- 5. Remove the following components:
 - **a.** Hard drive (see <u>Hard drive on page 52</u>)
 - **b.** Optical drive (see Optical drive on page 56)
 - c. Switch cover (see Switch cover on page 57)
 - **d.** Keyboard (see Keyboard on page 59)
 - e. Display assembly (see <u>Display assembly on page 62</u>)
 - **f.** Top cover (see Top cover on page 67)
 - **g.** System board (see System board on page 70)

Remove the modem module:

- 1. Turn the system board upside down, with the front toward you.
- 2. Remove the two Phillips PM2.5×4.0 screws (1) that secure the modern module to the system board.
- 3. Disconnect the modem module (2) from the system board by lifting it straight up.

Disconnect the modem module cable (3) from the system board.



Reverse this procedure to install the modem module.

5 Computer Setup

Starting Computer Setup

Computer Setup is a preinstalled, ROM-based utility that can be used even when the operating system is not working or will not load.

NOTE: Some of the Computer Setup menu items listed in this guide may not be supported by your computer.

NOTE: Pointing devices are not supported in Computer Setup. You must use the keyboard to navigate and make selections.

NOTE: An external keyboard connected by USB can be used with Computer Setup only if USB legacy support is enabled.

To start Computer Setup, follow these steps:

- 1. Turn on or restart the computer.
- 2. Before Windows® opens and while the "F10 = ROM Based Setup" message is displayed in the lower-left corner of the screen, press f10.

Using Computer Setup

Navigating and selecting in Computer Setup

The information and settings in Computer Setup are accessed from the File, Security, Diagnostics, and System Configuration menus.

1. Open Computer Setup by turning on or restarting the computer, and then pressing f10 while the "F10 = ROM Based Setup" message is displayed in the lower-left corner of the screen.

Because Computer Setup is not Windows-based, it does not support the TouchPad. Navigation and selection are by keystroke:

- To choose a menu or a menu item, use the arrow keys.
- To select an item, press enter.
- To close open dialog boxes and return to the main Computer Setup screen, press esc.
- To view navigation information, press f1.
- To change the language, press f2.
- 2. Select the File, Security, Diagnostics, or System Configuration menu.
- 3. To exit Computer Setup, choose one of the following methods:
 - To exit Computer Setup without saving your preferences, use the arrow keys to select File
 Ignore Changes and Exit. Then follow the instructions on the screen.
 - To save your preferences and exit Computer Setup, use the arrow keys to select File > Save Changes and Exit. Then follow the instructions on the screen.

Your preferences go into effect when the computer restarts.

Restoring factory settings in Computer Setup

To return all settings in Computer Setup to the values that were set at the factory, follow these steps:

- 1. Open Computer Setup by turning on or restarting the computer, and then pressing f10 while the "F10 = ROM Based Setup" message is displayed in the lower-left corner of the screen.
- 2. Use the arrow keys to select **File > Restore** defaults, and then press enter.
- 3. When the confirmation dialog box opens, press f10.
- 4. To save your preferences and exit Computer Setup, use the arrow keys to select File > Save Changes and Exit. Then follow the instructions on the screen.

Your preferences go into effect when the computer restarts.

NOTE: Your password settings and security settings are not changed when you restore the factory settings.

Computer Setup menus

The menu tables in this section provide an overview of Computer Setup options.

NOTE: Some of the Computer Setup menu items listed in this chapter may not be supported by your computer.

File menu

Select	To do this
System information	 View identification information for the computer and the batteries in the system.
	 View specification information for the processor, cache and memory size, system ROM, video revision, and keyboard controller version.
Restore defaults	Replace the configuration settings in Computer Setup with the original factory settings. (Password settings and security settings are not changed when you restore the factory settings.)
Ignore changes and exit	Cancel any changes entered during the current session. Then exit and restart the computer.
Save changes and exit	Save any changes entered during the current session. Then exit and restart the computer. Your changes go into effect when the computer restarts.

Security menu

Select	To do this
Setup password	Enter, change, or delete a setup password.
Power-On password	Enter, change, or delete a power-on password.
Password options	Enable/disable stringent security.
	 Enable/disable password requirement on computer restart.
DriveLock passwords	 Enable/disable DriveLock on any computer hard drive and on optional MultiBay hard drives.
	 Change a DriveLock user password or master password.
	NOTE: DriveLock settings are accessible only when you enter Computer Setup by turning on (not restarting) the computer.
Smart Card security	Enable/disable support for smart card and Java™ Card power-on authentication.
	NOTE: Power-on authentication for smart cards is supported only on computers with optional smart card readers.
	NOTE: You must have an administrator password to change this setting.
TPM Embedded Security	Enable/disable support for Trusted Platform Module (TPM) Embedded Security, which protects the computer from unauthorized access to owner functions available in Embedded Security for ProtectTools. For more information, refer to the ProtectTools software Help.
	NOTE: You must have a setup password to change this setting.
System IDs	Enter user-defined computer asset tracking number and ownership tag.
Disk Sanitizer	Run Disk Sanitizer to destroy all existing data on the primary hard drive. The following options are available:
	Fast: Runs the Disk Sanitizer erase cycle once.
	Optimum: Runs the Disk Sanitizer erase cycle 3 times.
	 Custom: Allows you to select the desired number of Disk Sanitizer erase cycles from a list.
	CAUTION: If you run Disk Sanitizer, the data on the primary hard drive is destroyed permanently.

Diagnostics menu

Select	To do this
Hard Drive Self-Test options	Run a comprehensive self-test on any hard drive in the system or on any optional MultiBay hard drive.
Memory Check	Run a comprehensive check on system memory.
Startup Check (select models only)	Verify the system components needed for starting the computer.

System Configuration menu

NOTE: Some of the listed System Configuration options may not be supported by your computer.

Select	To do this
Language (or press f2)	Change the Computer Setup language.
Boot options	Set f9, f10, and f12 delay when starting up.
	Enable/disable CD-ROM boot.
	Enable/disable floppy boot.
	 Enable/disable internal network adapter boot and set the boot mode (PXE or RPL).
	 Enable/disable MultiBoot, which sets a boot order that can include most boot devices in the system.
	 Set the Express Boot Popup delay in seconds.
	Set the boot order.
Device configurations	 Swap the functions of the fn key and left ctrl key.
	 Enable/disable multiple standard pointing devices at startup. (To set the computer to support only a single, usually nonstandard, pointing device a startup, select Disable.)
	 Enable/disable USB legacy support. When enabled, USB legacy support allows the following:
	 Use of a USB keyboard, mouse, and hub in Computer Setup even when a Windows operating system is not running.
	 Startup from bootable USB devices, including a hard drive, diskette drive, or optical drive connected by a USB port to the computer or to an optional docking device (select models only).
	 Select a parallel port mode: EPP (Enhanced Parallel Port), standard, bidirectional, or ECP (Enhanced Capabilities Port).
	 Enable/disable BIOS DMA data transfers.
	 Enable/disable fan always on while connected to an AC outlet.
	 Enable/disable Intel® Data Execution Prevention or AMD® PSAE Execution Disable. When enabled, the processor can disable some virus code execution, which helps to improve computer security.
	 Enable/disable LAN Power Save. When enabled, saves power by turning off the LAN when not in use.
	Enable/disable SATA Native Mode.
	Enable/disable Dual Core CPU.
	Enable/disable Secondary Battery Fast Charge.
	Choose Bit-shift or LBA assisted HDD Translation Mode.
	Enable/disable Windows direct application launcher.
	Enable/disable HP Lockout.

Select	To do this
Built-In Device Options	Enable/disable embedded WWAN Device Radio.
	Enable/disable embedded WLAN Device Radio.
	Enable/disable embedded Bluetooth® Device Radio.
	 Enable/disable LAN/WLAN Switching. When enabled, switches to a WLAN when a LAN is either unavailable or disconnected.
	Enable/disable Wake on LAN from Off.
	Enable/disable the ambient light sensor.
Port Options	Enable/disable the serial port.
	Enable/disable the parallel port.
	Enable/disable the flash media reader.
	Enable/disable the USB port.
	CAUTION: Disabling the USB port also disables MultiBay devices and ExpressCard devices on the advanced port replicator.
	Enable/disable the 1394 port.
	Enable/disable the cardbus slot.
	Enable/disable the ExpressCard slot.
	Enable/disable the infrared port.
	Enable/disable the optical disk drive.
	Enable/disable the network controller.

6 Specifications

Computer specifications

	Metric	U.S.
Dimensions		:
Depth	21.29 cm	8.38 in
Width	28.22 cm	11.11 in
Height (front to rear)	2.46 to 3.20 cm	0.97 to 1.26 in
Weight (varies by configuration)		
Equipped with optical drive, 9-cell battery, and WLAN module	1.77 kg	3.9 lbs
Equipped with optical drive, 6-cell battery, and WLAN module	1.63	3.6 lbs
Equipped with optical drive, 3-cell battery, and WLAN module	1.45	3.2 lbs
Equipped with 3-cell battery and WLAN module	1.27	2.8 lbs
Input power		
Operating voltage	19.0 V dc @ 4.74 A - 90 W	
Operating current	4.74 A	
Temperature		
Operating (not writing to optical disc)	0°C to 35°C	32°F to 95°F
Operating (writing to optical disc)	5°C to 35°C	41°F to 95°F
Nonoperating	-20°C to 60°C	-4°F to 140°F
Relative humidity		
Operating	10% to 90%	
Nonoperating	5% to 95%	
Maximum altitude (unpressurized)		
Operating (14.7 to 10.1 psia)	-15 m to 3,048 m	-50 ft to 10,000 ft
Nonoperating (14.7 to 4.4 psia)	-15 m to 12,192 m	-50 ft to 40,000 ft
Shock		

	Metric	U.S.
Operating	125 g, 2 ms, half-sine	
Nonoperating	200 g, 2 ms, half-sine	
Random vibration		
Operating	0.75 g zero-to-peak, 10	Hz to 500 Hz, 0.25 oct/min sweep rate
Nonoperating	1.50 g zero-to-peak, 10	Hz to 500 Hz, 0.5 oct/min sweep rate

12.1-inch, WXGA display specifications

	Metric	U.S.
Dimensions		
Height	16.9 cm	6.7 in
Width	26.2 cm	10.3 in
Diagonal	30.8 cm	12.1 in
Number of colors	Up to 16.8 million	
Contrast ratio	250:1 (typical)	
Brightness	180 nits (typical)	
Pixel resolution		
Pitch	0.279 × 0.279 mm	
Format	1280 × 800	
Configuration	RGB vertical stripe	
Backlight	Edge lit	
Character display	80 × 25	
Total power consumption	4.0 W	
Viewing angle	+/-40 horizontal, +120/-40° vertical (typical)	

Hard drive specifications

	100-GB*	80-GB*	60-GB*
Dimensions			
Height	9.5 mm	9.5 mm	9.5 mm
Width	70 mm	70 mm	70 mm
Weight	101 g	101 g	101 g
Interface type	SATA	SATA	SATA
Transfer rate	100 MB/sec	100 MB/sec	100 MB/sec
Security	ATA security	ATA security	ATA security
Seek times (typical read, including setting)			
Single track	3 ms	3 ms	3 ms
Average	13 ms	13 ms	13 ms
Maximum	24 ms	24 ms	24 ms
Logical blocks	195,350,400	156,280,320	117,210,240
Disc rotational speed	4200 rpm	4200 rpm	4200 rpm
Operating temperature	5°C to 55°C (41°F to 131°F)		

^{*1} GB = 1 billion bytes when referring to hard drive storage capacity. Actual accessible capacity is less. Actual drive specifications may differ slightly.

NOTE: Certain restrictions and exclusions apply. Contact technical support for details.

DVD±RW and **CD-RW** Double-Layer Combo Drive specifications

Applicable disc	Read:	Write:
	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-	CD-R and CD-RW
	ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD-RAM	DVD+R, DVD+RW, DVD-R, DVD- RW, DVD-RAM
Center hole diameter	1.5 cm (0.59 in)	
Disc diameter		
Standard disc	12 cm (4.72 in)	
Mini disc	8 cm (3.15 in)	
Disc thickness	1.2 mm (0.047 in)	
Track pitch	0.74 μm	
Access time	CD	DVD
Random	< 175 ms	< 230 ms
Full stroke	< 285 ms	< 335 ms
Audio output level	Line-out, 0.7 Vrms	
Cache buffer	2 MB	
Data transfer rate		
24X CD-ROM	3,600 KB/sec	
8X DVD-ROM	10,800 KB/sec	
24X CD-R	3,600 KB/sec	
16X CD-RW	2,400 KB/sec	
8X DVD+R	10,800 KB/sec	
4X DVD+RW	5,400 KB/sec	
8X DVD-R	10,800 KB/sec	
4X DVD-RW	5,400 KB/sec	
2.4X DVD+R(9)	2,700 KB/sec	
5X DVD-RAM	6,750 KB/sec	
Transfer mode	Multiword DMA Mode	
Startup time	< 15 seconds	
Stop time	< 6 seconds	

DVD/CD-RW Combo Drive specifications

Applicable disc	Read:	Write:
	CD-DA, CD+(E)G, CD-MIDI, CD-TEXT, CD-ROM, CD-ROM XA, MIXED MODE CD, CD-I, CD-I Bridge (Photo-CD, Video CD), Multisession CD (Photo-CD, CD-EXTRA, Portfolio, CD-R, CD-RW), CD-R, CD-RW, DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18), DVD-R, DVD-RW, DVD-RW, DVD-RAM	CD-R and CD-RW
Center hole diameter	1.5 cm (0.59 in)	
Disc diameter		
Standard disc	12 cm (4.72 in)	
Mini disc	8 cm (3.15 in)	
Disc thickness	1.2 mm (0.047 in)	
Track pitch	0.74 µm	
Access time	CD	DVD
Random	< 110 ms	< 130 ms
Full stroke	< 210 ms	< 225 ms
Audio output level	Line-out, 0.7 Vrms	
Cache buffer	2 MB	
Data transfer rate		
24X CD-ROM	3,600 KB/sec	
8X DVD	3,600 KB/sec	
24X CD-R	3,600 KB/sec	
24X CD-RW	3,600 KB/sec	
Transfer mode	Multiword DMA mode 2	
Startup time	< 15 seconds	
Stop time	< 6 seconds	

DVD-ROM Drive

Applicable disc	DVD-ROM (DVD-5, DVD-9, DVD-10, DVD-18, CD-ROM (Mode 1 and 2), CD Digital Audio, CD-XA ready (Mode 2, Form 1 and Form 2), CD-I (Mode 2, Form 1 and Form 2), CD-R, CD-RW, Photo CD (single and multisession), CD-Bridge			
Center hole diameter	1.5 cm (0.59 in)	1.5 cm (0.59 in)		
Disc diameter				
Standard disc	12 cm (4.72 in)			
Mini disc	8 cm (3.15 in)			
Disc thickness	1.2 mm (0.047 in)	1.2 mm (0.047 in)		
Track pitch	0.74 µm			
Access time	CD	DVD		
Random	< 100 ms	< 125 ms		
Full stroke	< 175 ms	< 225 ms		
Audio output level	Line-out, 0.7 Vrms			
Cache buffer	512 KB			
Data transfer rate				
CD-R (24X)	3600 KB/s (150 KB/s at 1X CD rate)			
CD-RW (10X)	1500 KB/s (150 KB/s at 1X CD rate)	1500 KB/s (150 KB/s at 1X CD rate)		
CD-ROM (24X)	3600 KB/s (150 KB/s at 1X CD rate)	3600 KB/s (150 KB/s at 1X CD rate)		
DVD (8X)	10,800 KB/s (1,352 KB/s at 1X DVD rate)			
Multiword DMA mode 2	16.6 MB/s	16.6 MB/s		
Startup time	< 10 seconds	< 10 seconds		
Stop time	< 3 seconds			

System DMA specifications

Hardware DMA	System function	
DMA0	Not applicable	
DMA1*	Not applicable	
DMA2*	Not applicable	
DMA3	Not applicable	
DMA4	Direct memory access controller	
DMA5*	Available for PC Card	
DMA6	Not assigned	
DMA7	Not assigned	
*PC Card controller can use DMA 1, 2, or 5.		

System interrupt specifications

Hardware IRQ	System function
IRQ0	System timer
IRQ1	Standard 101-/102-Key or Microsoft® Natural Keyboard
IRQ2	Cascaded
IRQ3	Intel 82801DB/DBM USB2 Enhanced Host Controller—24CD
IRQ4	COM1
IRQ5*	Conexant AC—Link Audio Intel 82801DB/DBM SMBus Controller—24C3 Data Fax Modem with SmartCP
IRQ6	Diskette drive
IRQ7*	Parallel port
IRQ8	System CMOS/real-time clock
IRQ9*	Microsoft ACPI-compliant system
IRQ10*	Intel USB UHCI controller—24C2
	Intel 82852/82855 GM/GME Graphic Controller
	Realtek RTL8139 Family PCI Fast Ethernet Controller
IRQ11	Intel USB EHCI controller—24CD
	Intel USB UHCI controller—24C4
	Intel USB UHCI controller—24C7
	Intel Pro/Wireless 2200BG
	TI OHCI 1394 host controller
	TI PCI1410 CardBus controller
IRQ12	Synaptics PS/2 TouchPad
IRQ13	Numeric data processor
	Primary IDE channel
IRQ14	Timary IDE Gramer

NOTE: PC Cards may assert IRQ3, IRQ4, IRQ5, IRQ7, IRQ9, IRQ10, IRQ11, or IRQ15. Either the infrared or the serial port may assert IRQ3 or IRQ4.

System I/O address specifications

I/O address (hex)	System function (shipping configuration)	
000 - 00F	DMA controller no. 1	
010 - 01F	Unused	
020 - 021	Interrupt controller no. 1	
022 - 024	Opti chipset configuration registers	
025 - 03F	Unused	
02E - 02F	87334 "Super I/O" configuration for CPU	
040 - 05F	Counter/timer registers	
044 - 05F	Unused	
060	Keyboard controller	
061	Port B	
062 - 063	Unused	
064	Keyboard controller	
065 - 06F	Unused	
070 - 071	NMI enable/RTC	
072 - 07F	Unused	
080 - 08F	DMA page registers	
090 - 091	Unused	
092	Port A	
093 - 09F	Unused	
0A0 - 0A1	Interrupt controller no. 2	
I/O Address (hex)	System Function (shipping configuration)	
0A2 - 0BF	Unused	
0C0 - 0DF	DMA controller no. 2	
0E0 - 0EF	Unused	
0F0 - 0F1	Coprocessor busy clear/reset	
0F2 - 0FF	Unused	
100 - 16F	Unused	
170 - 177	Secondary fixed disk controller	
178 - 1EF	Unused	
1F0 - 1F7	Primary fixed disk controller	
1F8 - 200	Unused	
201	JoyStick (decoded in ESS1688)	
202 - 21F	Unused	

I/O address (hex)	System function (shipping configuration)
220 - 22F	Entertainment audio
230 - 26D	Unused
26E - 26	Unused
278 - 27F	Unused
280 - 2AB	Unused
2A0 - 2A7	Unused
2A8 - 2E7	Unused
2E8 - 2EF	Reserved serial port
2F0 - 2F7	Unused
2F8 - 2FF	Infrared port
300 - 31F	Unused
320 - 36F	Unused
370 - 377	Secondary diskette drive controller
378 - 37F	Parallel port (LPT1/default)
380 - 387	Unused
388 - 38B	FM synthesizer—OPL3
38C - 3AF	Unused
3B0 - 3BB	VGA
3BC - 3BF	Reserved (parallel port/no EPP support)
3C0 - 3DF	VGA
3E0 - 3E1	PC Card controller in CPU
3E2 - 3E3	Unused
3E8 - 3EF	Internal modem
3F0 - 3F7	"A" diskette controller
3F8 - 3FF	Serial port (COM1/default)
CF8 - CFB	PCI configuration index register (PCIDIVO-1)
CFC - CFF	PCI configuration data register (PCIDIVO-1)


System memory map specifications

Size	Memory address	System function
640 KB	00000000-0009FFFF	Base memory
128 KB	000A0000-000BFFFF	Video memory
48 KB	000C0000-000CBFFF	Video BIOS
160 KB	000C8000-000E7FFF	Unused
64 KB	000E8000-000FFFFF	System BIOS
15 MB	00100000-00FFFFF	Extended memory
58 MB	04800000-07FFFFFF	Super extended memory
58 MB	04800000-07FFFFFF	Unused
2 MB	08000000-080FFFFF	Video memory (direct access)
4 GB	08200000-FFFEFFFF	Unused
64 KB	FFFF0000-FFFFFFF	System BIOS


Screw listing

This section provides specification and reference information for the screws and screw locks used in the computer. All screws listed in this section are available in the Screw Kit, spare part number 451745-001, and the Display Screw Kit, spare part number 451737-001.

Phillips PM2.0×5.0 captive screw




Color	Quantity	Length	Thread	Head diameter
Black	8	5.0 mm	2.0 mm	4.5 mm




Where used:

- (1) One screw that secures the Bluetooth module compartment cover to the computer (screw is captured on the cover by a C-clip)
- (2) Two screws that secure the memory module/WLAN module compartment cover to the computer (screws are captured on the cover by C-clips)
- (3) Two screws that secure the hard drive cover to the computer (screws are captured on the cover by C-clips)
- **(4)** One screw that secures the WWAN module compartment cover to the computer (screw is captured on the cover by a C-clip)




Where used: 2 captive screws that secure the hard drive bracket to the computer (screws are captured on the bracket by C-clips)

Phillips PM2.0×5.0 screw




Color	Quantity	Length	Thread	Head diameter
Black	1	5.0 mm	2.0 mm	4.5 mm




Where used: One screw that secures the Bluetooth module to the Bluetooth module compartment cover

Phillips PM2.5×4.0 screw




Color	Quantity	Length	Thread	Head diameter
Black	6	4.0 mm	2.5 mm	5.0 mm




Where used:

- (1) Two screws that secure the WLAN module to the system board
- (2) Two screws that secure the WWAN module to the system board




Where used: 2 screws that secure the modem module to the system board

Torx T8M2.5×7.0 screw



Color	Quantity	Length	Thread	Head diameter
Black	20	7.0 mm	2.5 mm	5.0 mm




Where used:


- (1) One screw that secures the optical drive to the computer
- (2) Six screws that secure the keyboard to the computer




Where used: 2 screws that secure the display assembly to the computer




Where used: 2 screws that secure the display assembly to the computer



Where used: 3 screws that secure the top cover to the base enclosure




Where used: 3 screws that secure the top cover to the base enclosure




Where used: 3 screws that secure the system board to the base enclosure


Torx T8M2.5×4.0 screw




Color	Quantity	Length	Thread	Head diameter
Black	9	4.0 mm	2.5 mm	5.0 mm



Where used: One screw that secures the optical drive to the computer




Where used: 5 screws that secure the top cover to the base enclosure




Where used:

- (1) One screw that secures the speaker to the base enclosure
- (2) Two screws that secure the fan/heat sink assembly to the base enclosure

Phillips PM2.0×3.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	2	3.0 mm	2.0 mm	4.5 mm




Where used: 2 screws that secure the optical drive bracket to the optical drive

Phillips PM1.5×3.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	1	3.0 mm	1.5 mm	4.0 mm




Where used: One screw that secures the display lid switch module to the display assembly


Torx T6M2.0×5.0 screw



Color	Quantity	Length	Thread	Head diameter
Black	9	5.0 mm	2.0 mm	4.5 mm




Where used: 5 screws that secure the display bezel to the display enclosure




Where used: 4 screws that secure the display panel to the display enclosure

Phillips PM2.0×4.0 screw




Color	Quantity	Length	Thread	Head diameter
Silver	4	4.0 mm	2.0 mm	4.5 mm




Where used: 4 screws that secure the display hinges to the display panel

Phillips PM2.0×2.0 broad-head screw




Color	Quantity	Length	Thread	Heat width
Silver	2	7.0 mm	2.5 mm	7.0 mm




Where used: 2 screws that secure the fingerprint reader board to the top cover

Phillips PM2.0×10.0 screw



Color	Quantity	Length	Thread	Head diameter
Black	2	10.0 mm	2.0mm	4.5 mm



Where used: 2 screws that secure the system board to the base enclosure

8 Backup and recovery

Backup and recovery using Windows Vista

Creating recovery discs

After setting up the computer for the first time, be sure to create a set of recovery discs of the full factory image. The recovery discs are used to start up (boot) the computer and recover the operating system and software to factory settings in case of system instability or failure.

Note the following guidelines before creating recovery discs:

- Use any of the following types of discs: CD-R, DVD+R, DVD+R DL, DVD-R, or DVD-R DL (purchased separately). The discs you use will depend on the type of optical drive installed in your computer. Because DVDs store more information than CDs, DVDs and DVDs with double-layer (DL) support reduce the number of discs required.
- NOTE: Read-write discs, such as CD-RW, DVD+RW, and DVD-RW, are not compatible with the HP Backup & Recovery Manager software.
- The computer must be connected to AC power during the process.
- Only one set of the recovery discs can be created per computer.
- Number each disc before inserting it into the optical drive of the computer.
- If necessary, you can cancel the disc creation before you have finished creating the recovery discs. The next time you select Create a set of recovery discs (Recommended), you will be prompted to continue the disc creation.

To create a set of recovery discs:

- 1. Select Start > All Programs > HP Backup & Recovery > Backup & Recovery Manager.
- Click Next.
- 3. Click Create a set of recovery discs (Recommended), and then click Next.
- Follow the on-screen instructions.

Backing up your information

NOTE: You can only recover files that you have previously backed up. HP recommends that you use HP Backup & Recovery Manager to create an entire drive backup as soon as you set up your computer.

With HP Backup & Recovery Manager, you can perform the following tasks:

- Backing up your information regularly to protect your important system files
- Creating system recovery points that allow you to reverse undesireable changes to your computer by restoring the computer to an earlier state
- Scheduling backups at specific intervals or events

When to back up

- On a regularly scheduled basis
- NOTE: Set reminders to back up your information periodically.
- Before the computer is repaired or restored
- Before you add or modify hardware or software

Backup suggestions

- Create a set of recovery discs using HP Backup & Recovery Manager.
- Create system recovery points using HP Backup & Recovery Manager, and periodically copy them to disc.
- Store personal files in the Documents folder and back up these folders periodically.
- Back up templates stored in their associated programs.
- Save customized settings in a window, toolbar, or menu bar by taking a screen shot of your settings.

The screen shot can be a time saver if you have to reset your preferences.

To copy the screen and paste it into a word-processing document:

- Display the screen. a.
- b. Copy the screen.

To copy only the active window, press alt+fn+prt sc.

To copy the entire screen, press **fn+prt sc**.

- **c.** Open a word-processing document, and then select **Edit > Paste**.
- NOTE: Before you can perform backup and recovery procedures, the computer must be connected to external power.

NOTE: Drivers, utilities, and software installed by HP can be copied to a CD or to a DVD using HP Backup & Recovery Manager.

Backing up specific files or folders

You can back up specific files or folders to the recovery partition on the hard drive, to an optional external hard drive, or to optical discs (CDs or DVDs).

NOTE: This process will take several minutes, depending on the file size and the speed of the computer.

To back up specific files or folders:

- Select Start > All Programs > HP Backup & Recovery > Backup & Recovery Manager.
- 2. Click Next.
- Click Create or manage backups, and then click Next.
- Click Back up user created files and folders, and then click Next.
- Follow the on-screen instructions.

Backing up the entire hard drive

When you perform a complete backup of the hard drive, you are saving the full factory image, including the Windows® operating system, software, and all personal files and folders.

NOTE: A copy of the entire hard drive image can be stored on another hard drive, on a network drive, or on recovery discs that you create.

NOTE: This process may take over an hour, depending on your computer speed and the amount of data being stored.

To back up your entire hard drive:

- Select Start > All Programs > HP Backup & Recovery > Backup & Recovery Manager.
- 2. Click Next.
- 3. Click Create or manage backups, and then click Next.
- 4. Click Create or manage Entire Drive Backups, and then click Next.
- **5**. Follow the on-screen instructions.

Creating recovery points

When you back up modifications since your last backup, you are creating system recovery points. This allows you to save a snapshot of your hard drive at a specific point in time. You can then recover back to that point if you want to reverse subsequent changes made to your system.

NOTE: The first system recovery point, a snapshot of the entire image, is automatically created the first time you perform a backup. Subsequent recovery points make copies of changes made after that time.

HP recommends that you create recovery points at the following times:

- Before you add or extensively modify software or hardware
- Periodically, whenever the system is performing optimally
- NOTE: Recovering to an earlier recovery point does not affect data files or e-mails created since that recovery point.

To create a system recovery point:

- Select Start > All Programs > HP Backup & Recovery > Backup & Recovery Manager.
- 2. Click Next.
- 3. Click Create or manage backups, and then click Next.
- Click Create or manage Recovery Points, and then click Next. 4.
- 5. Follow the on-screen instructions.

Scheduling backups

Use HP Backup Scheduler to schedule backups for the entire system, for recovery points, or for specific files and folders. With this tool, you can schedule backups at specific intervals (daily, weekly, or monthly) or at specific events, such as at system restart or when you dock to an optional docking station (select models only).

To schedule backups:

- Select Start > All Programs > HP Backup & Recovery > HP Backup Scheduler.
- Follow the on-screen instructions.

Performing a recovery

NOTE: You can only recover files that you have previously backed up. HP recommends that you use HP Backup & Recovery Manager to create an entire drive backup as soon as you set up your computer.

HP Backup & Recovery Manager helps you with the following tasks for safeguarding your information and restoring it in case of a system failure:

- Recovering important files—This feature helps you reinstall important files without performing a full system recovery.
- Performing a full system recovery—With HP Backup & Recovery Manager, you can recover your full factory image if you experience system failure or instability. HP Backup & Recovery Manager works from a dedicated recovery partition on the hard drive or from recovery discs you create.

Performing a recovery from the recovery discs

To perform a recovery from the recovery discs, follow these steps:

- 1. Back up all personal files.
- Insert the first recovery disc into the optical drive and restart the computer.
- Follow the on-screen instructions. 3.

Performing a recovery from the hard drive

There are 2 ways to initiate a recovery from the hard drive:

- From within Windows
- From the recovery partition

Initiating a recovery in Windows

To initiate a recovery in Windows, follow these steps:

- 1. Back up all personal files.
- Select Start > All Programs > HP Backup & Recovery > Backup & Recovery Manager.
- 3. Click Next.
- 4. Click **Perform a recovery**, and then click **Next**.
- **5.** Follow the on-screen instructions.

Initiating a recovery from the hard drive recovery partition

To initiate a recovery from the hard drive recovery partition, follow these steps:

- Back up all personal files.
- Restart the computer, and then press f11 before the Windows operating system loads. 2.
- Click a recovery option, and then click **Next**. 3.
- **4.** Follow the on-screen instructions.

Backup and recovery using Windows XP

Creating recovery discs

After setting up the computer for the first time, be sure to create a set of recovery discs of the full factory image. The recovery discs are used to start up (boot) the computer and recover the operating system and software to factory settings in case of system instability or failure.

Note the following guidelines before creating recovery discs:

- Use any of the following types of discs: CD-R, DVD+R, DVD+R DL, DVD-R, or DVD-R DL (purchased separately). The discs you use will depend on the type of optical drive installed in vour computer. Because DVDs store more information than CDs, DVDs and DVDs with doublelayer (DL) support reduce the number of discs required.
- NOTE: Read-write discs, such as CD-RW, DVD+RW, and DVD-RW, are not compatible with the HP Backup and Recovery Manager software.
- The computer must be connected to AC power during the process.
- Only one set of the recovery discs can be created per computer.
- Number each disc before inserting it into the optical drive of the computer.
- If necessary, you can cancel the disc creation before you have finished creating the recovery discs. The next time you select Create factory software recovery CDs or DVDs to recover the system (Highly recommended), you will be prompted to continue the disc creation.

To create a set of recovery discs:

- Select Start > All Programs > HP Backup & Recovery > HP Backup and Recovery Manager.
- 2. Click Next.
- Click Create factory software recovery CDs or DVDs to recover the system (Highly recommended), and then click Next.
- Follow the on-screen instructions.

Backing up your information

NOTE: You can only recover files that you have previously backed up. HP recommends that you use HP Backup and Recovery Manager to create an entire drive backup as soon as you set up your computer.

With HP Backup and Recovery Manager, you can perform the following tasks:

- Backing up your information regularly to protect your important system files
- Creating system recovery points that allow you to reverse undesireable changes to your computer by restoring the computer to an earlier state
- Scheduling backups at specific intervals or events

When to back up

- On a regularly scheduled basis
- NOTE: Set reminders to back up your information periodically.
- Before the computer is repaired or restored
- Before you add or modify hardware or software

Backup suggestions

- Create a set of recovery discs using HP Backup and Recovery Manager.
- Create system recovery points using HP Backup and Recovery Manager, and periodically copy them to disc.
- Store personal files in the My Documents folder and back up these folders periodically.
- Back up templates stored in their associated programs.
- Save customized settings in a window, toolbar, or menu bar by taking a screen shot of your settings.

The screen shot can be a time saver if you have to reset your preferences.

To copy the screen and paste it into a word-processing document:

- Display the screen. a.
- Copy the screen.

To copy only the active window, press alt+fn+prt sc.

To copy the entire screen, press **fn+prt sc**.

- Open a word-processing document, and then select **Edit > Paste**.
- NOTE: Before you can perform backup and recovery procedures, the computer must be connected to external power.

NOTE: Drivers, utilities, and software installed by HP can be copied to a CD or to a DVD using HP Backup and Recovery Manager.

Backing up specific files or folders

You can back up specific files or folders to the recovery partition on the hard drive, to an optional external hard drive, or to optical discs (CDs or DVDs).

NOTE: This process will take several minutes, depending on the file size and the speed of the computer.

To back up specific files or folders:

- Select Start > All Programs > HP Backup & Recovery > HP Backup and Recovery Manager.
- 2. Click Next.
- Click Back up to protect system settings and important data files, and then click Next.

- Click Back up individual files and folders, and then click Next.
- **5**. Follow the on-screen instructions.

Backing up the entire hard drive

When you perform a complete backup of the hard drive, you are saving the full factory image, including the Windows® operating system, software, and all personal files and folders.

NOTE: A copy of the entire hard drive image can be stored on another hard drive, on a network drive, or on recovery discs that you create.

NOTE: This process may take over an hour, depending on your computer speed and the amount of data being stored.

To back up your entire hard drive:

- Select Start > All Programs > HP Backup & Recovery > HP Backup and Recovery Manager.
- Click Next. 2.
- 3. Click Back up to protect system settings and important data files, and then click Next.
- 4. Click Back up entire hard drive, and then click Next.
- 5. Follow the on-screen instructions.

Creating recovery points

When you back up modifications since your last backup, you are creating system recovery points. This allows you to save a snapshot of your hard drive at a specific point in time. You can then recover back to that point if you want to reverse subsequent changes made to your system.

NOTE: The first system recovery point, a snapshot of the entire image, is automatically created the first time you perform a backup. Subsequent recovery points make copies of changes made after that time.

HP recommends that you create recovery points at the following times:

- Before you add or extensively modify software or hardware
- Periodically, whenever the system is performing optimally
- NOTE: Recovering to an earlier recovery point does not affect data files or e-mails created since that recovery point.

To create a system recovery point:

- Select Start > All Programs > HP Backup & Recovery > HP Backup and Recovery Manager.
- Click Next. 2.
- Click Back up to protect system settings and important data files, and then click Next.
- Click Create or manage Recovery Points, and then click Next. 4.
- Follow the on-screen instructions.

Scheduling backups

Use HP Backup Scheduler to schedule backups for the entire system, for recovery points, or for specific files and folders. With this tool, you can schedule backups at specific intervals (daily, weekly, or monthly) or at specific events, such as at system restart or when you dock to an optional docking station (select models only).

To schedule backups:

- Select Start > All Programs > HP Backup & Recovery > HP Backup Scheduler.
- Follow the on-screen instructions.

Performing a recovery

NOTE: You can only recover files that you have previously backed up. HP recommends that you use HP Backup and Recovery Manager to create an entire drive backup as soon as you set up your computer.

HP Backup and Recovery Manager helps you with the following tasks for safeguarding your information and restoring it in case of a system failure:

- Recovering important files—This feature helps you reinstall important files without performing a full system recovery.
- Performing a full system recovery—With HP Backup and Recovery Manager, you can recover your full factory image if you experience system failure or instability. HP Backup and Recovery

Manager works from a dedicated recovery partition on the hard drive or from recovery discs you create.

Performing a recovery from the recovery discs

To perform a recovery from the recovery discs, follow these steps:

- Back up all personal files.
- 2. Insert the first recovery disc into the optical drive and restart the computer.
- Follow the on-screen instructions.

Performing a recovery from the hard drive

There are 2 ways to initiate a recovery from the hard drive:

- From within Windows
- From the recovery partition

Initiating a recovery in Windows

To initiate a recovery in Windows, follow these steps:

- 1. Back up all personal files.
- 2. Select Start > All Programs > HP Backup & Recovery > HP Backup and Recovery Manager.
- 3. Click Next.
- 4. Click Recover important files or the entire system, and then click Next.
- **5.** Follow the on-screen instructions.


Initiating a recovery from the hard drive recovery partition

To initiate a recovery from the hard drive recovery partition, follow these steps:

- Back up all personal files.
- 2. Restart the computer, and then press f11 before the Windows operating system loads.
- Click a recovery option, and then click **Next**. 3.
- 4. Follow the on-screen instructions.


9 Connector pin assignments

Audio-out (headphone)




Pin	Signal
1	Audio out, left channel
2	Audio out, right channel
3	Ground

Audio-in (microphone)




Pin	Signal
1	Audio signal in
2	Audio signal in
3	Ground

External monitor




Pin	Signal
1	Red analog
2	Green analog
3	Blue analog
4	Not connected
5	Ground
6	Ground analog
7	Ground analog
8	Ground analog
9	+5 VDC
10	Ground
11	Monitor detect
12	DDC 2B data
13	Horizontal sync
14	Vertical sync
15	DDC 2B clock

RJ-11 (modem)




Pin	Signal
1	Unused
2	Tip
3	Ring
4	Unused
5	Unused
6	Unused

RJ-45 (network)



Pin	Signal
1	Transmit +
2	Transmit -
3	Receive +
4	Unused
5	Unused
6	Receive -
7	Unused
8	Unused

Universal Serial Bus



Pin	Signal
1	+5 VDC
2	Data -
3	Data +
4	Ground

10 Power cord set requirements

The wide range input feature of the computer permits it to operate from any line voltage from 100 to 120 volts AC or from 220 to 240 volts AC.

The 3-conductor power cord set included with the computer meets the requirements for use in the country or region where the equipment is purchased.

Power cord sets for use in other countries and regions must meet the requirements of the country or region where the computer is used.

Requirements for all countries and regions

The requirements listed below are applicable to all countries and regions:

- The length of the power cord set must be at least 1.5 m (5.0 ft) and no more than 2.0 m (6.5 ft).
- All power cord sets must be approved by an acceptable accredited agency responsible for evaluation in the country or region where the power cord set will be used.
- The power cord sets must have a minimum current capacity of 10 amps and a nominal voltage rating of 125 or 250 V AC, as required by the power system of each country or region.
- The appliance coupler must meet the mechanical configuration of an EN 60 320/IEC 320 Standard Sheet C13 connector for mating with the appliance inlet on the back of the computer.

Requirements for specific countries and regions

Country/region	Accredited agency	Applicable note number
Australia	EANSW	1
Austria	OVE	1
Belgium	CEBC	1
Canada	CSA	2
Denmark	DEMKO	1
Finland	FIMKO	1
France	UTE	1
Germany	VDE	1
Italy	IMQ	1
Japan	METI	3
Korea	EK	4
The Netherlands	KEMA	1
Norway	NEMKO	1
The People's Republic of China	CCC	5
Sweden	SEMKO	1
Switzerland	SEV	1
Taiwan	BSMI	4
The United Kingdom	BSI	1
The United States	UL	2

- 1. The flexible cord must be Type HO5VV-F, 3-conductor, 1.0-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.
- 2. The flexible cord must be Type SPT-3 or equivalent, No. 18 AWG, 3-conductor. The wall plug must be a two-pole grounding type with a NEMA 5-15P (15 A, 125 V) or NEMA 6-15P (15 A, 250 V) configuration.
- 3. The appliance coupler, flexible cord, and wall plug must bear a "T" mark and registration number in accordance with the Japanese Dentori Law. The flexible cord must be Type VCT or VCTF, 3-conductor, 1.00-mm² conductor size. The wall plug must be a two-pole grounding type with a Japanese Industrial Standard C8303 (7 A, 125 V) configuration.
- 4. The flexible cord must be Type RVV, 3-conductor, 0.75-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.
- 5. The flexible cord must be Type VCTF, 3-conductor, 0.75-mm² conductor size. Power cord set fittings (appliance coupler and wall plug) must bear the certification mark of the agency responsible for evaluation in the country or region where it will be used.

11 Recycling

Battery

When a battery has reached the end of its useful life, do not dispose of the battery in general household waste. Follow the local laws and regulations in your area for computer battery disposal.

Display

- ⚠ WARNING! The backlight contains mercury. Exercise caution when removing and handling the backlight to avoid damaging this component and causing exposure to the mercury.
- △ CAUTION: The procedures in this appendix can result in damage to display components. The only components intended for recycling purposes are the liquid crystal display (LCD) panel and the backlight. Careful handling must be exercised when removing these components. When you remove these components, handle them carefully.
- NOTE: Materials Disposal. This HP product contains mercury in the backlight in the display assembly that might require special handling at end-of-life. Disposal of mercury may be regulated because of environmental considerations. For disposal or recycling information, contact your local authorities, or see the Electronic Industries Alliance (EIA) Web site at http://www.eiae.org.


This section provides disassembly instructions for the display assembly. The display assembly must be disassembled to gain access to the backlight (1) and the liquid crystal display (LCD) panel (2).




NOTE: The procedures provided in this appendix are general disassembly instructions. Specific details, such as screw sizes, quantities, and locations, and component shapes and sizes, can vary from one computer model to another.

Perform the following steps to disassemble the display assembly:


1. Remove all screw covers (1) and screws (2) that secure the display bezel to the display assembly.




- 2. Lift up and out on the left and right inside edges (1) and the top and bottom inside edges (2) of the display bezel until the bezel disengages from the display assembly.
- 3. Remove the display bezel (3).




Disconnect all display panel cables (1) from the display inverter and remove the inverter (2).



- Remove all screws (1) that secure the display panel assembly to the display enclosure.
- 6. Remove the display panel assembly (2) from the display enclosure.




- **7**. Turn the display panel assembly upside down.
- 8. Remove all screws that secure the display panel frame to the display panel.




Use a sharp-edged tool to cut the tape (1) that secures the sides of the display panel to the display panel frame.

10. Remove the display panel frame (2) from the display panel.




- **11.** Remove the screws **(1)** that secure the backlight cover to the display panel.
- 12. Lift the top edge of the backlight cover (2) and swing it outward.




- 13. Remove the backlight cover.
- **14.** Turn the display panel right-side up.


15. Remove the backlight cables (1) from the clip (2) in the display panel.




- **16.** Turn the display panel upside down.
- ⚠ WARNING! The backlight contains mercury. Exercise caution when removing and handling the backlight to avoid damaging this component and causing exposure to the mercury.
- 17. Remove the backlight frame from the display panel.




18. Remove the backlight from the backlight frame.



- 19. Disconnect the display panel cable (1) from the LCD panel.
- **20.** Remove the screws **(2)** that secure the LCD panel to the display rear panel.
- **21.** Release the LCD panel **(3)** from the display rear panel.
- 22. Release the tape (4) that secures the LCD panel to the display rear panel.



23. Remove the LCD panel.



24. Recycle the LCD panel and backlight.

Index

Symbols/Numerics 1394a port 14	Bluetooth module compartment cover	computer feet locations 40
A	illustrated 25	spare part number 21, 32, 40
AC adenter energ part	removal 43	Computer Setup
AC adapter, spare part	boot options 84	accessing 80
number 27, 29	boot order 84	Diagnostics menu 83
ambient light sensor 5	bottom components 16	File menu 82
antennae, disconnecting 50, 54	business-card holder 17	navigating and selecting 81
audio, product description 2	buttons	restoring factory settings 81
audio-in jack	info 6	Security menu 83
location 14, 15	power 6	System Configuration
pin assignments 126	presentation 6	menu 84
audio-out jack	TouchPad on/off 7	using 81
location 14, 15	volume mute 7	computer specifications 86
pin assignments 126	wireless 6	connectors
		docking 14, 15
В	C	service considerations 35
backing up 114, 120	Cable Kit	creating recovery points 117, 123
backup	contents 26	
files and folders 115, 121	spare part number 24, 26, 31	D
hard drive 116, 122	cables, service considerations 35	Diagnostics menu 83
modifications made to the	capacity board cable 26	Disk Sanitizer 83
system 117, 123	caps lock light 8	diskette drive
scheduling 117, 123	carrying case, spare part	precautions 35
base enclosure, spare part	number 28	product description 2
number 21, 31	chipset, product description 1	spare part number 28
battery	CMOS clearing 39	display assembly
location 16	components	removal 62
removal 41	bottom 16	spare part number 19, 32, 62
spare part numbers 21, 31, 41	buttons 6	display bezel
battery bay 16	display 5	removal 64
battery latches 16	fingerprint reader 6	spare part number 19, 32, 65
battery light 8, 11	front 11	display component recycling 132
Bluetooth module	keys 7	display components 5
location 11	left-side 12	display enclosure, spare part
removal 43	lights 8	number 20, 32
spare part number 24, 31, 43	pointing devices 10	display hinge
Bluetooth module cable 26	rear 13	removal 65
Bluetooth module	right-side 14	spare part number 20, 32, 66
compartment 17	top 6	

removal 63	location 14, 15	HP Extended Life Battery, spare part number 27
spare part number 20, 32	pin assignments 127	HP Fingerprint Sensor 7
display panel cable, spare part number 19, 32	External MultiBay II power cable and stand, spare part	1
display panel, removal 65	number 27	I/O address specifications 94
display release latch 5, 11	External MultiBay II, spare part	info button 6
Display Screw Kit, spare part	number 27	interrupt specifications 93
number 20, 32	-	J
display specifications 87	F	
display switch 5	fan/heat sink assembly	jacks
docking connector 14, 15	removal 74	audio-in 14, 15
docking station, spare part	spare part number 21, 32, 74	audio-out 14, 15
numbers 27, 29, 33	feet	headphone 14, 15
docking support, product	locations 40	microphone 14, 15
description 3	spare part number 21, 32, 40	modem 12
drive light 8, 11	File menu 82	network 13
DriveLock password 83	fingerprint reader board cable 26	RJ-11 12
drives	fn key 7	RJ-45 13
boot order 84	front components 11	
preventing damage 35	function keys 7	K
DVD-ROM Drive		keyboard
precautions 35	G	product description 4
removal 56	graphics, product description 1	removal 59
spare part	grounding equipment and	spare part numbers 20, 32, 59
numbers 21, 27, 32, 56	methods 38	keypad keys 7
specifications 91		keys
DVD/CD-RW Combo Drive	Н	esc 7
precautions 35	hard drive	fn 7
removal 56	location 16	function 7
spare part	precautions 35	keypad 7
number 21, 27, 32, 56	product description 2	Windows applications 7
specifications 90	removal 52	Windows logo 7
DVD±RW and CD-RW Combo	spare part	
Drive	numbers 24, 27, 32, 33, 52	L
precautions 35	specifications 88	Label Kit, spare part
removal 56	hard drive backup 116, 122	number 27, 32
spare part	hard drive bay 16	LAN Power Save 84
number 21, 27, 32, 56	hard drive bracket, removal 53	language, changing in Computer
specifications 89	hard drive cover	Setup 84
opcomoduciie co	illustrated 25	LED cable 26
E	removal 52	left-side components 12
electrostatic discharge 36	hard drive recovery 118, 124	legacy support, Universal Serial
esc key 7	hard drive test 83	Bus (USB) 80, 84
Ethernet, product description 2	headphone jack	lights
Execution Disable 84	location 14, 15	battery 8, 11
external media cards, product	pin assignments 126	caps lock 8
description 3	hinge	drive 8, 11
accomplicit o	removal 65	num lock 9
	spare part number 20, 32, 66	power 8, 11
	20, 02, 00	volume down 9

volume mute 9	spare part	monitor port 14, 15
volume up 9	numbers 21, 27, 32, 56	product description 3
wireless 8, 11	specifications 89, 90, 91	Universal Serial Bus
	optical drive light 12	(USB) 12, 14, 15
M		power button 6
mass storage devices, spare part	P	power connector 12
numbers 27	packing guidelines 37	power cord
Media Card Reader 14	panels, product description 1	set requirements 130
memory check 83	parallel port mode 84	·
•	•	spare part numbers 28, 29
memory map specifications 96	password clearing 39	power light 8, 11
memory module	passwords 83	power requirements, product
product description 1	PC Card assembly	description 4
removal 45	removal 76	power-on password 83
spare part numbers 24, 32, 45	spare part number 21, 32, 76	presentation button 6
memory module/WLAN module	PC Card slot 14	processor, product description 1
compartment 16	PC Card slot bezel, illustrated 25	product description
memory module/WLAN module	pin assignments	audio 2
compartment cover	audio-in jack 126	chipset 1
illustrated 25	audio-out jack 126	diskette drive 2
removal 45	external monitor port 127	docking support 3
microphone 5	headphone jack 126	Ethernet 2
microphone jack	microphone jack 126	external media cards 3
location 14, 15	modem jack 128	graphics 1
pin assignments 126	monitor port 127	hard drives 2
modem cable 26	network jack 128	keyboard 4
modem jack	RJ-11 128	memory module 1
location 12	RJ-45 jack 128	modem module 2
pin assignments 128	Universal Serial Bus (USB)	operating system 4
modem module	port 129	optical drives 2
product description 2	plastic parts 34	panels 1
removal 78	Plastics Kit	•
spare part numbers 21, 31, 78	contents 25	pointing devices 4
		ports 3
monitor port	spare part number 21, 25, 32	power requirements 4
location 14, 15	pointing device components	processors 1
pin assignments 127	illustrated 10	security 4
NI.	pointing stick 10	serviceability 4
N	pointing stick buttons 10	wireless 2
navigating in Computer Setup 81	TouchPad 10	_
network jack	TouchPad buttons 10	R
location 13	TouchPad on/off button 10	rear components 13
pin assignments 128	TouchPad scroll zone 10	recovery discs
num lock light 9	pointing devices, product	creating 114, 120
	description 4	using 118, 124
0	pointing stick 10	recovery partition 119, 125
operating system, product	pointing stick buttons 10	recovery points 117, 123
description 4	pointing stick cable	removal/replacement
optical drive	removal 61	preliminaries 34
location 12	ports	procedures 40
precautions 35	1394a 14	restoring Computer Setup factory
product description 2	external monitor port 14, 15	settings 81
removal 56	,	3. 2.

right-side components 14 RJ-11 jack location 12 pin assignments 128 RJ-45 jack location 13 pin assignments 128 RTC battery removal 47 spare part number 24, 31, 47 Rubber Kit, spare part	static-shielding materials 38 stringent security 83 switch cover removal 57 spare part number 20, 31, 57 system backup 116, 122 system board removal 70 spare part numbers 21, 31, 33, 70 System Configuration menu 84	wireless antennae, disconnecting 50, 54 wireless button 6 wireless light 8, 11 wireless, product description 2 WLAN module removal 48 spare part numbers 21, 29, 48 workstation guidelines 37 WWAN module removal 54
number 21, 32	system DMA 92 system fan 84	spare part numbers 24, 31, 54 WWAN module compartment 17
S	system information 82	WWAN module compartment
scheduling backups 117, 123	system memory map 96	cover
Screw Kit	system recovery points 117, 123	illustrated 25
contents 97	_	removal 54
spare part number 28, 32	T thermal material replacement 75	
screw listing 97 security cable slot 13	thermal material, replacement 75 tools required 34	
Security menu 83	top components 6	
security, product description 4	top cover	
selecting in Computer Setup 81	removal 67	
serial number 18, 40	spare part number 21, 31, 67	
service considerations 34	TouchPad 10	
serviceability, product	TouchPad buttons 10	
description 4	TouchPad on/off button 7, 10 TouchPad scroll zone 10	
SIM slot 16 SIM, removal 42	TouchPad scroll zone 10 transporting guidelines 37	
smart card reader module, spare	transporting galdelines of	
part number 24, 32	U	
smart card security 83	Universal Serial Bus (USB) legacy	
speaker 16	support 84	
speaker assembly	Universal Serial Bus (USB) port	
removal 73	location 14, 15	
spare part number 21, 32, 73 specifications	pin assignments 129 unknown password 39	
computer 86	USB legacy support 80	
display 87	Cob logacy cappoint of	
DVD-ROM Drive 91	V	
DVD/CD-RW Combo Drive 90	vents 12, 14, 15, 16	
DVD±RW and CD-RW Combo	volume down light 9	
Drive 89	volume mute button 7	
hard drive 88	volume mute light 9	
I/O addresses 94	volume scroll zone 7 volume up light 9	
interrupts 93 memory map 96	volume up light 9	
optical drive 89, 90, 91	W	
system DMA 92	Windows applications key 7	
startup check 83	Windows logo key 7	
•		