

Technical Whitepaper

Installing Windows 7 through USB Type C

April 2016
901238-001



Table of contents

1 Introduction.....	3
2 Drivers and updates	4
2.1 USB 3.1 driver.....	4
2.2 Windows updates.....	4
3 Procedure overview	5
4 Modifying install.wim	6
5 Modifying boot.wim	7

1 Introduction

Windows 7 does not come with built-in USB 3.1 drivers support during install. Since the drivers are missing, once you boot into the OS installation set up, the communication through the USB type C port is lost.

This guide provides instructions on how to prepare to install Windows 7 through a USB Type C port.

2 Drivers and updates

The following driver and Windows updates will be needed for this process:

2.1 USB 3.1 driver

Download Intel® USB 3.1 eXtensible Host Controller v15.2.30.250. This package provides drivers for Alpine Ridge USB3.1 Controller for Windows 7:

- Intel(R) USB 3.1 eXtensible Host Controller Driver
- Intel(R) USB 3.1 Hub Driver

The drivers are available on **HP Support**: (<http://support.hp.com/us-en/>)

2.2 Windows updates

- KB2990941 (<https://support.microsoft.com/en-us/kb/2990941>)
- KB3087873 (<https://support.microsoft.com/en-us/kb/3087873>)

3 Procedure overview

1. Download and extract the USB 3.1 drivers (see [Drivers and updates on page 4](#)).
2. Download and extract the Windows updates (see [Windows updates on page 4](#)).

NOTE: The downloaded drivers and updates should be placed in a location on your system that is easy to find or remember.

3. Create a bootable Windows 7 image on a USB flash drive.
4. With the bootable Windows 7 flash drive inserted, launch the Windows Command Prompt.

NOTE: You must run the Command Prompt as an Administrator.

5. Follow the steps to modify the **install.wim** (see [Modifying install.wim on page 6](#)) and **boot.wim** files (see [Modifying boot.wim on page 7](#)).
6. Eject and remove the USB flash drive, then attach it to the computer on which Windows 7 will be installed using a USB Type C-to-USB Type A dongle.
7. Turn on or restart the computer and enter the system BIOS by pressing the **f10** key when the HP logo appears, then make the following modifications.
 - a. Turn fast boot off
 - b. Change USB settings to No Security
 - c. Enable Legacy boot
 - d. Disable Secure boot
8. Save changes, restart the system, and enter the boot menu by pressing the **f9** key when the HP logo appears.
9. Select "Legacy boot" from the options provided.
10. Follow the on-screen instructions to install Windows 7.

4 Modifying install.wim

Using the command prompt as Administrator, enter the following commands:

1. Type the following command to get the WIM index information.

```
Dism /Get-WimInfo /WimFile:<install_wim_file>
```

NOTE: <install_wim_file> is the path to the **install.wim** (usually d:\sources\install.wim).

An index or name value is required for most operations that specify a WIM file. Note the index number of the windows version you are installing.

2. Create a directory to mount the windows image.

```
MD <mount_directory1>
```

EXAMPLE: MD C:\temp\installw7

3. Mount install.wim to the directory created in step 2.

```
DISM /Mount-Wim /WimFile: <install_wim_file> /name: "<Name>" /MountDir:<mount_directory1>
```

For <Name>, fill in the name of the Windows version, i.e. "Windows 7 Professional."

4. Apply the update package (.msu) file:

```
DISM /image: <mount_directory1> /Add-Package /Packagepath: <msu_file>
```

NOTE: <msu_file> is the path to each one of the updates KB2990941 and KB3087873 (see [Windows updates on page 4](#) and [Procedure overview on page 5](#)). You will need to run this step twice, once for each update package.

5. Inject the downloaded USB 3.1 drivers (see [USB 3.1 driver on page 4](#)).

```
Dism /Image:<mount_directory1> /Add-Driver /Driver:<driver_folder> /Recurse /forceunsigned
```

<driver_folder> is the location of the USB 3.1 drivers on the flash drive (see [Procedure overview on page 5](#)).

6. Unmount the **install.wim**.

```
Dism /Unmount-Wim /MountDir:<mount_directory1> /Commit
```

5 Modifying boot.wim

Using the command prompt as Administrator, enter the following commands:

1. Type the following command to get the WIM index information.

```
Dism /Get-WimInfo /WimFile:<boot_wim_file>
```

NOTE: <boot_wim_file> is the path to the **boot.wim** (usually d:\sources\boot.wim).

An index or name value is required for most operations that specify a WIM file. Note the index number of the windows version you are installing.

2. Create a directory to mount the windows image.

```
MD <mount_directory1>
```

EXAMPLE: MD C:\temp\bootw7

3. Mount boot.wim to the directory created in step 2.

```
DISM /Mount-Wim /WimFile: <boot_wim_file> /index:2 /MountDir:<mount_directo
```

4. Inject the downloaded USB 3.1 drivers (see [USB 3.1 driver on page 4](#)).

```
Dism /Image:<mount_directory1> /Add-Driver /Driver:<driver_folder> /Recurse  
/forceunsigned
```

<driver_folder> is the location of the USB 3.1 drivers on the flash drive (see [Procedure overview on page 5](#)).

5. Unmount the **boot.wim**.

```
Dism /Unmount-Wim /MountDir:<mount_directory2> /Commit
```